



Ultimaker 3 Extended

Specification sheet



Specifications

Printer and Printing Properties

Technology	Fused Filament Fabrication
Print head	Dual nozzle, with lifting mechanism on 2nd nozzle. Easily swappable printcores. Left nozzle: 215x215x300mm Right nozzle: 215x215x300mm Dual material: 197x215x300mm
Build volume	2.85 mm
Filament diameter	0.4mm nozzle: 20 - 200 micron
Layer resolution	12.5, 12.5, 2.5 micron
Step accuracy X, Y, Z	30 - 300 mm/s
Print head travel speed	0.40: up to 16mm ³ /s
Material flow speed	Heated glass bed
Build plate	PLA, PVA, ABS, CPE, Nylon
Material types	0.4mm
Nozzle diameter	180 - 280 °C
Nozzle temperature	20 - 100 °C
Build plate temperature	< 2 min
Nozzle heat up time	< 4 min (20 - > 60 °C)
Build plate heat up time	50 dBA
Average operation noise	Easily swappable printcores
Nozzle replacement	Open, reel holder incl guide for 2 spools of 750g
Filament storage	NFC system to automatically detect material type
Connectivity	Wifi, ethernet, stand alone via USB-drive
Bed levelling	Active leveling
Camera	Yes

Physical dimensions

Printer outer dimensions (incl bowden tube and spoolholder)	49,3 x 33,8 x 68,8 cm
Printer outer dimensions (excl bowden tube and spoolholder)	35,7 x 33,8 x 48,8 cm
Nett weight	11,3 kg
Shipping weight	16,2 kg
Shipping box dimensions	40,0 x 39,0 x 68,0 cm

Power requirements

Input	100 - 240V 4A, 50-60Hz 221 W max.
Output	24 V DC, 9.2 A

Ambient conditions

Ambient operating conditions	15 - 32 °C, 10 - 90% RH non condensing Refer to material specs for optimal operating conditions
Storage conditions printer	0 - 32 °C

Software

Supplied software	Cura 2 - Official Ultimaker Software
Supported OS	Windows, Mac, Linux
File types	STL, OBJ, 3MF
File transfer	Print direct from Cura via Network, Stand alone USB drive printing