

TOSHIBA CMOS Digital Integrated Circuit Silicon Monolithic

TC7SP3066TU, TC7SP3067TU

TC7SP3066TU Low Voltage Dual Supply Single Bus Switch (analog)


TC7SP3067TU Low Voltage Dual Supply Single Bus Switch (analog)

The TC7SP3066 and TC7SP3067 are high-speed CMOS one-bit analog bus switches with separate power supplies for control and switch portions. In the TC7SP3066, the switch is on when Output Enable (OE) is High. In the TC7SP3067, the switch is on when Output Enable (\overline{OE}) is Low.

The TC7SP3066 and TC7SP3067 support power-down protection by incorporating 3.6-V-tolerant control inputs.

These devices are suitable for applications where the control voltage is lower than the signal line voltage.

All inputs are equipped with protection circuits against static discharge or transient excess voltage.




Weight: 0.007 g (typ.)

Features

- Operating voltage range:
 - $V_{CCA} = 1.1$ to 2.7 V (Control portion)
 - $V_{CCB} = 1.65$ to 3.6 V (Switch portion)
- ON-resistance: $R_{ON} = 8 \Omega$ (max) ($V_{CCB} = 2.7$ V)
 $R_{ON} = 10 \Omega$ (max) ($V_{CCB} = 2.3$ V)
- ESD performance: Machine model $\geq \pm 200$ V
Human body model $\geq \pm 2000$ V
- Ultra-small package: UF6
- 3.6-V tolerance function and power-down protection at the Output Enable input.



Pin Assignment (top view)



Truth Table

Input (3066)	Function	Input (3067)	Function
OE		$\overline{\text{OE}}$	
H	Aport = Bport	H	Disconnected
L	Disconnected	L	Aport = Bport

Circuit Schematic



Absolute Maximum Ratings (Note 1)

Characteristics	Symbol	Rating	Unit
Power supply voltage (Note 2)	V_{CCA}	-0.5 to 4.6	V
	V_{CCB}	-0.5 to 4.6	
Control input voltage (OE (3066)/ OE (3067))	V_{IN}	-0.5 to 4.6	V
Switch input/output voltage	V_S	-0.5 to $V_{CCB} + 0.5$	V
Diode current in the control portion	I_{IK}	-25	mA
Diode current in the switch portion	I_{IK}	±50 (Note 3)	mA
Switch input/output current	I_S	128	mA
DC V_{CC} /ground current	I_{CCA}	±50	mA
	I_{CCB}	±100	
Power dissipation	P_D	200	mW
Storage temperature	T_{stg}	-65 to 150	°C

Note 1: Exceeding any of the absolute maximum ratings, even briefly, lead to deterioration in IC performance or even destruction.

Using continuously under heavy loads (e.g. the application of high temperature/current/voltage and the significant change in temperature, etc.) may cause this product to decrease in the reliability significantly even if the operating conditions (i.e. operating temperature/current/voltage, etc.) are within the absolute maximum ratings and the operating ranges.

Please design the appropriate reliability upon reviewing the Toshiba Semiconductor Reliability Handbook ("Handling Precautions"/"Derating Concept and Methods") and individual reliability data (i.e. reliability test report and estimated failure rate, etc).

Note 2: Do not supply a voltage to the V_{CCB} pin when V_{CCA} is in the OFF state.

Note 3: $V_S < GND$, $V_S > V_{CCB}$

Operating Ranges (Note)

Characteristics	Symbol	Rating	Unit
Power supply voltage	V_{CCA}	1.1 to 2.7	V
	V_{CCB}	1.65 to 3.6	
Control input voltage	V_{IN}	0 to 3.6	V
Switch input/output voltage	V_S	0 to V_{CCB}	V
Operating temperature	T_{opr}	-40 to 85	°C
Control input rise and fall times	dt/dv	0 to 10	ns/V

Note: The operating ranges must be maintained to ensure the normal operation of the device. Unused inputs must be tied to either V_{CCA} or GND.

Electrical Characteristics

DC Characteristics (1.1 V ≤ V_{CCA} ≤ 2.7 V, 1.65 V ≤ V_{CCB} ≤ 3.6 V)

Characteristics	Symbol	Test Condition		V _{CCA} (V)	V _{CCB} (V)	Ta = -40 to 85°C		Unit
						Min	Max	
High-level input voltage	V _{IH}	OE (3066), \overline{OE} (3067)		1.1 ≤ V _{CCA} < 1.4	1.65 to 3.6	0.70 × V _{CCA}	—	V
				1.4 ≤ V _{CCA} < 1.65	1.65 to 3.6	0.70 × V _{CCA}	—	V
				1.65 ≤ V _{CCA} < 2.3	2.3 to 3.6	0.70 × V _{CCA}	—	V
				2.3 ≤ V _{CCA} ≤ 2.7	2.7 to 3.6	1.6	—	V
Low-level input voltage	V _{IL}	OE (3066), \overline{OE} (3067)		1.1 ≤ V _{CCA} < 1.4	1.65 to 3.6	—	0.30 × V _{CCA}	V
				1.4 ≤ V _{CCA} < 1.65	1.65 to 3.6	—	0.30 × V _{CCA}	V
				1.65 ≤ V _{CCA} < 2.3	2.3 to 3.6	—	0.30 × V _{CCA}	V
				2.3 ≤ V _{CCA} ≤ 2.7	2.7 to 3.6	—	0.7	V
ON-resistance (Note)	R _{ON}	V _{IS} = 0 V	I _S = 30 mA	1.1 to 2.7	2.7	—	8	Ω
		V _{IS} = 2.7 V	I _S = 30 mA	1.1 to 2.7	2.7	—	12	
		V _{IS} = 2.1 V	I _S = 15 mA	1.1 to 2.7	2.7	—	20	
		V _{IS} = 0 V	I _S = 24 mA	1.1 to 2.3	2.3	—	10	
		V _{IS} = 2.3 V	I _S = 24 mA	1.1 to 2.3	2.3	—	15	
		V _{IS} = 2.0 V	I _S = 15 mA	1.1 to 2.3	2.3	—	25	
Switch-off leakage current	I _{SZ}	A1, B1 = 0 to V _{CCB} \overline{OE} = V _{CCA} , OE = GND		1.1 to 2.7	1.65 to 3.6	—	±2.0	μA
Control input current	I _{IN}	\overline{OE} or OE = 0 to 3.6 V		1.1 to 2.7	1.65 to 3.6	—	±1.0	μA
Quiescent supply current	I _{CCA}	V _{IN} = V _{CCA} or GND, I _S = 0 A		1.1 to 2.7	1.65 to 3.6	—	4.0	μA
	I _{CCB}	V _{IN} = V _{CCA} or GND, I _S = 0 A		1.1 to 2.7	1.65 to 3.6	—	4.0	
	I _{CCA}	V _{CCA} ≤ V _{IN} ≤ 3.6 V, I _S = 0 A		1.1 to 2.7	1.65 to 3.6	—	4.0	
	I _{CCB}	V _{CCA} ≤ V _{IN} ≤ 3.6 V, I _S = 0 A		1.1 to 2.7	1.65 to 3.6	—	4.0	

Note: ON-resistance is measured by measuring the voltage drop across the switch at the indicated current. V_{IS} is defined as the lower voltage at the A and B pins.

AC Characteristics (Ta = -40 to 85°C, Input: tr = tf = 2.0 ns)

VCCA = 2.5 ± 0.2 V, VCCB = 3.3 ± 0.3 V

Characteristics	Symbol	Test Condition	Min	Max	Unit
Propagation delay time (bus to bus)	t _{pLH} t _{pHL}	Figures 1 and 2 (Note)	—	0.25	ns
3-state output enable time	t _{pZL} t _{pZH}	Figures 1 and 3	—	7	
3-state output disable time	t _{pLZ} t _{pHZ}	Figures 1 and 3	—	7	

Note: Calculated from the RC time constant of the ON-resistance of the output and the capacitive load.

VCCA = 1.8 ± 0.15 V, VCCB = 3.3 ± 0.3 V

Characteristics	Symbol	Test Condition	Min	Max	Unit
Propagation delay time (bus to bus)	t _{pLH} t _{pHL}	Figures 1 and 2 (Note)	—	0.25	ns
3-state output enable time	t _{pZL} t _{pZH}	Figures 1 and 3	—	9	
3-state output disable time	t _{pLZ} t _{pHZ}	Figures 1 and 3	—	9	

Note: Calculated from the RC time constant of the ON-resistance of the output and the capacitive load.

VCCA = 1.5 ± 0.1 V, VCCB = 3.3 ± 0.3 V

Characteristics	Symbol	Test Condition	Min	Max	Unit
Propagation delay time (bus to bus)	t _{pLH} t _{pHL}	Figures 1 and 2 (Note)	—	0.25	ns
3-state output enable time	t _{pZL} t _{pZH}	Figures 1 and 3	—	12	
3-state output disable time	t _{pLZ} t _{pHZ}	Figures 1 and 3	—	12	

Note: Calculated from the RC time constant of the ON-resistance of the output and the capacitive load.

VCCA = 1.2 ± 0.1 V, VCCB = 3.3 ± 0.3 V

Characteristics	Symbol	Test Condition	Min	Max	Unit
Propagation delay time (bus to bus)	t _{pLH} t _{pHL}	Figures 1 and 2 (Note)	—	0.25	ns
3-state output enable time	t _{pZL} t _{pZH}	Figures 1 and 3	—	20	
3-state output disable time	t _{pLZ} t _{pHZ}	Figures 1 and 3	—	20	

Note: Calculated from the RC time constant of the ON-resistance of the output and the capacitive load.

$$V_{CCA} = 1.8 \pm 0.15 \text{ V}, V_{CCB} = 2.5 \pm 0.2 \text{ V}$$

Characteristics	Symbol	Test Condition	Min	Max	Unit
Propagation delay time (bus to bus)	t_{pLH} t_{pHL}	Figures 1 and 2 (Note)	—	0.61	ns
3-state output enable time	t_{pZL} t_{pZH}	Figures 1 and 3	—	11	
3-state output disable time	t_{pLZ} t_{pHZ}	Figures 1 and 3	—	11	

Note: Calculated from the RC time constant of the ON-resistance of the output and the capacitive load.

$$V_{CCA} = 1.5 \pm 0.1 \text{ V}, V_{CCB} = 2.5 \pm 0.2 \text{ V}$$

Characteristics	Symbol	Test Condition	Min	Max	Unit
Propagation delay time (bus to bus)	t_{pLH} t_{pHL}	Figures 1 and 2 (Note)	—	0.61	ns
3-state output enable time	t_{pZL} t_{pZH}	Figures 1 and 3	—	12	
3-state output disable time	t_{pLZ} t_{pHZ}	Figures 1 and 3	—	12	

Note: Calculated from the RC time constant of the ON-resistance of the output and the capacitive load.

$$V_{CCA} = 1.2 \pm 0.1 \text{ V}, V_{CCB} = 2.5 \pm 0.2 \text{ V}$$

Characteristics	Symbol	Test Condition	Min	Max	Unit
Propagation delay time (bus to bus)	t_{pLH} t_{pHL}	Figures 1 and 2 (Note)	—	0.61	ns
3-state output enable time	t_{pZL} t_{pZH}	Figures 1 and 3	—	17	
3-state output disable time	t_{pLZ} t_{pHZ}	Figures 1 and 3	—	17	

Note: Calculated from the RC time constant of the ON-resistance of the output and the capacitive load.

$$V_{CCA} = 1.2 \pm 0.1 \text{ V}, V_{CCB} = 1.8 \pm 0.15 \text{ V}$$


Characteristics	Symbol	Test Condition	Min	Max	Unit
Propagation delay time (bus to bus)	t_{pLH} t_{pHL}	Figures 1 and 2 (Note)	—	1.15	ns
3-state output enable time	t_{pZL} t_{pZH}	Figures 1 and 3	—	25	
3-state output disable time	t_{pLZ} t_{pHZ}	Figures 1 and 3	—	25	

Note: Calculated from the RC time constant of the ON-resistance of the output and the capacitive load.

Capacitive Characteristics (Ta = 25°C)

Characteristics	Symbol	Test Condition	VCCB (V)		Typ.	Unit
			VCCA (V)	VCCB (V)		
Control input capacitance	C _{IN}		2.5	3.3	7	pF
Switch input/output capacitance	C _{I/O}	$\overline{OE} = V_{CCA}, OE = GND$	2.5	3.3	10	pF

AC Test Circuit



Parameter	Switch
t _{pLH} , t _{pHL}	Open
t _{pLZ} , t _{pZL}	6.0 V @ V _{CCB} = 3.3 ± 0.3 V
	V _{CCB} × 2 @ V _{CCB} = 2.5 ± 0.2 V
	@ V _{CCB} = 1.8 ± 0.15 V
t _{pHZ} , t _{pZH}	GND

Symbol	V _{CCB} (output)	
	3.3 ± 0.3 V 2.5 ± 0.2 V	1.8 ± 0.15 V
R _L	500 Ω	1 kΩ
C _L	30 pF	30 pF

Figure 1

AC Test Waveform




Figure 2 t_{pLH} , t_{pHL}





Figure 3 t_{pLZ} , t_{pHZ} , t_{pZL} , t_{pZH}

	Symbol	V_{CCA} or V_{CCB}		
		3.3 ± 0.3 V	2.5 ± 0.2 V 1.8 ± 0.15 V	1.5 ± 0.1 V 1.2 ± 0.1 V
Input	V_{IH}	—	V_{CCA}	V_{CCA}
	V_{IM}	—	$V_{CCA}/2$	$V_{CCA}/2$
Output	V_{OM}	$V_{OH}/2$	$V_{OH}/2$	—
	V_X	$V_{OL} + 0.3$ V	$V_{OL} + 0.15$ V	—
	V_Y	$V_{OH} - 0.3$ V	$V_{OH} - 0.15$ V	—

Package Dimensions

UF6

Unit: mm



Weight: 0.007 g (typ.)

RESTRICTIONS ON PRODUCT USE

- Toshiba Corporation, and its subsidiaries and affiliates (collectively "TOSHIBA"), reserve the right to make changes to the information in this document, and related hardware, software and systems (collectively "Product") without notice.
- This document and any information herein may not be reproduced without prior written permission from TOSHIBA. Even with TOSHIBA's written permission, reproduction is permissible only if reproduction is without alteration/omission.
- Though TOSHIBA works continually to improve Product's quality and reliability, Product can malfunction or fail. Customers are responsible for complying with safety standards and for providing adequate designs and safeguards for their hardware, software and systems which minimize risk and avoid situations in which a malfunction or failure of Product could cause loss of human life, bodily injury or damage to property, including data loss or corruption. Before creating and producing designs and using, customers must also refer to and comply with (a) the latest versions of all relevant TOSHIBA information, including without limitation, this document, the specifications, the data sheets and application notes for Product and the precautions and conditions set forth in the "TOSHIBA Semiconductor Reliability Handbook" and (b) the instructions for the application that Product will be used with or for. Customers are solely responsible for all aspects of their own product design or applications, including but not limited to (a) determining the appropriateness of the use of this Product in such design or applications; (b) evaluating and determining the applicability of any information contained in this document, or in charts, diagrams, programs, algorithms, sample application circuits, or any other referenced documents; and (c) validating all operating parameters for such designs and applications. **TOSHIBA ASSUMES NO LIABILITY FOR CUSTOMERS' PRODUCT DESIGN OR APPLICATIONS.**
- Product is intended for use in general electronics applications (e.g., computers, personal equipment, office equipment, measuring equipment, industrial robots and home electronics appliances) or for specific applications as expressly stated in this document. Product is neither intended nor warranted for use in equipment or systems that require extraordinarily high levels of quality and/or reliability and/or a malfunction or failure of which may cause loss of human life, bodily injury, serious property damage or serious public impact ("Unintended Use"). Unintended Use includes, without limitation, equipment used in nuclear facilities, equipment used in the aerospace industry, medical equipment, equipment used for automobiles, trains, ships and other transportation, traffic signaling equipment, equipment used to control combustions or explosions, safety devices, elevators and escalators, devices related to electric power, and equipment used in finance-related fields. Do not use Product for Unintended Use unless specifically permitted in this document.
- Do not disassemble, analyze, reverse-engineer, alter, modify, translate or copy Product, whether in whole or in part.
- Product shall not be used for or incorporated into any products or systems whose manufacture, use, or sale is prohibited under any applicable laws or regulations.
- The information contained herein is presented only as guidance for Product use. No responsibility is assumed by TOSHIBA for any infringement of patents or any other intellectual property rights of third parties that may result from the use of Product. No license to any intellectual property right is granted by this document, whether express or implied, by estoppel or otherwise.
- **ABSENT A WRITTEN SIGNED AGREEMENT, EXCEPT AS PROVIDED IN THE RELEVANT TERMS AND CONDITIONS OF SALE FOR PRODUCT, AND TO THE MAXIMUM EXTENT ALLOWABLE BY LAW, TOSHIBA (1) ASSUMES NO LIABILITY WHATSOEVER, INCLUDING WITHOUT LIMITATION, INDIRECT, CONSEQUENTIAL, SPECIAL, OR INCIDENTAL DAMAGES OR LOSS, INCLUDING WITHOUT LIMITATION, LOSS OF PROFITS, LOSS OF OPPORTUNITIES, BUSINESS INTERRUPTION AND LOSS OF DATA, AND (2) DISCLAIMS ANY AND ALL EXPRESS OR IMPLIED WARRANTIES AND CONDITIONS RELATED TO SALE, USE OF PRODUCT, OR INFORMATION, INCLUDING WARRANTIES OR CONDITIONS OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE, ACCURACY OF INFORMATION, OR NONINFRINGEMENT.**
- Do not use or otherwise make available Product or related software or technology for any military purposes, including without limitation, for the design, development, use, stockpiling or manufacturing of nuclear, chemical, or biological weapons or missile technology products (mass destruction weapons). Product and related software and technology may be controlled under the Japanese Foreign Exchange and Foreign Trade Law and the U.S. Export Administration Regulations. Export and re-export of Product or related software or technology are strictly prohibited except in compliance with all applicable export laws and regulations.
- Please contact your TOSHIBA sales representative for details as to environmental matters such as the RoHS compatibility of Product. Please use Product in compliance with all applicable laws and regulations that regulate the inclusion or use of controlled substances, including without limitation, the EU RoHS Directive. TOSHIBA assumes no liability for damages or losses occurring as a result of noncompliance with applicable laws and regulations.