

AUDIO FREQUENCY POWER AMPLIFIER
LOW SPEED SWITCHING


FEATURES

- Complementary to KTD1882.

MAXIMUM RATING (Ta=25℃)

CHARACTERISTIC		SYMBOL	RATING	UNIT
Collector-Base Voltage		V_{CBO}	-40	V
Collector-Emitter Voltage		V_{CEO}	-30	V
Emitter-Base Voltage		V_{EBO}	-5	V
Collector Current	DC	I_C	-3	A
	Pulse (Note)	I_{CP}	-7	
Base Current (DC)		I_B	-0.6	A
Collector Power Dissipation		P_C	625	mW
Junction Temperature		T_j	150	℃
Storage Temperature Range		T_{stg}	-55 ~ 150	℃

Note : Pulse Width $\leq 10\text{ms}$, Duty Cycle $\leq 50\%$.



ELECTRICAL CHARACTERISTICS (Ta=25℃)

CHARACTERISTIC	SYMBOL	TEST CONDITION	MIN.	TYP.	MAX.	UNIT
Collector Cut-off Current	I_{CBO}	$V_{CB}=-30\text{V}$, $I_E=0$	-	-	-1	μA
Emitter-Cut-off Current	I_{EBO}	$V_{EB}=-3\text{V}$, $I_C=0$	-	-	-1	μA
DC Current Gain *	$h_{FE}(1)$	$V_{CE}=-2\text{V}$, $I_C=-20\text{mA}$	30	220	-	
	$h_{FE}(2)$ (Note)	$V_{CE}=-2\text{V}$, $I_C=-1\text{A}$	100	160	400	
Collector-Emitter Saturation Voltage *	$V_{CE(sat)}$	$I_C=-2\text{A}$, $I_B=-0.2\text{A}$	-	-0.3	-0.5	V
Base-Emitter Saturation Voltage *	$V_{BE(sat)}$	$I_C=-2\text{V}$, $I_B=-0.2\text{A}$	-	-1.0	-2.0	V
Current Gain Bandwidth Product	f_T	$V_{CE}=-5\text{V}$, $I_C=-0.1\text{A}$	-	80	-	MHz
Collector Output Capacitance	C_{ob}	$V_{CB}=-10\text{V}$, $I_E=0$, $f=1\text{MHz}$	-	55	-	pF

* Pulse Test : Pulse Width $\leq 350\mu\text{s}$, Duty Cycle $\leq 2\%$ Pulsed

Note: $h_{FE}(2)$ Classification O:100 ~ 200 , Y:160 ~ 320 , GR:200 ~ 400

