

# Absolute encoders - parallel

Magnetic sensor bore max.  $\varnothing 12$  mm

Magnetic singleturn encoders / kit 12 bit

## BMSK 58 parallel - MAGRES



BMSK 58 parallel kit

### Features

- Encoder kit singleturn / parallel
- Magnetic sensing
- Resolution: 12 bit
- High protection standard
- High resistance to shock and vibrations
- Reset input

### Technical data - electrical ratings

Voltage supply	10...30 VDC
Consumption w/o load (typ.)	50 mA (24 VDC)
Initializing time (typ.)	170 ms after power on
Interface	12 parallel outputs
Function	Singleturn
Steps per turn	4096 / 12 bit
Absolute accuracy	$\pm 1^\circ$
Sensing method	Magnetic
Code	Gray or binary
Code sequence	CW: ascending values with clockwise sense of rotation (looking at flange)
Inputs	Reset input
Interference immunity	DIN EN 61000-6-2
Emitted interference	DIN EN 61000-6-3
Approval	UL approval / E217823

### Technical data - mechanical design

Dimensions (flange)	$\varnothing 58$ mm
Shaft	Magnet hole 12 mm
Protection DIN EN 60529	IP 67
Operating speed	$\leq 12000$ rpm (mechanical) $\leq 6000$ rpm (electric)
Materials	Housing: steel/aluminium Flange: aluminium
Operating temperature	$-20 \dots +85^\circ\text{C}$
Relative humidity	95 %
Resistance	DIN EN 60068-2-6 Vibration 30 g, 10-2000 Hz DIN EN 60068-2-27 Shock 100 g, 6 ms
Weight approx.	300 g
Connection	Cable 2 m
Gap tolerance	$\leq 0.3$ mm axial $\leq 0.1$ mm radial

# Absolute encoders - parallel

Magnetic sensor bore max.  $\varnothing$ 12 mm


Magnetic singleturn encoders / kit 12 bit

## BMSK 58 parallel - MAGRES

### Part number

BMSK 58S1 

	24K	12/00	12	5
--	-----	-------	----	---



### Accessories

#### Mounting accessories

10110616	Clamp set
10112432	Hexagon wrench 2.5 mm

# Absolute encoders - parallel

Magnetic sensor bore max.  $\varnothing$ 12 mm

Magnetic singleturn encoders / kit 12 bit

## BMSK 58 parallel - MAGRES

### Terminal significance

+Vs	Encoder supply voltage.
0 V	Encoder ground connection relating to +Vs.
Bit 1-12	12 parallel output signals.
Zero	Input for setting a zero point anywhere within the encoder resolution. The zero setting operation is triggered by a Low impulse. Connect to +Vs after setting operation for maximum interference immunity. Impulse duration >2 ms.

### Terminal assignment

#### Cable

for connection reference -5

Core colour	Signals	Description
brown	+Vs	Supply voltage
white	0 V	Supply voltage
green	Bit 1 LSB	Data bit
yellow	Bit 2	Data bit
grey	Bit 3	Data bit
pink	Bit 4	Data bit
blue	Bit 5	Data bit
red	Bit 6	Data bit
black	Bit 7	Data bit
purple	Bit 8	Data bit
grey/pink	Bit 9	Data bit
white/green	Bit 10	Data bit
brown/green	Bit 11	Data bit
yellow/brown	Bit 12 MSB	Data bit
white/yellow	Bit 12 MSB comp. <sup>1)</sup> Data bit	
red/blue	Zero	Zero setting input
Screen	connected to housing	
Cable data	16 x 0.14 mm <sup>2</sup>	

<sup>1)</sup> The direction of rotation for encoders with gray-code can be defined by connecting the MSB or MSB comp. If MSB is connected, the encoder counts up as the shaft rotates clockwise (CW). If MSB inv. is connected, the encoder counts up if the shaft rotates counter clockwise (CCW).

### Trigger level

Control inputs	Input circuit
Zero setting	<0,4 V (>2 ms)
Off state	+Vs or open

### Parallel outputs 24K

	Output circuit
	Push-pull short-circuit protection
Output level High	>UB - 5,5 V (I = -30 mA)
Output level Low	<5,5 V (I = 30 mA)
Load High	<30 mA / Output
Load Low	<30 mA / Output

# Absolute encoders - parallel

Magnetic sensor bore max.  $\varnothing 12$  mm

Magnetic singleturn encoders / kit 12 bit

**BMSK 58 parallel - MAGRES**

## Dimensions

### BMSK 58 parallel cable radial

