



POWER AMPLIFIER APPLICATION.
POWER SWITCHING APPLICATION.

FEATURES

- Low Collector Saturation Voltage
: $V_{CE(sat)}=0.5V(\text{Max.})$ ($I_C=1A$)
- High Speed Switching Time : $t_{stg}=1\mu S(\text{Typ.})$
- Complementary to KTA1718D/L.

MAXIMUM RATING ($T_a=25^\circ\text{C}$)

CHARACTERISTIC		SYMBOL	RATING	UNIT
Collector-Base Voltage		V _{CBO}	50	V
Collector-Emitter Voltage		V _{CEO}	50	V
Emitter-Base Voltage		V _{EBO}	5	V
Collector Current		I _C	2	A
Emitter Current		I _E	-2	A
Collector Power Dissipation	Ta=25 ℃	P _C	1.0	W
	Tc=25 ℃		10	
Junction Temperature		T _j	150	℃
Storage Temperature Range		T _{stg}	-55 ~ 150	℃









ELECTRICAL CHARACTERISTICS ($T_a=25^\circ\text{C}$)

CHARACTERISTIC	SYMBOL	TEST CONDITION	MIN.	TYP.	MAX.	UNIT
Collector Cut-off Current	I_{CBO}	$V_{CB}=50V, I_E=0$	-	-	0.1	μA
Emitter Cut-off Current	I_{EBO}	$V_{EB}=5V, I_C=0$	-	-	0.1	μA
Collector-Emitter Breakdown Voltage	$V_{(BR)CEO}$	$I_C=10mA, I_B=0$	50	-	-	V
DC Current Gain	$h_{FE(1)}$ (Note)	$V_{CE}=2V, I_C=0.5A$	70	-	240	
	h_{FE2}	$V_{CE}=2V, I_C=1.5A$	40	-	-	
Collector-Emitter Saturation Voltage	$V_{CE(sat)}$	$I_C=1A, I_B=0.05A$	-	-	0.5	V
Base-Emitter Saturation Voltage	$V_{BE(sat)}$	$I_C=1A, I_B=0.05A$	-	-	1.2	V
Transition Frequency	f_T	$V_{CE}=2V, I_C=0.5A$	-	100	-	MHz
Collector Output Capacitance	C_{ob}	$V_{CB}=10V, I_E=0, f=1MHz$	-	30	-	pF
Switching Time	Turn On Time	t_{on}	-	0.1	-	μS
	Storage Time	t_{stg}	-	1.0	-	
	Fall Time	t_f	-	0.1	-	


Note : $h_{FE(1)}$ Classification O:70~140, Y:120~240.

STATIC CHARACTERISTICS



KTC2815D/L

SAFE OPERATING AREA



Pc - Ta

