


HIGH SPEED SWITCHING.

FEATURES


- Low Forward Voltage : $V_F=0.25(\text{Typ.}) @ I_F=5\text{mA}$
- Small Package : ESM.

MAXIMUM RATING ($T_a=25^\circ\text{C}$)


CHARACTERISTIC	SYMBOL	RATING	UNIT
Maximum (Peak) Reverse Voltage	V_{RM}	15	V
Reverse Voltage	V_R	10	V
Maximum (Peak) Forward Current	I_{FM}	100 *	mA
Average Forward Current	I_O	50 *	mA
Surge Current (10ms)	I_{FSM}	1 *	A
Power Dissipation	P_D	100	mW
Junction Temperature	T_j	125	$^\circ\text{C}$
Storage Temperature Range	T_{stg}	-55 ~ 125	$^\circ\text{C}$
Operating Temperature Range	T_{opr}	-40 ~ 100	$^\circ\text{C}$

* : Unit Rating. Total Rating=Unit Rating $\times$ 1.5


DIM	MILLIMETERS
A	1.60±0.10
B	0.85±0.10
C	0.70±0.10
D	0.27+0.10/-0.05
E	1.60±0.10
G	1.00±0.10
H	0.50
J	0.13±0.05




1. ANODE 1
2. ANODE 2
3. CATHODE



ESM

Marking

ELECTRICAL CHARACTERISTICS ($T_a=25^\circ\text{C}$)

CHARACTERISTIC	SYMBOL	TEST CONDITION	MIN.	TYP.	MAX.	UNIT
Forward Voltage	$V_{F(1)}$	$I_F=1\text{mA}$	-	0.21	-	V
	$V_{F(2)}$	$I_F=5\text{mA}$	-	0.25	0.30	
	$V_{F(3)}$	$I_F=50\text{mA}$	-	0.35	0.50	
Reverse Current	I_R	$V_R=10\text{V}$	-	-	20	μA
Total Capacitance	C_T	$V_R=0\text{V}, f=1\text{MHz}$	-	13	40	pF

KDR331E

