



Agilent 10898D High Resolution Dual Laser Axis Board

Data Sheet



The new 10898D High Resolution Dual Laser Axis Board offers the outstanding performance for which Agilent Technologies is known. The Agilent 10898D dual axis board combines the same excellent resolution of the 10897D board together with increased slew rates and even better noise performance to provide the ultimate in repeatable and accurate positioning for advanced applications such as IC fabrication.

The 10898D offers very high data rates to provide exceptional bandwidth and high-performance closed-loop positioning for critical applications. The 10898D's standard VMEbus interface speeds system integration, saving valuable time and money. To further simplify and speed system layout, the 10898D also offers programmable signal routing. Like all VMEbus laser electronics from Agilent, the 10898D has a three-year warranty.



Agilent Technologies

Agilent 10898D High Resolution Dual Laser Axis Board

High Performance for Advanced Applications

The Agilent 10898D High Resolution Dual Laser Axis Board offers outstanding position resolution and low noise, resulting in unsurpassed positioning repeatability and accuracy compared to previous laser systems. The Agilent 10898D provides measurement resolution up to $\lambda/2048$, or 0.3 nm (3 Å) with the high resolution plane mirror interferometer. The Agilent 10898D is tested at frequencies equivalent to 2700 mm/s plane mirror slew rates.

Systems generally can compensate for data age, the constant time lag between triggering a measurement and receiving the data, but not for variable data age, the portion that changes and translates directly into stage position error. For example, a stage moving at 500 mm/s with 800 ps of variable data age has a minimum 0.4 nm position error due to variable data age.

The unique Agilent 10898D design has improved dynamic positioning accuracy by reducing the variable data age to less than 1 nanosecond for most applications. This results in unsurpassed positioning accuracy when compensating moving systems for the delay between the position measurement and the time the position information is available. Dynamic accuracy is especially important for E-beam machines and step and scan IC fabrication tools.

The 10898D contains an onboard, low-pass filter which may be enabled to provide more stable operation in low signal-to-noise conditions. This filter is programmable to provide the most stable positioning for your specific application.

The 10898D is a register-programmed position axis board that provides a 36-bit position word in fractional wavelengths. The position word is readable over the VMEbus and is also available from a real-time hardware output on the A and C rows of the P2 connector.

Flexible VMEbus Electronics Speed System Integration

The Agilent 10898D is a 6U-size board that complies electrically and mechanically with Revision C.1 of the VMEbus specifications.

The heart of the 10898D is a proprietary interpolator specifically designed for this application. Surface mount technology is used to provide a compact, reliable design.

To further simplify and speed system layout, the 10898D offers programmable signal routing. Cable routing is flexible; the reference and measurement signals can come from either the front panel connectors or the multi-axis interconnect cable.

The 10898D uses Agilent 10880A/B/C or N1250A/B/E Receiver Cables, and 10881A/B/C/D/E/F Laser Head Cables. Contact your Agilent representative for more information about cable options.



Agilent Technologies

Agilent Technologies 10898D High Resolution Dual Laser Axis Board	
General System Specifications	
Number of measurement channels	Two channels
Maximum number of boards in system	Seven boards (for larger board groups, consult your Agilent representative)
Measurement resolution	Linear Optics 1.2 nm ($\lambda/512$) Plane Mirror Optics 0.6 nm ($\lambda/1024$) High Resolution Optics 0.3 nm ($\lambda/2048$)
Velocity range (using plane mirror)	± 1.100 m/s with Agilent 5517GL laser head ± 1.000 m/s with Agilent 5517FL laser head ± 0.790 m/s with Agilent 5517EL laser head ± 0.670 m/s with Agilent 5517DL laser head ± 0.500 m/s with Agilent 5517D laser head ± 0.356 m/s with Agilent 5517C laser head ± 0.254 m/s with Agilent 5517B laser head ± 0.203 m/s with Agilent 5517A laser head (Consult your Agilent representative for help in selecting the correct receiver that corresponds to the velocity for your laser head.)
Working range with plane mirror optics	± 10.6 m
General VME Characteristics	
VME Compliance	Complies with VME Specification Rev. C.1 6U size, VME64X A16 Data Transfer Cycles D16 Data Transfer Cycles A24 Data Transfer Cycles D32 Data Transfer Cycles D08 (O) Interrupt Acknowledge Cycles
Power Requirements	
Power requirements	5 Vdc ± 0.25 V/ -0.125 V at less than 4.5 A $+12$ V ± 0.5 V at less than 0.2 A
Environmental Requirements	
Operating temperature range	0 to 40°C
Airflow requirements	19 linear meters (60 linear feet) per minute minimum
Physical Characteristics	
Weight	0.45 kg (1 lb)

Agilent Technologies 10898D High Resolution Dual Laser Axis Board

VMEbus Position Output

Data format	Units: fractions of a wavelength 2's Complement: choose any 32 of 35 bits to read Positive Logic Least Significant Bit (or one count) equals resolution
Data rate over backplane	>100 kHz VMEbus cycle rate
Sample data age and delay (typical)	<p>Fixed</p> <p>With respect to the rising edge of the 10 MHz P2 clock pin immediately after assertion of one of the asynchronous sample pins of P2, the value in the position register will reflect the actual position that occurred approximately N ns before.</p> <p>There are two user-selectable values of N: 262 ns and 762 ns.</p> <p>Variable</p> <p><800 ps over the full power supply voltage specification, and <40 ps/°C</p> <p>Delay</p> <p>When N=262 ns is selected, the position data is available to be read on the VMEbus 600 ns after the sampling operation. For N=762 ns, position data is available on the VMEbus 100 ns after the sampling operation.</p>

P2 Connector Hardware Position Output

Data format	Units: fractions of a wavelength <i>either</i> 2's Complement: 36 parallel binary <i>or</i> signed magnitude (bit 35 is sign bit) Positive Logic Least Significant Bit (or one count) equals resolution
Data update rate	10 MHz using a single channel 5 MHz using both channels (hardware included to synchronize to slower clocks)
Data age (typical)	<p>Fixed</p> <p>Fixed</p> <p>There is a time lag of approximately 1.1 μs between the actual position and the position at the hardware output lines (located on rows A and C of P2 connector).</p> <p>Variable</p> <p><800 ps over the full power supply voltage specification, and <40 ps/°C</p>





Agilent Email Updates

www.agilent.com/find/emailupdates
Get the latest information on the products and applications you select.



www.axistandard.org

AdvancedTCA® Extensions for Instrumentation and Test (AXIe) is an open standard that extends the AdvancedTCA for general purpose and semiconductor test. Agilent is a founding member of the AXIe consortium.



www.lxistandard.org

LAN eXtensions for Instruments puts the power of Ethernet and the Web inside your test systems. Agilent is a founding member of the LXI consortium.



www.pxisa.org

PCI eXtensions for Instrumentation (PXI) modular instrumentation delivers a rugged, PC-based high-performance measurement and automation system.

Agilent T&M Software and Connectivity

Agilent's Test and Measurement software and connectivity products, solutions and developer network allows you to take time out of connecting your instruments to your computer with tools based on PC standards, so you can focus on your tasks, not on your connections. For more information, visit www.agilent.com/find/connectivity



Agilent Advantage Services is committed to your success throughout your equipment's lifetime. To keep you competitive, we continually invest in tools and processes that speed up calibration and repair and reduce your cost of ownership. You can also use Infoline Web Services to manage equipment and services more effectively. By sharing our measurement and service expertise, we help you create the products that change our world.

www.agilent.com/find/advantageservices



Agilent Channel Partners

www.agilent.com/find/channelpartners

Get the best of both worlds: Agilent's measurement expertise and product breadth, combined with channel partner convenience.

www.agilent.com
www.agilent.com/find/lasers

For more information on Agilent Technologies' products, applications or services, please contact your local Agilent office. The complete list is available at: www.agilent.com/find/contactus

Americas

Canada	(877) 894 4414
Brazil	(11) 4197 3500
Mexico	01800 5064 800
United States	(800) 829 4444

Asia Pacific

Australia	1 800 629 485
China	800 810 0189
Hong Kong	800 938 693
India	1 800 112 929
Japan	0120 (421) 345
Korea	080 769 0800
Malaysia	1 800 888 848
Singapore	1 800 375 8100
Taiwan	0800 047 866
Other AP Countries	(65) 375 8100

Europe & Middle East

Belgium	32 (0) 2 404 93 40
Denmark	45 45 80 12 15
Finland	358 (0) 10 855 2100
France	0825 010 700*
	*0.125 €/minute
Germany	49 (0) 7031 464 6333
Ireland	1890 924 204
Israel	972-3-9288-504/544
Italy	39 02 92 60 8484
Netherlands	31 (0) 20 547 2111
Spain	34 (91) 631 3300
Sweden	0200-88 22 55
United Kingdom	44 (0) 118 927 6201

For other unlisted countries:

www.agilent.com/find/contactus

Revised: January 6, 2012

Product specifications and descriptions in this document subject to change without notice.

© Agilent Technologies, Inc. 2009-2012
Published in USA, May8, 2012
5990-7924EN



Agilent Technologies