


Agilent E8241A/44A/51A/54A PSG Family Performance Signal Generator

Data Sheet



	CW only PSG-L Series	Analog PSG-A Series
250 kHz to 20 GHz	E8241A	E8251A
250 kHz to 40 GHz	E8244A	E8254A

All specifications and characteristics apply over a 0 to 55°C range (unless otherwise stated) and apply after a 45 minute warm-up time. Supplemental characteristics, denoted as typical or nominal, provide additional (non-warranted) information.

Definitions

Specifications (spec): represent warranted performance.

Typical (typ): performance is not warranted. It applies at 25°C. 80% of all products meet typical performance.

Nominal (nom): values are not warranted. They represent the value of a parameter that is most likely to occur; the expected or mean value. They are included to facilitate the application of the product.

Standard (std): No options are included when referring to the signal generator unless noted otherwise.



Specifications

L and A Series

Frequency		
Range¹		
Frequency Range	PSG-L Series	PSG-A Series
250 kHz to 20 GHz	E8241A	E8251A
250 kHz to 40 GHz	E8244A	E8254A
Resolution	0.01 Hz	
Accuracy	Calibration = aging rate ± temperature effects ± line voltage effects	
Switching speed (typical)²		
Analog modulation	< 15 ms	
Modulation off	< 15 ms	
Phase offset	Adjustable in nominal 0.1° increments.	
Frequency bands		
Band	Frequency range	N #
1	250 kHz to 250 MHz	1/8
2	> 250 to 500 MHz	1/16
3	> 500 MHz to 1 GHz	1/8
4	> 1 to 2 GHz	1/4
5	> 2 to 3.2 GHz	1/2
6	> 3.2 to 10 GHz	1
7	> 10 to 20 GHz	2
8	> 20 to 40 GHz	4
Internal timebase reference oscillator		
	Standard	Option UNJ
Aging rate	< ±1 × 10 ⁻⁷ /year or < ±4.5 × 10 ⁻⁹ /day after 45 days	< ±3 × 10 ⁻⁸ /year or < ±2.5 × 10 ⁻¹⁰ /day after 24 hours
Temperature effects (typical)	< ±5 × 10 ⁻⁸ 0 to 55°C	< ±4.5 × 10 ⁻⁹ 0 to 55°C
Line voltage effects (typical)	< ±2 × 10 ⁻⁹ for +5% -10% change	< ±2 × 10 ⁻¹⁰ for ±10% change
External reference frequency	1, 2, 2.5, 5, 10 MHz (within 1 ppm)	10 MHz only (within 1 ppm)
Reference output		
Frequency	10 MHz	
Amplitude	> +4 dBm typical into 50Ω load	
External reference input		
Amplitude	> -3 dBm	
Opt UNJ	5 dBm ±5 dB ³	
Input impedance	50Ω↔ nominal	
Digital sweep		
Operating modes	Step sweep of frequency or amplitude or both (Start to stop)	
	List sweep of frequency or amplitude or both (Arbitrary list)	

¹ Useable to 100 kHz

² To within 0.1 ppm of final frequency above 250 MHz or within 100 Hz below 250 MHz



³ To optimize phase noise 5 dBm ± 2 dB

L and A Series

Sweep range	
Frequency sweep	Within instrument frequency range
Amplitude sweep	Within attenuator hold range
Dwell time	1 ms to 60 s
Frequency settling time	28 ms typical
Amplitude settling time	10 ms typical
Number of points	2 to 1601
Triggering	Auto, external, single, or GPIB

Output

Power ⁴ (dBm)	Standard	Option 1EA
Frequency range		
20 GHz Models		
250 kHz to 3.2 GHz	-20 to +13	-20 to +16
> 3.2 to 20 GHz	-20 to +13	-20 to +20
40 GHz Models		
250 kHz to 3.2 GHz	-20 to +9	-20 to +15
> 3.2 to 20 GHz	-20 to +9	-20 to +18
> 20 to 40 GHz	-20 to +9	-20 to +14
20 GHz Models with option 1E1		
250 kHz to 3.2 GHz	-135 to +11	-135 to +15
> 3.2 to 20 GHz	-135 to +11	-135 to +18
40GHz Models with option 1E1		
250 kHz to 3.2 GHz	-135 to +7	-135 to +14
> 3.2 to 20 GHz	-135 to +7	-135 to +16
> 20 to 40 GHz	-135 to +7	-135 to +12
Option 1E1 step attenuator	0 dB and 5 to 115 dB in 10 dB steps	



Attenuator hold range
(Same as max power sweep range)

Minimum

From -20 dBm to maximum specified output power.
Can be offset using Option 1E1 attenuator.

Amplitude switching speed⁵

CW or analog modulation < 25 ms, typical

When using power search < 25 ms, typical

CW level accuracy⁶ (dB)

Frequency	> +10 dBm	+10 to -10 dBm	-10 to -20 dBm
250 kHz to 2 GHz	±0.6	±0.6	±1.4
2 GHz to 20 GHz	±0.8	±0.8	±1.2
> 20 to 40 GHz	±1.0	±0.9	±1.3

⁴ Maximum power specification is warranted from 15 to 35°C, and is typical from 0 to 15°C. Maximum power over the 35 to 55°C range typically degrades less than 2 dB.

⁵ To within 0.1 dB of final amplitude within one attenuator range

⁶ Specifications apply over the 15 to 35°C temperature range. Degradation outside this range, for power levels > -10 dBm, is typically < 0.3 dB.

For instruments with type-N connectors (Option 1ED), specifications are degraded typically 0.2 dB above 18 GHz.


L and A Series

CW level accuracy with option 1E1⁷ (dB)

Frequency	> +10 dBm	+10 to -10 dBm	-10 to -70 dBm	-70 to -90 dBm	-90 to -110 dBm
250 kHz to 2 GHz	±0.6	±0.6	±0.7	±0.8	±1.4
> 2 to 20 GHz	±0.8	±0.8	±0.9	±1.0	±1.7
> 20 to 40 GHz	±1.0	±0.9	±1.0	±2.0	


20 GHz level accuracy

Measured level accuracy +5 dBm option 1E1



40 GHz level accuracy

Measured level accuracy +5 dBm option 1E1



Resolution	0.01 dB
Temperature stability	0.01 dB/°C, typical
User flatness correction	
Number of points	2 to 1601 points/table
Number of tables	Up to 10,000, memory limited
Path loss	Arbitrary, within attenuator range
Entry modes	Remote power meter ⁸ , remote bus, manual (user edit/view)
Output impedance	50 Ω, nominal
SWR (internally leveled, typical)	
250 kHz to 2 GHz	< 1.4:1
> 2 GHz to 20 GHz	< 1.6:1
> 20 GHz to 40 GHz	< 1.8:1
Leveling modes	Internal leveling, external detector leveling, millimeter source module, ALC Off
External detector leveling	
Range	-0.2 mV to -0.5 V, nominal (-36 dBm to +4 dBm using Agilent 33330D/E detector)
Bandwidth	Typically 10 kHz (Note: not intended for pulsed operation)
Maximum reverse power	1/2 Watt nominal

Spectral purity

Harmonics⁹ (dBc at +10 dBm or maximum specified output power, whichever is lower)

< 1 MHz	-30 dBc typical
1 MHz to 2 GHz	-30 dBc
> 2 GHz to 20 GHz	-55 dBc
> 20 GHz to 40 GHz	-50 dBc typical

⁷ Specifications apply over the 15 to 35°C temperature range, with attenuator lock off (normal operating mode). Degradation outside this range, for ALC power levels > -10 dBm, is typically < 0.3 dB.


For instruments with type-N connectors (Option 1ED), specifications are degraded typically 0.2 dB above 18 GHz. Level accuracy is not specified below -110 dBm.

⁸ Compatible with Agilent Technologies EPM Series (E4418B and E4419B) power meters.


⁹ Specifications for harmonics beyond maximum instrument frequencies are typical.

L and A Series

20 GHz Measured harmonics



40 GHz Measured harmonics



Sub-harmonics: ¹⁰ (dBc at +10 dBm or maximum specified output power, whichever is lower)

250 kHz to 10 GHz	None
> 10 GHz to 20 GHz	< -60 dBc
> 20 GHz to 40 GHz	< -50 dBc

Non-harmonics: (dBc at +10 dBm or maximum specified output power, whichever is lower, for offsets > 3 KHz (>300 Hz with Option UNJ))¹¹

Frequency	Spec	Typical
250 kHz to 250 MHz	< -65	-72 for > 10 kHz offsets
> 250 MHz to 1 GHz	< -80	< -88
> 1 to 2 GHz	< -74	< -82
> 2 to 3.2 GHz	< -68	-76
> 3.2 to 10 GHz	< -62	-70
> 10 to 20 GHz	< -56	-64
> 20 to 40 GHz	< -50	-58

SSB phase noise (CW)
Offset from Carrier (dBc/Hz)

Frequency	20 kHz	20 kHz typical
250 kHz to 250 MHz	-130	-134
> 250 to 500 MHz	-136	-140
> 500 MHz to 1 GHz	-130	-134
> 1 to 2 GHz	-124	-128
> 2 to 3.2 GHz	-120	-124
> 3.2 to 10 GHz	-110	-113
> 10 to 20 GHz	-104	-108
> 20 to 40 GHz	-98	-102

¹⁰ Specifications for harmonics beyond maximum instrument frequencies are typical.

¹¹ Performance is typical for spurs at frequencies above the maximum operating frequency of the instrument. Specifications apply for CW mode only. Performance typically is -60 dBc between 200 and 250 MHz.

L and A Series

Option UNJ: Improved SSB phase noise

Offset from carrier (dBc/Hz)

Frequency	100 Hz spec (typ)	1 kHz spec (typ)	10 kHz spec (typ)	100 kHz spec (typ)
250 kHz to 250 MHz	-94 (-115)	-110 (-123)	-128 (-132)	-130 (-133)
> 250 to 500 MHz	-100 (-110)	-124 (-130)	-132 (-136)	-136 (-141)
> 500 MHz to 1 GHz	-94 (-104)	-118 (-126)	-130 (-135)	-130 (-135)
> 1 to 2 GHz	-88 (-98)	-112 (-120)	-124 (-129)	-124 (-129)
> 2 to 3.2 GHz	-84 (-94)	-108 (-116)	-120 (-125)	-120 (-125)
> 3.2 to 10 GHz	-74 (-84)	-98 (-106)	-110 (-115)	-110 (-115)
> 10 to 20 GHz	-68 (-78)	-92 (-100)	-104 (-107)	-104 (-109)
> 20 to 40 GHz	-62 (-72)	-86 (-94)	-98 (-101)	-98 (-103)

Residual FM < N x 6 Hz, typical

Option UNJ < N x 4 Hz, typical

(rms, 50 Hz to 15 kHz bandwidth)

Broadband noise (CW mode at +10 dBm output,
for offsets > 10 MHz)

> 0.25 to 20 GHz


< -148 dBc/Hz typical

> 20 to 40 GHz


< -141 dBc/Hz typical

Measured phase noise


Standard Product




Option UNJ



Measured Standard vs. Option UNJ at 10 GHz



Measured AM noise at 10 GHz



A Series only

Frequency modulation		
Maximum deviation	N x 8 MHz	
Resolution	0.1% of deviation or 1 Hz, whichever is greater	
Deviation accuracy	< ± 3.5% of FM deviation + 20 Hz (1 kHz rate, deviations < N x 800 kHz)	
Modulation frequency response		
Path	Rates (at 100 kHz deviation)	
	1 dB Bandwidth	3 dB Bandwidth, typical
FM 1	dc/20 Hz to 100 kHz	dc/5 Hz to 10 MHz
FM 2	dc/20 Hz to 100 kHz	dc/5 Hz to 1 MHz
dc FM¹² carrier offset	±0.1% of set deviation + (N x 8 Hz)	
Distortion	< 1% (1 kHz rate, deviations < N x 800 kHz)	
Sensitivity	±1 V _{peak} for indicated deviation	
Paths	FM1 and FM2 are summed internally for composite modulation. Either path may be switched to any one of the modulation sources: Ext1, Ext2, internal1, internal2. The FM2 path is limited to a maximum rate of 1 MHz. The FM2 path must be set to a deviation less than FM1.	
Phase modulation		
Maximum deviation	N x 80 radians (N x 8 radians in high-bandwidth mode)	
Resolution	0.1% of set deviation	
Deviation accuracy	< ±5% of deviation + 0.01 radians (1 kHz rate, normal BW mode)	
Modulation frequency response		
Mode	Maximum Deviation	Rates (3 dB BW)
Normal BW	N x 80 rad	dc – 100 kHz
High BW	N x 8 rad	dc – 1 MHz (typ)
Distortion	< 1 % (1 kHz rate, THD, dev < N x 80 rad, normal BW mode)	
Sensitivity	±1 V _{peak} for indicated deviation	
Path	ΦM1 and ΦM2 are summed internally for composite modulation. Either path may be switched to any one of the modulation sources: Ext1, Ext2, internal1, internal2. The ΦM2 path must be set to a deviation less than ΦM1.	

¹² At the calibrated deviation and carrier frequency, within 5°C of ambient temperature at time of user calibration.

A Series only

Amplitude modulation ($f_c > 2$ MHz)¹³ (typical)		
Depth	Linear mode	Exponential (log) mode (Downward modulation only)
Maximum	> 90%	> 20 dB
Settable¹⁴	0 - 100 %	0 to 40 dB
Resolution	0.1%	0.01 dB
Accuracy (1 kHz rate)	< $\pm(6\%$ of setting + 1 %)	< $\pm(2\%$ of setting + 0.2 dB)
Ext sensitivity	± 1 Vpeak for indicated depth	-1 V for indicated depth
Rates (3 dB bandwidth, 30% depth)		dc/10 Hz to 100 kHz typical (useable to 1 MHz)
Distortion (1 kHz rate, linear mode, THD)		
30% AM		< 1.5%
90% AM		< 4 %
Path	AM1 and AM2 are summed internally for composite modulation. Either path may be switched to any one of the modulation sources: Ext1, Ext2, internal1, internal2.	
External modulation inputs (Ext1 & Ext2)		
Modulation types	AM, FM, and Φ M	
Input impedance	50 or 600 Ω , nominal, switched	
High/low indicator (100 Hz to 10 MHz BW, ac coupled inputs only)	Activated when input level error exceeds 3%, nominal	
Simultaneous modulation	All modulation types may be simultaneously enabled except: FM with Φ M, and linear AM with exponential AM. AM, FM, and Φ M can sum simultaneous inputs from any two sources (Ext1, Ext2, internal1, or internal2) Any given source (Ext1, Ext2, internal1, or internal2) may be routed to only one activated modulation type.	
Internal modulation source	Dual function generators provides two independent signals (internal1 and internal2) for use with AM, FM, Φ M, or LF Out.	
Waveforms	Sine, square, positive ramp, negative ramp, triangle, Gaussian noise, uniform noise, swept sine, dual sine ¹⁵	
Rate range		
Sine	0.5 Hz to 1 MHz	
Square, ramp, triangle	0.5 Hz to 100 kHz	
Resolution	0.5 Hz	
Accuracy	Same as timebase	

¹³ For $f_c < 2$ MHz AM is usable but not specified. AM specifications apply with ALC on, and envelope peaks < maximum specified power. For instruments without Option 1E1 attenuator, specs apply for carrier amplitude > -2 dBm.

¹⁴ For AM depth settings > 90% or > 20 dB, deep AM mode or 1 kHz ALC BW is recommended.

¹⁵ Internal2 is not available when using swept sine or dual sine modes.

A Series only

LF out		
Output	Internal1 or internal2. Also provides monitoring of internal1 or internal2 when used for AM, FM, or Φ M.	
Amplitude	0 to 3 V _{peak} , nominal into 50 Ω	
Output impedance	50 Ω , nominal	
Swept sine mode: (frequency, phase continuous)		
Operating modes	Triggered or continuous sweeps	
Frequency range	1 Hz to 1 MHz	
Sweep rate	0.5 Hz to 100 k sweeps/s, equivalent to sweep times 10 μ s to 2 s	
Resolution	0.5 Hz (0.5 sweep/s)	
Pulse modulation		
	≥ 500 MHz to ≤ 3.2 GHz¹⁶	> 3.2 GHz
Power range		
Internally leveled	0 to +10 dBm	0 to +10 dBm
With option 1E1	-110 to +10 dBm	-110 to +10 dBm
On/off ratio	80 dB typical	80 dB
Rise/fall times (T_r, T_f)	100 ns typical	10 ns (6 ns typical)
Pulse width		
Internally leveled	≥ 2 μ s typical	≥ 1 μ s
ALC Off	≥ 0.5 μ s typical	≥ 20 ns typical
Repetition freq		
Internally leveled	10 Hz to 250 kHz typical	10 Hz to 500 kHz typical
ALC Off	dc to 1 MHz typical	dc to 10 MHz typical
Level accuracy (relative to CW)		
Internally leveled	± 0.5 dB	± 0.4 dB (± 0.15 typical)
ALC Off with power search ¹⁷	± 0.5 dB typical	≤ 20 GHz ± 0.8 dB typical ≤ 40 GHz ± 1.2 dB typical
Width compression	± 50 ns typical	± 5 ns typical
Video feedthrough¹⁸	< 200 mV typical	< 2 mV typical
Pulse delay (ext input to RF output)	300 ns nominal	70 ns nominal
Pulse overshoot (V_{or})	$< 10\%$ typical	
Input level	+1 V _{peak} = RF On	
Input impedance	50 Ω , nominal	


¹⁶ For improved performance ≤ 3.2 GHz, special Option HE6 is available. Contact your local Agilent Online representative.

¹⁷ Power search is a calibration routine that improves level accuracy in ALC-off mode. Unpulsed RF power will be present typically up to 5 ms when executing power search.

¹⁸ With attenuator in 0 dB position. Video feed-through decreases with attenuator setting.

A Series only


Measured pulse modulation envelope



Internal pulse generator

Modes	Free-run, triggered, triggered with delay, doublet, and gated. Triggered with delay, doublet, and gated require external trigger source.
Period (PRI) (T_p)	70 ns to 42 s (Repetition frequency: 0.024 Hz to 14.28 MHz)
Pulse width (T_w)	10 ns to 42 s
Delay (T_d)	
Free-run mode	0 to ± 42 s
Triggered with delay and doublet modes	75 ns to 42s with ± 10 ns jitter
Resolution	10 ns (width, delay, and PRI)
RF delay (T_m)	< 20 ns typical

- T_d Video delay (variable)
- T_w Video pulse width (variable)
- T_p Pulse period (variable)
- T_m RF delay
- T_{rf} RF pulse width
- T_f RF pulse fall time
- T_r RF pulse rise time
- V_{or} Pulse overshoot
- V_f Video feedthrough



L and A Series

Remote programming

Interfaces	GPIB (IEEE-488.2,1987) with listen and talk, RS-232, and 10-base T-LAN interface.
Control languages	SCPI version 1992.0. Also will emulate most applicable Agilent 836xxB, Agilent 8373xB, and Agilent 8340/41B commands, providing general compatibility with ATE systems which include these signal generators.
IEEE-488 functions	SH1, AH1, T6, TE0, L4, LE0, SR1, RL1, PP0, DC1, DT0, C0, E2.
VXIplug&play drivers	Are available.

L and A Series

ISO compliant	This family of signal generators is manufactured in an ISO-9001 registered facility in concurrence with Agilent Technologies commitment to quality.
General	
Power requirements	90 to 132 Vac 50 to 60 Hz, or 195 to 267 Vac 50 to 60 or 400 Hz, (automatically selected), 300 W maximum.
Operating temperature range	0 to 55°C
Storage temperature range	-40 to 71°C
Shock and vibration	Meets MIL-STD-28800E Type III, Class 3.
EMC	Conducted and radiated interference and immunity meets IEC/EN 61326-1 and MIL-STD-461C Part 2, RE02. Meets radiated emission requirements of CISPR Pub 11/1997 Group 1 class A.
Storage registers	Memory is shared by instrument states, user data files, sweep list files, and waveform sequences. Depending on the number and size of these files, up to 800 storage registers and 10 register sequences are available.
Security	Display blanking.
Compatibility	Agilent 83550 Series millimeter heads
Self-test	Internal diagnostic routine tests most modules (including microcircuits) in a preset condition. For each module, if its node voltages are within acceptable limits, then module "passes" the test.
Weight	< 22 kg (48 lb.) net, < 30 kg (68 lb.) shipping.
Dimensions	178 mm H x 426 mm W x 498 mm D (7" H x 16.8" W x 19.6" D in.).
Front panel connectors (All connectors are BNC female unless otherwise noted.)	
RF output	Nominal output impedance 50 Ω.
For 20 GHz models	Precision APC-3.5 male, or Type-N with Option 1ED.
For 40 GHz models	Precision 2.4 mm male; plus 2.4-2.4 mm and 2.4-2.9 mm female adaptors also included.
ALC input	Used for negative external detector leveling. Nominal input impedance 120 kΩ, damage level ±15 V.
LF output (PSG-A Series only)	Outputs the internally generated LF source. Nominal output impedance 50 Ω.
External input 1 (PSG-A Series only)	Drives either AM, FM, or ΦM. Nominal input impedance 50 or 600 Ω, damage levels are 5 Vrms and 10 Vpeak.
External input 2 (PSG-A Series only)	Drives either AM, FM, or ΦM. Nominal input impedance 50 or 600 Ω, damage levels are 5 Vrms and 10 Vpeak.
Pulse/trigger gate input (PSG-A Series only)	Accepts input signal for external fast pulse modulation. Also accepts external trigger pulse input for internal pulse modulation. Nominal impedance 50 Ω. Damage levels are 5 Vrms and 10 Vpeak.
Pulse video out (A series only)	Outputs a signal that follows the RF output in all pulse modes. TTL-level compatible, nominal source impedance 50 Ω.

Pulse sync out (A series only)	Outputs a synchronizing pulse, nominally 50 ns width, during internal and triggered pulse modulation. TTL-level compatible, nominal source impedance 50 Ω .
Rear panel connectors (All connectors are BNC female unless otherwise noted.)	
Serial interface	Used for serial communication (9-pin RS-232 connector female).
GPIB	Allows communication with compatible devices.
LAN	Allows LAN communication
10 MHz input	Accepts an external reference (timebase) input (at 1, 2, 2.5, 5, 10 MHz for standard and 10 MHz only for option UNJ) Nominal input impedance 50 Ω . Damage levels > +10 dBm
10 MHz output	Outputs internal or external reference signal. Nominal output impedance 50 Ω . Nominal output power +4 dBm
Sweep output	Generates output voltage, 0 to +10 V when signal generator is sweeping. Output impedance < 1 Ω , can drive 2000 Ω .
Trigger output	Outputs a TTL signal: high at start of dwell, or when waiting for point trigger in manual sweep mode; low when dwell is over or point trigger is received, high or low 4 us pulse at start of LF sweep.
Trigger input	Accepts TTL signal for triggering point-to-point in manual sweep mode, or to trigger start of LF sweep. Damage levels \geq +10 V or \leq -4 V.
Source module interface	Provides bias, flatness correction, and leveling connections to the model 83550 Series mm-wave source modules.
Source settled output	Provides an output trigger that indicates when the signal generator has settled to a new frequency or power level (open-collector output).
EFC	> 0.25 ppm for -5 to +5 V
Recommended calibration cycle	24 months

Agilent Technologies' Test and Measurement Support, Services, and Assistance

Agilent Technologies aims to maximize the value you receive, while minimizing your risk and problems. We strive to ensure that you get the test and measurement capabilities you paid for and obtain the support you need. Our extensive support resources and services can help you choose the right Agilent products for your applications and apply them successfully. Every instrument and system we sell has a global warranty. Support is available for at least five years beyond the production life of the product. Two concepts underlie Agilent's overall support policy: "Our Promise" and "Your Advantage."

Our Promise

Our Promise means your Agilent test and measurement equipment will meet its advertised performance and functionality. When you are choosing new equipment, we will help you with product information, including realistic performance specifications and practical recommendations from experienced test engineers. When you use Agilent equipment, we can verify that it works properly, help with product operation, and provide basic measurement assistance for the use of specified capabilities, at no extra cost upon request. Many self-help tools are available.

Your Advantage

Your Advantage means that Agilent offers a wide range of additional expert test and measurement services, which you can purchase according to your unique technical and business needs. Solve problems efficiently and gain a competitive edge by contracting with us for calibration, extra-cost upgrades, out-of-warranty repairs, and on-site education and training, as well as design, system integration, project management, and other professional engineering services. Experienced Agilent engineers and technicians worldwide can help you maximize your productivity, optimize the return on investment of your Agilent instruments and systems, and obtain dependable measurement accuracy for the life of those products.

By internet, phone, or fax, get assistance with all your test & measurement needs

Online assistance:
www.agilent.com/find/assist

Phone or Fax

United States:
(tel) 1 800 452 4844

Korea:
(tel) (82 2) 2004 5004
(fax) (82 2) 2004 5115

Canada:
(tel) 1 877 894 4414
(fax) (905) 282 6495

Latin America:
(tel) (305) 269 7500
(fax) (305) 269 7599

China:
(tel) 800 810 0189
(fax) 1 0800 650 0121

Taiwan:
(tel) 080 004 7866
(fax) (886 2) 2545 6723

Europe:
(tel) (31 20) 547 2323
(fax) (31 20) 547 2390

Other Asia Pacific Countries:
(tel) (65) 375 8100
(fax) (65) 836 0252
tm_asia@agilent.com

Japan:
(tel) (81) 426 56 7832
(fax) (81) 426 56 7840

Product specifications and descriptions in this document subject to change without notice.

© Agilent Technologies, Inc. 2002
Printed in USA, March 13, 2002
5988-2412EN



Agilent Technologies