

# Agilent 355C/D VHF Attenuators dc to 1 GHz

Data Sheet

## Discontinued Product Information — For Support Reference Only —

Information herein, may refer to products/services no longer supported. We regret any inconvenience caused by obsolete information. For the latest information on Agilent's test and measurement products go to: [www.agilent.com/find/products](http://www.agilent.com/find/products)

In the US, call Agilent Technologies at 1-800-829-4444  
(any weekday between 8am–5pm in any U.S. time zone)

World-wide Agilent sales office contact information is available at:  
[www.agilent.com/find/contactus](http://www.agilent.com/find/contactus)



## Features and applications

- Broad frequency coverage, dc to 1000 megahertz
- Low insertion loss
- Low SWR and negligible leakage
- Measure gain, attenuation, frequency response
- Broaden usefulness of present equipment
- Calibrate signal sources

## Description

Precision attenuation from dc to 1000 MHz is available with these attenuators. Model 355C provides 0 to 12 dB in 1-dB steps and Model 355D provides 0 to 120 dB in 10-dB steps. Standard 355C's and D's are equipped with BNC connectors. Units can be coupled together with a standard UG-491A/U male-to-male BNC adapter. Option 001 Type N connector 355's are ideally suited for applications such as receiver testing where minimum leakage is important. Option 001 355's may be coupled together with the

1250-0778 Type N male-to-male adapter (UG-57B/U). Using the 355C and 355D in series provides precision, the attenuation in 1-dB steps from 0 to 132 dB. Also, these attenuators may be connected with either terminal as input or output.

## Basic design

A departure from the usual attenuator design has resulted in an accurate, compact, and rugged attenuator with low insertion loss and low SWR. Error is reduced to a minimum

on all steps. Attenuator sections are inserted and removed by camactuated microswitches which keep lead lengths short. This system minimizes stray capacitances and inductances and extends the upper frequency limit of the 355 attenuators to 1000 MHz. In addition, the phase shift is kept at a minimum. Electrical length for the 355 C/D is approximately 60 cm at 0 dB (no sections engaged). For each section engaged, the electrical length decreases approximately 2 cm.



Agilent Technologies

In addition, the design provides a rugged, compact unit in which the component parts are rigidly positioned and well shielded so that neither stray pickup nor signal leakage is a problem. The 355 attenuators are available for either bench or panel mounting (Option 003). To enable the attenuator to be panel mounted, the shaft has been extended 0.18 in. and the casting drilled and tapped for (4) 6-32 screws. Remotely programmable units are also available under model numbers 355E and 355F.

## Specifications

### Model 355C

**Attenuation:** 12 dB in 1-dB steps.

**Frequency range:** DC to 1000 MHz.

**Overall accuracy:**  $\pm 0.1$  dB at 1000 MHz;  
 $\pm 0.25$  dB dc, to 500 MHz;  $\pm 0.35$  dB, dc to 1000 MHz.

### Model 355D

**Attenuation:** 120 dB in 10-dB steps.

**Frequency range:** DC to 1000 MHz.

**Overall accuracy:**  $\pm 0.3$  dB to 120 dB at 1000 Hz;  
 $\pm 1.5$  dB to 90 dB below 1000 MHz;  $\pm 3$  dB to 120 dB below 1000 MHz.

## For both models

**Impedance:** 50 ohms nominal.

**Power handling capability:** 0.5 watt average, 350 watts peak.

**Maximum SWR** (input and output): 1.2 below 250 MHz;  
1.3 below 500 MHz; 1.5 below 1000 MHz.

**Maximum insertion loss** (insertion loss at 0 dB):  
0.20 dB + 2.30 dB/GHz.

**Dimensions** (maximum envelope, bench or panel mount):  
152 x 71 x 69 mm (6 in. long, 2 13/16 in. wide, 2 11/16 in. high).

**Weight** (bench or panel mount): net, 0.7 kg (1 1/2 lb);  
shipping, 1.4 kg (3 lb).

**Option 001:** 355C, 355D Type-N connectors

**Option 003:** 355C, 355D panel mounting capability

**Option 005:** 355C



### Agilent Email Updates

[www.agilent.com/find/emailupdates](http://www.agilent.com/find/emailupdates)


Get the latest information on the products and applications you select.



### Agilent Direct

[www.agilent.com/find/agilentdirect](http://www.agilent.com/find/agilentdirect)

Quickly choose and use your test equipment solutions with confidence.



[www.agilent.com/find/open](http://www.agilent.com/find/open)

Agilent Open simplifies the process of connecting and programming test systems to help engineers design, validate and manufacture electronic products. Agilent offers open connectivity for a broad range of system-ready instruments, open industry software, PC-standard I/O and global support, which are combined to more easily integrate test system development.

## www.agilent.com

### Agilent Technologies' Test and Measurement Support, Services, and Assistance

Agilent Technologies aims to maximize the value you receive, while minimizing your risk and problems. We strive to ensure that you get the test and measurement capabilities you paid for and obtain the support you need. Our extensive support resources and services can help you choose the right Agilent products for your applications and apply them successfully. Every instrument and system we sell has a global warranty. Two concepts underlie Agilent's overall support policy: "Our Promise" and "Your Advantage."

#### Our Promise

Our Promise means your Agilent test and measurement equipment will meet its advertised performance and functionality. When you are choosing new equipment, we will help you with product information, including realistic performance specifications and practical recommendations from experienced test engineers. When you receive your new Agilent equipment, we can help verify that it works properly and help with initial product operation.

#### Your Advantage

Your Advantage means that Agilent offers a wide range of additional expert test and measurement services, which you can purchase according to your unique technical and business needs. Solve problems efficiently and gain a competitive edge by contracting with us for calibration, extra-cost upgrades, out-of-warranty repairs, and onsite education and training, as well as design, system integration, project management, and other professional engineering services. Experienced Agilent engineers and technicians worldwide can help you maximize your productivity, optimize the return on investment of your Agilent instruments and systems, and obtain dependable measurement accuracy for the life of those products.

**For more information on Agilent Technologies' products, applications or services, please contact your local Agilent office.**

#### Phone or Fax

##### United States:

(tel) 800 829 4444  
(fax) 800 829 4433

##### Canada:

(tel) 877 894 4414  
(fax) 800 746 4866

##### China:

(tel) 800 810 0189  
(fax) 800 820 2816

##### Europe:

(tel) 31 20 547 2111

##### Japan:

(tel) (81) 426 56 7832  
(fax) (81) 426 56 7840

##### Korea:

(tel) (080) 769 0800  
(fax) (080) 769 0900

##### Latin America:

(tel) (305) 269 7500

##### Taiwan:

(tel) 0800 047 866  
(fax) 0800 286 331

##### Other Asia Pacific Countries:

(tel) (65) 6375 8100  
(fax) (65) 6755 0042

Email: [tm\\_ap@agilent.com](mailto:tm_ap@agilent.com)

Contacts revised: 09/26/05

**The complete list is available at:**  
[www.agilent.com/find/contactus](http://www.agilent.com/find/contactus)

Product specifications and descriptions in this document subject to change without notice.

© Agilent Technologies, Inc. 2001, 2006  
Printed in USA, July 13, 2006  
5952-0922



**Agilent Technologies**