

Technical Data Sheet

CAR4A Car/Truck/Air Power Adapter



60 Watt automobile power adapter

Features:

- Wide input voltage range
- Max. output power 72 Watt
- Car/Truck/Air input connector

Applications:

- Suitable for use with tablet PC's, netbooks, handheld devices (e.g. scanner, RFID devices), etc.



Specification

Input	
Voltage range	10.5 - 32VDC
Standby current	typical 77mA @ 10.5V input typical 54mA @ 32V input
Input fuse	10A
Protection	Reverse polarity (input fuse) Under voltage protection (Transient suppression circuit)

Output	
Voltage range	3 - 24V nominal
Power	60W cont. 72W max.
Initial set tolerance	±5% max.
Load regulation ⁽¹⁾	- 100mV max. / A
Line regulation	±1% max.
Ripple & noise ⁽²⁾	< 300mV _{pk-pk}
Current limit	Constant current, 4A max.
Protection	Short circuit Over temperature protection Over voltage protection

Environmental	
Cooling	convection cooled
Temperature	Operating: -20°C to 35°C 35°C to 50°C, derating 35% Non-operating -40°C to 85°C
Pressure & altitude	Operating: 1200hPa to 570hPa max. 4600m above sea level Non-operating: 1200hPa to 115hPa max. 15000m above sea level
Humidity	5 to 95% r.H., non-condensing

General	
Input connector	Cigarette lighter adapter
Output connector	Customer-specific
Efficiency ⁽³⁾	typical 86% at 100% load
MTBF	20000h @ 25°C ambient temperature and G _B per MIL-HDBK217F
Green procurement	WEEE RoHS
Indicator	Single green LED
Ingress protection rating	IEC60529, IP40

Technical Data Sheet

CAR4A Car/Truck/Air Power Adapter



Safety & EMC		
Regulatory approvals	Europe USA/Canada	CE UL60950-1
Electromagnetic emissions	Europe USA	EN 55011/55022 classB, EN55024, EN55014-1 FCC15 class B
	Airborne equipment	RTCA/DO-160D, Section 21
Electromagnetic immunity	ESD immunity	IEC61000-4-2, 4kV contact, 8kV air
	Electromagnetic field immunity	IEC61000-4-3, 80-1000MHz, 10V/m, AM 80% 1kHz, PM ED50% 200Hz
	Electrical fast transient/burst immunity test	IEC61000-4-4, +/-1kV, 5/50ns
	Surge immunity test	IEC61000-4-5, +/-0.5kVsym, 1.2/50(8/20) μ s
	Conducted Immunity	IEC61000-4-6, 0.15-80MHz, 10V, 80%, 1KHz, AM, CDN-M2
	Immunity	IEC61000-6-1
	Impulses	DIN40839 part 1
	Airborne equipment	RTCA/DO-160D Section 20
	UNECE vehicle regulation	E13 ECE Reg. 10

- other approvals on request

Mechanical Details	
Housing dimensions (LxWxH)	111 x48 x 35mm, without cables and connectors
Input cable length	100cm $\pm$ 5%
Output cable length	100cm $\pm$ 5%
Weight	approx. 200g, without cables and connectors

Notes

1. Load regulation is measured at the output connector and includes the voltage drop across the output cable.
2. Measured with a 0.1 μ F ceramic and a 10 μ F electrolytic capacitors across the output terminals. The oscilloscope bandwidth is set at 20MHz a co-axial cable will be used to measure it. The test condition is maximum load.
3. Power losses of input and output cables are not considered here.

Germany/Headquarters	France	USA	Hong Kong/China
RRC power solutions GmbH Technologiepark 1 D-66424 Homburg / Saar	RRC power solutions SAS 69, rue Louise Michel F-92300 Levallois-Perret	RRC power solutions Inc. 18340 Yorba Linda Blvd., Suite 107-437 Yorba Linda, CA 92886-4104	RRC power solutions Ltd. 9/F Park Tower, 15 Austin Road Tsim Sha Tsui, Kowloon, Hong Kong
Tel.: +49 6841 98090 Fax: +49 6841 9809280 Email: sales@rrc-ps.de Web: www.rrc-ps.de	Tel.: +33 13005 6100 Fax: +33 13005 6101 Email: france@rrc-ps.com Web: www.rrc-ps.com	Tel.: +1 714 777 3604 Fax: +1 714 777 3658 Email: usa@rrc-ps.com Web: www.rrc-ps.com	Tel.: +852 2376 0106 Fax: +852 2376 0107 Email: hkrrc@rrc-ps.cn Web: www.rrc-ps.com