

Q-LS 60

Output

Capacity (VA)	60000
Capacity (Watts)	48000
Output Current (peak Amp) 1 phase (208/120 VAC)	520
Output Current (peak Amp) 1 phase (415/380 VAC)	260
Output Current (peak Amp) 1 phase (480/277 VAC)	208
Output Current (peak Amp) 3 phase (208/120 VAC)	NA
Output Current (peak Amp) 3 phase (415/380 VAC)	NA
Output Current (peak Amp) 3 phase (480/277 VAC)	NA
Nominal Voltage range (3 phase)*	220V Δ / 380V Δ / 460V Δ 208VY / 380 VY / 400VY / 415 VY / 480VY
Nominal Voltage range (1 phase)*	220 / 230 / 240 V, 1p2w or 1p3w
Frequency*	50, 60 or 400 Hz \pm .1%
Frequency tracking	\pm 5% of the input frequency
Output power factor	> 0.8
Output Waveform	High resolution, pure sine wave
Outlets	Terminal block
Single phase output	Yes
3 phase output	Yes

Input

Current (amp) (208 / 120VAC)	216
Current (amp) (415 / 380VAC)	108
Current (amp) (480 / 277VAC)	86
Current (max amp) (120/130 VAC)	272
Current (max amp) (415 / 380VAC)	136
Current (max amp) (480 / 277VAC)	109
Power factor (6 pulse rectifier)	.70 to .80
Power factor (12 pulse rectifier)	.75 to .90
Frequency*	50, 60 or 400 Hz \pm 5 %
Input impedance of entire system	750 m ohm

General

Input and output impedance	5%
UPQ power conditioning topology	Five (5) Stages of Isolation and Conversion, High Frequency, True On-line digital sine wave
Remote power management	Yes

Voltage Regulation

Input voltage range:	208 to 600 VAC
- Full load without using battery	\pm 20%
- Half load without using battery	\pm 25%
Output voltage regulation	\pm 1%

Isolation

Input to output isolation	Dielectric Strength 5 kv, 120 dB
	common mode attenuation
Common-mode noise rejection	Yes
Normal-mode noise rejection	Yes

Suppression

IEEE 587/ANSI 62.41 (North America)	Yes
IEEE 587/ANSI 62.41 (International)	Yes
Joules (energy absorption)	2200
TVSS MOV joule rating	765 Joules per phase
TVSS low pass filter	750 Hz
Peak surge current (amp)	20000
Multi-stage protection	Yes
Reverse inverter impulse protection	54 joules without batteries
IEC	62040-2
FCC	Class A
EN500091-1	Yes
EN500091-2	Yes
EN 60610 (leakage current)	< 1 mA
CE approval	Yes
Conditioning	Yes
Output THD (linear load)	< 2%
Current THD (6 pulse rectifier)	Maximum of 20%
Current THD (12 pulse rectifier)	Maximum of 9%
Input frequency range	50/60 Hz \pm 7 Hz

High Frequency on-Line Inverter

Inverter design	Full bridge
Inverter driver frequency	20 kHz
Inverter regulation	50/60 Hz \pm 0.1 Hz
Overload capacity	>110% continuous
Crest factor	3:1
Transfer time	Zero
Overall system efficiency	93%
Efficiency	> 93%
UPQ to bypass/bypass to UPQ	Zero cross transfer, < 4 mSec (2 mSec minimum)

Rectifier

6 pulse	110 μ s single phase triggering
12 pulse	6.4 kHz pulse width, 80 μ s for 1.7 ms around 11 pulses
Efficiency	0.98
Current limit (amp) (208 / 120VAC)	54

Current limit (amp) (415 / 380VAC)	27
Current limit (amp) (480 / 277VAC)	22

Static Switch

Voltage range	174 VAC - 277VAC (line to neutral)
Frequency range	45 - 55 Hz / 55 - 65 Hz
Efficiency	99.5%
Transfer time - main to inverter	0 ms
Transfer time - inverter to main	0 ms
Transfer time - overload 100%	30 seconds
Transfer time - overload 300%	1 seconds

Battery (standard configurations)

Full load run time 9min/ext. pack)	26 min/(2)B
Half load run time (min/ext. pack)	64 min/(2)B
DC voltage	348 VDC
Recharge time	5 to 8 hours
Battery charger	Constant voltage with current limit
Maximum recharge current (amps)	30
Boost charge	410 / 415 VDC
Float charge	396 / 410 VDC
Battery low voltage	320 / 305 VDC
Battery low stop voltage	295 / 285 VDC
Hot-swappable	Yes

Environmental

Maximum heat dissipation kW	2.6
Maximum heat dissipation BTU/hr	8,875
Operating temperature	32° to 122° F (0° to 50° C)
Humidity	0% - 90% non-condensing
Audible noise	< 65 dBA at 1 meter
Altitude	Less than 6,600 ft 92,000 m) above sea level
De-rating temperature to altitude	39° F / 3,281 ft (4° C / 1,000 m)

Physical

WxDxH	43.5 x 32 x 63 in (1,100 x 800 x 1600 mm)
Weight in lbs (no battery)	1500
Weight in kg (no battery)	680
Battery pack A/B WxDxH (26 Ah)	21.5 x 32 x 63 in (550 x 800 x 1600 mm)
Battery pack A/B weight (26 Ah)	882 lbs (400 kg) / 1765 (800 kg)
Battery pack C/D WxDxH (88 & 100 Ah)	43.5 x 32 x 63 in (1100 x 800 x 1600 mm)
Battery pack C/D weight (88 & 100 Ah)	2375 lb (1077 kg) / 2500 lbs (1134 kg)



Power Innovations Int'l, Inc.
www.power-innovations.com phone: 801-785-4123 fax: 801-785-6999