

InGaAs PIN photodiode with preamp

G12072-54



ROSA type, 1.3 μm , 10 Gbps

Features

- ϕ 1.25 mm sleeve type ROSA (receiver optical sub-assembly)
- High-speed response: 11.3 Gbps
- Low power supply voltage: $V_{cc}=3.3\text{ V}$
- Differential output
- Sensitivity: +5 to -19.5 dBm typ.
- Flexible board interface

Applications

- 8 gigabit fiber channel
- 10 gigabit ethernet (LR)
- SFP + transceiver correspondence

The device is susceptible to static electricity. To prevent the devices from electrostatic damage, take measures against electrostatic charges, such as grounding yourself, the workbench and tools.

Absolute maximum ratings ($T_a=25\text{ }^{\circ}\text{C}$)

Parameter	Symbol	Value	Unit
Supply voltage	V_{cc}	-0.3, +4.0	V
	V_{RSSI}		
Operating temperature*1 *2	T_{opr}	-20 to +90	$^{\circ}\text{C}$
Storage temperature*1	T_{stg}	-40 to +90	$^{\circ}\text{C}$

Note: Absolute maximum ratings are the values that must not be exceeded at any time. If even one of the absolute maximum ratings is exceeded even for a moment, the product quality may be impaired. Always be sure to use the product within the absolute maximum ratings.

*1: No condensation

*2: Case temperature

Recommended operating conditions (Case temperature=-20 to +90 $^{\circ}\text{C}$, no condensation)

Parameter	Symbol	Condition	Value	Unit
Supply voltage	V_{cc}	$V_{cc}\text{-GND}$	2.97 to 3.63	V
	V_{RSSI}	$V_{RSSI}\text{-GND}$	less than 2	V
Spectral response range	λ		1.26 to 1.37	μm
Load resistance	R_L	Capacitive coupling	50	Ω
Data rate	-	NRZ, Mark ratio=1/2	8.5 to 11.3	Gbps

Electrical and optical characteristics (Recommended operating conditions, unless otherwise noted)*3

Parameter	Symbol	Condition	Min.	Typ.	Max.	Unit
Responsivity*4	R	$\lambda=1.31\ \mu\text{m}$, $\text{Pin}=-10\ \text{dBm}$	0.70	0.80	-	A/W
Supply current	I _{cc}	Dark state, $R_L=\infty$	-	28	50	mA
Cutoff frequency	f _c	$\lambda=1.31\ \mu\text{m}$, -3 dB $\text{Pin}=-18\ \text{dBm}$, $f_{\text{ref}}=1\ \text{GHz}$	7.0	10.0	-	GHz
Low cutoff frequency	f _{c-L}	$\lambda=1.31\ \mu\text{m}$, -3 dB $\text{Pin}=-18\ \text{dBm}$, $f_{\text{ref}}=100\ \text{MHz}$ Extinction ratio=6 dB	-	30	100	kHz
Transimpedance*5	T _z	$f=1\ \text{GHz}$, $\text{Pin}=-18\ \text{dBm}$	1.0	2.25	-	k Ω
Minimum receivable sensitivity (average)	P _{min}	11.3 Gbps, $\lambda=1.31\ \mu\text{m}$ PRBS=2 ³¹ -1, BER=10 ⁻¹²	-	-19.5	-17.5	dBm
Maximum receivable sensitivity (average)	P _{max}	Extinction ratio=14 dB	+2	+4	-	dBm
Output amplitude	V _{omax}	Differential, $\text{Pin}=-5\ \text{dBm}$	200	280	400	mV _{pp}
RSSI offset current	I _{RSSI}	Dark state, $R_L=\infty$ $V_{\text{cc}}=3.3\ \text{V}$	2.5	10	17	μA
Optical return loss*6	ORL	$\lambda=1.31\ \mu\text{m}$	12	14	-	dB


*3: Output=capacitive coupling

*4: Responsivity=2×(RSSI output current-RSSI offset current)/Optical input power

*5: Single-ended (V_{out}+) measurement


*6: Metal package type with anti-reflection (ORL≥27 dB) is also available.

Bit error rate




KIRD80472EA

Frequency response



KIRD80473EA


■ Dimensional outlines (unit: mm)




KIRDA0214EA

Eye diagram

$T_a=25\text{ }^{\circ}\text{C}$, Bit rate 11.3 Gbps, PRBS= $2^{31}-1$, NRZ, $\lambda=1.31\text{ }\mu\text{m}$, Extinction ratio 14 dB, $V_{cc}=3.3\text{ V}$



Pin=+2 dBm, 70 mV/div., 20 ps/div.



Pin=-20 dBm, 20 mV/div., 20 ps/div.

Information described in this material is current as of December, 2011.

Product specifications are subject to change without prior notice due to improvements or other reasons. Before assembly into final products, please contact us for the delivery specification sheet to check the latest information.

Type numbers of products listed in the delivery specification sheets or supplied as samples may have a suffix "(X)" which means preliminary specifications or a suffix "(Z)" which means developmental specifications.

The product warranty is valid for one year after delivery and is limited to product repair or replacement for defects discovered and reported to us within that one year period. However, even if within the warranty period we accept absolutely no liability for any loss caused by natural disasters or improper product use.

Copying or reprinting the contents described in this material in whole or in part is prohibited without our prior permission.

HAMAMATSU

www.hamamatsu.com

HAMAMATSU PHOTONICS K.K., Solid State Division

1126-1 Ichino-cho, Higashi-ku, Hamamatsu City, 435-8558 Japan, Telephone: (81) 53-434-3311, Fax: (81) 53-434-5184

U.S.A.: Hamamatsu Corporation: 360 Foothill Road, P.O.Box 6910, Bridgewater, N.J. 08807-0910, U.S.A., Telephone: (1) 908-231-0960, Fax: (1) 908-231-1218

Germany: Hamamatsu Photonics Deutschland GmbH: Arzbergerstr. 10, D-82211 Herrsching am Ammersee, Germany, Telephone: (49) 8152-375-0, Fax: (49) 8152-265-8

France: Hamamatsu Photonics France S.A.R.L.: 19, Rue du Saule Trépu, Parc du Moulin de Massy, 91882 Massy Cedex, France, Telephone: 33-(1) 69 53 71 00, Fax: 33-(1) 69 53 71 10

United Kingdom: Hamamatsu Photonics UK Limited: 2 Howard Court, 10 Tewin Road, Welwyn Garden City, Hertfordshire AL7 1BW, United Kingdom, Telephone: (44) 1707-294888, Fax: (44) 1707-325777

North Europe: Hamamatsu Photonics Norden AB: Smidesvägen 12, SE-171 41 Solna, Sweden, Telephone: (46) 8-509-031-00, Fax: (46) 8-509-031-01

Italy: Hamamatsu Photonics Italia S.R.L.: Strada della Moia, 1 int. 6, 20020 Arese, (Milano), Italy, Telephone: (39) 02-935-81-733, Fax: (39) 02-935-81-741

China: Hamamatsu Photonics (China) Co., Ltd.: 1201 Tower B, Jiaming Center, No.27 Dongsanhuan Beilu, Chaoyang District, Beijing 100020, China, Telephone: (86) 10-6586-6006, Fax: (86) 10-6586-2866