

S1L6R Pin Diode Switch


Single Pole, Single Throw

Reflective



Features:

- Incorporated TTL-compatible driver for convenient system integration and operates from +5V and -15V DC power supplies.
- DC blocks at all RF ports.
- Ruggedized construction.
- RoHS-compliant versions available.
- Hermetic versions available.



Specifications:

| Parameter | Specification | Units |
|------------------------------|---------------|-------|
| Frequency Range | 1 – 14 | GHz |
| Insertion Loss (max) | 2.2 | dB |
| VSWR (max) 50 ohms | 2.0 | ratio |
| Isolation (min) | 65 | dB |
| Switching Speed (max) | 100 | nsec |
| CW RF Power, Operating (max) | 0.5 | W |

Notes:

| | |
|-----------------------|--|
| DC Bias: (Standard) | +5V +/-0.5V @ 50 mA max -15V +/-3V @ 50 mA max |
| DC Bias: (-5 option) | +5V +/-0.5V @ 60 mA max -5V +/-0.5V @ 60 mA max |
| DC Bias: (-12 option) | +15V +/-3V @ 50 mA max -15V +/-3V @ 50 mA max |
| Control: | TTL 0 = Low Loss TTL 1 = Isolation |

Switching speed is defined as 50% TTL to 90% RF (t-on) and 50% TTL to 10% RF (t-off).

Environmental Specifications:

| | |
|--------------------------------------|-----------------------------|
| MIL-E-5400, MIL-STD-202, MIL-E-16400 | |
| Operating Temp: | -55 °C to +85 °C |
| Storage Temp: | -65 °C to +125 °C |
| Humidity: | MIL-STD-202F, M103, Cond B |
| Shock: | MIL-STD-202F, M213, Cond B |
| Altitude: | MIL-STD-202F, M105, Cond B |
| Vibration: | MIL-STD-202F, M204, Cond B |
| Thermal Shock: | MIL-STD-202F, M107, Cond A |
| Temperature Cycle: | MIL-STD-202F, M105C, Cond D |

Mechanical Specifications:

| | |
|----------------------|------------------------------------|
| Case Style: | S1 Outline |
| Finish: | Gold Plate per MIL-G-45204 |
| Bias & Control Pins: | ø0.02" x 0.15" long |
| Weight: | 20 g max |
| Mounting: | ø0.10" through holes (4) places |


Screening:

Internal Visual per MIL-STD-883, Method 2017
Temperature Cycle: -65 °C to +100 °C, 10 cycles

Hermetically-sealed switches are fine and gross leak checked per MIL-STD-883, Method 1014.

Optional High-Rel screening available upon request. Contact the factory to discuss your screening requirements.

Outline Drawing:



Part Number Ordering Information:

- Add "-RC" suffix: RoHS-compliant
- Add "-H" suffix: Hermetic seal
- Add "-5" suffix: +/-5V DC supplies
- Add "-5-RC" suffix: +/-5V DC supplies, RoHS-compliant
- Add "-5-H" suffix: +/-5V DC supplies, Hermetic seal
- Add "-12" suffix: +/-15V DC supplies
- Add "-12-RC" suffix: +/-15V DC supplies, RoHS-compliant
- Add "-12-H" suffix: +/-15V DC supplies, Hermetic seal

Aeroflex Control Components
 Aeroflex Microelectronic Solutions
 40 Industrial Way East
 Eatontown, NJ 07724 [USA]
 Fax: (732) 460-0214

Sales
 Phone: (732) 460-0212
 ACC-sales@aeroflex.com

www.aeroflex.com/Microwave www.aeroflex.com/ACC

Aeroflex Control Components reserves the right to make changes to any products and services herein at any time without notice. Consult Aeroflex or an authorized sales representative to verify that the information in this data sheet is current before using this product. Aeroflex does not assume any responsibility or liability arising out of the application or use of any product or service described herein, except as expressly agreed to in writing by Aeroflex; nor does the purchase, lease, or use of a product or service from Aeroflex convey a license under any patent rights, copyrights, trademark rights, or any other of the intellectual rights of Aeroflex or of third parties.

Copyright 2011 Aeroflex Control Components. All rights reserved.

ISO 9001:2008 certified



Our passion for performance is defined by three attributes represented by these three icons: solution-minded, performance-driven and customer-focused.