


Features

- Built-in current limiting resistor for direct application of different across current.
- Long life.
- Low current, power savings.
- Low maintenance.
- Different color available.
- Solid state, high vibration resistant.
- 6V internal resistor.
- RoHS compliant.

Description

The Mega Green source color devices are made with Al-GaN on GaAs substrate Light Emitting Diode.

Package Dimensions



Notes:

1. All dimensions are in millimeters (inches).
2. Tolerance is $\pm 0.25 (0.01)$ unless otherwise noted.
3. The specifications, characteristics and technical data described in the datasheet are subject to change without prior notice.



Selection Guide

Part No.	Dice	Lens Type	Iv (mcd) V= 6V		Viewing Angle
			Min.	Typ.	2 θ 1/2
BLS101MGC-6V-P	Mega Green (AlGaInP)	Water Clear	1000	2000	20°

Note:


1. θ 1/2 is the angle from optical centerline where the luminous intensity is 1/2 of the optical peak value.

Electrical / Optical Characteristics at TA=25°C

Symbol	Parameter	Device	Typ.	Max.	Units	Test Conditions
λ_{peak}	Peak Wavelength	Mega Green	574		nm	V _F =6V
λ_D	Dominant Wavelength	Mega Green	570		nm	V _F =6V
$\Delta\lambda_{1/2}$	Spectral Line Half-width	Mega Green	26		nm	V _F =6V
I _F	Forward Current	Mega Green	20	25	mA	V _F =6V
I _R	Reverse Current	Mega Green		10	uA	V _R = 5V





Absolute Maximum Ratings at TA=25°C

Parameter	Mega Green	Units
Power dissipation	175	mW
Forward Voltage	7	V
Reverse Voltage	5	V
Operating Temperature	-40°C To +70°C	
Storage Temperature	-40°C To +85°C	




Mega Green

BLS101MGC-6V-P



PACKING & LABEL SPECIFICATIONS

BLS101MGC-6V-P



Kingbright	
P/NO:BLS101xxx	
QTY: 100 pcs	Q.C. Q C xx xx xxxx PASSED
S/N: XXXX	
CODE: XXX	
LOT NO:	
 xxxxxxxxxxxxxxxxxxxxxx	
RoHS Compliant	