

Green

- 1.2 inch character height .
- Low current operation.
- High contrast and light output.
- Easy mounting on P.C. boards or sockets.
- Categorized for luminous intensity.
- Mechanically rugged.
- Standard:gray face, white segment.
- RoHS compliant.

The Green source color devices are made with AlGaInP on GaAs substrate Light Emitting Diode.



Selection Guide

Part No.	Dice	Lens Type	Iv (ucd) [1] @ 10mA		Description
			Min.	Typ.	
PSC12-11CGKWA	Green (AlGaInP)	White Diffused	14000	37000	Common Cathode, Rt. Hand Decimal.

Note:

1. Luminous intensity/ luminous Flux: +/-15%.

Electrical / Optical Characteristics at TA=25°C

Symbol	Parameter		Device	Typ.	Max.	Units	Test Conditions
λ peak	Peak Wavelength		Green	574		nm	If=20mA
λ D[1]	Dominant Wavelength		Green	570		nm	If=20mA
$\Delta\lambda$ 1/2	Spectral Line Half-width		Green	20		nm	If=20mA
C	Capacitance		Green	15		pF	V _F =0V;f=1MHz
V _F [2]	Forward Voltage	c,d,g,h,k,m,n,s,r,t	Green	4.2	5	V	If=20mA
		a,b,e,f,p,u and DP		2.1	2.5		
I _R	Reverse Current	c,d,g,h,k,m,n,s,r,t	Green		10	uA	V _R = 5V
		a,b,e,f,p,u and DP			10	uA	

Notes:

1.Wavelength: +/-1nm.

2. Forward Voltage: +/-0.1V.


Absolute Maximum Ratings at TA=25°C

Parameter		Green	Units
Power dissipation	c,d,g,h,k,m,n,s,r,t	150 (75)	mW
	a,b,e,f,p,u and DP		
DC Forward Current	c,d,g,h,k,m,n,s,r,t	30 (30)	mA
	a,b,e,f,p,u and DP		
Peak Forward Current [1]	c,d,g,h,k,m,n,s,r,t	150 (150)	mA
	a,b,e,f,p,u and DP		
Reverse Voltage	c,d,g,h,k,m,n,s,r,t	5	V
	a,b,e,f,p,u and DP		
Operating / Storage Temperature		-40°C To +85°C	
Lead Solder Temperature[2]		260°C For 3-5 Seconds	

Notes:





1. 1/10 Duty Cycle, 0.1ms Pulse Width.

2. 2mm below package base.







Green

PSC12-11CGKWA




Note: the curves are on the segment c,d,g,h,k,m,n,s,r and t.




Note:the curves are on the segment a,b,e,f,p,u and DP.

PACKING & LABEL SPECIFICATIONS


PSC12-11CGKWA



Inside Label On IC-tube

Kingbright	TYPE: PSx12-11xxx	PASSED xx xx xx FQCX	Date
	QTY: 12 PCS CODE: xx		
		Number OF FQC	
XXXXXXXXXX-XXXX			
LOT NO.		RoHS Compliant	


Outside Label On Box

XXXXXX		Bin Code	Number OF QA
PSx12-11xxx			
756 PCS	XX	QA xx xx xx PASSED	Date
RoHS Compliant			

THROUGH HOLE DISPLAY MOUNTING METHOD


Lead Forming

Do not bend the component leads by hand without proper tools.
The leads should be bent by clinching the upper part of the lead firmly such that the bending force is not exerted on the plastic body.




Installation

- 1.The installation process should not apply stress to the lead terminals.
- 2.When inserting for assembly, ensure the terminal pitch matches the substrate board's hole pitch to prevent spreading or pinching the lead terminals.



DISPLAY SOLDERING CONDITIONS

Wave Soldering Profile For Lead-free Through-hole LED.



NOTES:

- 1.Recommend the wave temperature 245°C~260°C.The maximum soldering temperature should be less than 260°C.
- 2.Do not apply stress on epoxy resins when temperature is over 85°C.
- 3.The soldering profile apply to the lead free soldering (Sn/Cu/Ag alloy).
- 4.During wave soldering , the PCB top-surface temperature should be kept below 105°C
- 5.No more than once.

Soldering General Notes:

- a. Through-hole displays are incompatible with reflow soldering.
- b. If components will undergo multiple soldering processes, or other processes where the components may be subjected to intense heat, please check with Kingbright for compatibility.

CLEANING

1. Mild "no-clean" fluxes are recommended for use in soldering.
2. If cleaning is required, Kingbright recommends to wash components with water only. Do not use harsh organic solvents for cleaning, because they may damage the plastic parts. And the devices should not be washed for more than one minute.

CIRCUIT DESIGN NOTES

1. Protective current-limiting resistors may be necessary to operate the Displays.
2. LEDs mounted in parallel should each be placed in series with its own current-limiting resistor.

