

Shock-Safe Fuseholder, 5 x 20 mm, Fingergrip, Solder



250 VAC · 1.3W

**Description**

- Screw type fuse carrier

**Weblinks**

[pdf-datasheet](#), [html-datasheet](#), [General Product Information](#), [Approvals](#), [RoHS](#), [CHINA-RoHS](#), [e-Shop](#), [SCHURTER-Stock-Check](#), [Distributor-Stock-Check](#), [Detailed request for product](#)



**Technical Data**

Fuse-Link	5 x 20 mm
Mounting	Panel Mount, Front-Side
Mounting	Fixing Nut
Terminal	Solder
Rated Voltage	250VAC
Rated Current	6.3A
Rated Power Acceptance IEC	1.3W @ Ta 23°C
Degree of Protection	IP 40
Material: Socket	Thermoset, black
Material: Cap	Thermoplastic, black
Unit Weight (Socket/Cap)	8 g
Storage Conditions	0°C to 60°C, max. 70% r.h.
Product Marking	Dielectric strength, Current

Soldering Methods	Iron
Resistance to Vibration	acc. to NF C 20-706 / IEC 60068-2-6, test Fc
Admissible Torque on Fixing Nut	max 1.0Nm
Panel Thickness s	max 5 mm

**Dimensions**

38 mm



Mounting holes

**Variants**

Holder	Cap	Degree of Protection	Order Number
●	Fingergrip	IP 40	7091.3120

**Packaging Unit**

Bulk (10 pcs.)