

Clip, 5 x 20 mm, Version 2



250 VAC

**Description**

- Through hole mounting

**Weblinks**

[pdf-datasheet](#), [html-datasheet](#), [General Product Information](#), [Approvals](#), [RoHS](#), [CHINA-RoHS](#), [e-Shop](#), [SCHURTER-Stock-Check](#), [Distributor-Stock-Check](#), [Detailed request for product](#)

**Technical Data**

Fuse-Link	5 x 20 mm
Mounting	PCB
Terminal	Solder THT
Rated Voltage	250 VAC
Rated Current	6.3 A
Degree of Protection	IP 00
Material: Terminals	see variants
Unit Weight (Socket/Cap)	0.7 g
Storage Conditions	0 °C to 60 °C, max. 70% r.h.
Product Marking	none

Soldering Methods	Wave
Solderability	235 °C / 2 sec acc. to IEC 60068-2-20, Test Ta, method 1
Resistance to Soldering Heat	260 °C / 10 sec acc. to IEC 60068-2-20, Test Tb, method 1A

**Dimensions**

7.1 mm



Drilling diagram

**Variants**

Clip	Terminal	Material: Terminals	Order Number
●	Straight	Tin-Plated Bronze	7141.2001

**Packaging Unit** Bulk (100 pcs.)