



## Analog Performance Characteristics

Parameter	Minimum	Typical	Maximum	Units
<b>Line Outputs</b>				
Full Scale Output Voltage		1.0		Vrms
Dynamic Range (measured with -60 dBFS signal present)		100		dBFS
Total Harmonic Distortion + Noise (THD + N)		-85		dB
Channel Crosstalk		-84		dBFS
Analog Frequency Response (+/- 3 dB at 20 Hz, +/- 1 dB at 20000 Hz)	20		20000	Hz
<b>Headphone Output</b>				
Full Scale Output Voltage		1.2		Vrms
Dynamic Range (measured with -60 dBFS signal present)		99		dBFS
Total Harmonic Distortion + Noise (THD + N)		-87		dB
Channel Crosstalk		-75		dBFS
Analog Frequency Response (+/- 3 dB at 20 Hz, +/- 1 dB at 20000 Hz)	20		20000	Hz
<b>Class-D Speaker Amplifier Outputs</b>				
Full Scale Output Voltage (into 4 Ω)	3.96 2.83	4.0 2.90	4.2 3	Vp Vrms
Dynamic Range (measured with -60 dBFS signal present)		94		dBFS
Total Harmonic Distortion + Noise (THD + N, measured at -3 dBFS)		-71		dBFS
Analog Frequency Response (+/- 3 dB at 20 Hz, +/- 1 dB at 20000 Hz)	20		20000	Hz
Efficiency (Measured at 1 W/Ch)		85		%
<b>Microphone/Line Inputs</b>				
Full Scale Input Voltage (With 20 dB boost)	0.1			Vrms
Full Scale Input Voltage (With boost off)	1.0			
Dynamic Range (measured with -60 dBFS signal present)		91		dBFS
Total Harmonic Distortion + Noise (THD + N)		-87		dBFS
Channel Crosstalk (measured at 1 kHz, 0 dB gain)		-84		dBFS
Analog Frequency Response (+/- 3 dB at 200 Hz, +/- 1 dB at 20000 Hz)	200		20000	Hz
Input Resistance				
0 dB		15.8		kΩ
10-40 dB		5.0		
Input Capacitance		5		pF

## Ordering Information

Model/Order/Part Numbers				Supported Functions		Operating Temperature
Device Order Number	Audio Codec Part Number	Revision	Audio Codec Package Type	Integrated Mono Class-D Amplifier	Number of DACs/ADCs	
CX20665-11Z	CX20664	-11Z	48-QFN	Y	6/4	0 to 70 °C

© 2012 Conexant Systems, Inc. All Rights Reserved. Conexant and the Conexant logo are registered trademarks of Conexant Systems, Inc. All other trademarks are owned by their respective owners. Although Conexant strives for accuracy in all its publications, this material may contain errors or omissions and is subject to change without notice. **THIS MATERIAL IS PROVIDED AS IS AND WITHOUT ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NON-INFRINGEMENT.** Conexant shall not be liable for any special, indirect, incidental or consequential damages as a result of its use.

[www.conexant.com](http://www.conexant.com)  
 General Information:  
 U.S. and Canada: (888) 855-4562  
 International: 1+ (949) 483-3000  
 Headquarters  
 4000 MacArthur Blvd.  
 Newport Beach, CA 92660  
 Doc# PBR-203100



**CONEXANT**