

FST08T200-T1-4RT

8.4", 800 x 600 SVGA, Fully Sealed Stainless Steel Monitor with Four-Wire Resistive Touchscreen and VGA Port



Features and Benefits

- Brushed stainless steel enclosure
- IP65 sealed, with anti-corrosive rubber providing 360 degree protection
- Full IP65 I/O connectors protect from any particles, water, and corrosive agents
- Technical support for drivers (installing, and supporting files) and hardware (screens, monitors, controllers, peripherals), including troubleshooting procedures and general system issues
- Customer service and sales support help with product selection, order management, and warranty status

Introduction

The AIS 8.4" rugged touch monitor features industrial-duty fully sealed NEMA 4/IP65 stainless steel chassis, for use in OEM and process manufacturing. These units offer extra protection from extensive corrosive environments with the intrusion of dust, rain, hose directed water, and applications where corrosive materials and caustic cleaners are used. General applications include: sanitary poultry processing facilities, petro-chemical refineries and offshore drilling platforms for oil and natural gas. The ruggedized touchscreen displays are specially designed for hygienic and harsh environments.

Specifications

Display	
Display	8.4" diagonal, Active matrix TFT LCD
Aspect Ratio	4:3
Active/Area	170.4 (H) x 127.8 (V) mm
Native (Optimal) Resolution	800 x 600
General Supported Resolution	VGA 640 x 480 (60/66/70/72/75 Hz) SVGA 800 x 600 (60/70/72/75 Hz)
Colors	16.2M (8 bits + FRC)
Brightness (Typical)	LCD Panel: 450 nits Resistive Touch: 360 nits
Contrast Ratio	600:1
Viewing Angle	Horizontal: 160° Total Vertical: 140° Total
On-Screen Display (OSD)	Controls (back): menu, up, down, select, power Settings: contrast, brightness, H/V position, RGB (color temp), clock, phase, recall
Input Video Format	Analog VGA
Input Video Signal Connector	Mini D-Sub 15-Pin VGA Type

Touch Technology	Resistive (USB (Type-B): Touch Interface)
General	
Power Consumption (Typical)	25W
MTBF	50,000 Hours Demonstrated
Mounting Options	75 mm VESA mount
Input Voltage	AC: 100-240 VAC, 50/60 Hz DC: 12.0 V±10%
Environmental Conditions	
Temperature	Operating: 0°C to 40°C (32°F to 104°F) Storage: -20°C to 60°C (-4°F to 140°F)
Humidity (Non-condensing)	Operating: 20%-80% Storage: 10%-90%
Approvals	
Approvals	CE, FCC (DOC)

Order Information

FST08T200-T1-4RT: 8.4" Fully Sealed Stainless Steel Monitor with Four-Wire Resistive Touchscreen, 800 x 600 SVGA, 600:1 contrast ratio and VGA Port

Unit: mm

