


MR17ID3S-M1-5RT

17" color TFT, 1280 x 1024 SXGA, Intel® Atom™ Dual Core N2600 Marine Touch Panel Computer Compliance with IEC 60945, DNV 2.4, and IACS-E10



Introduction

AIS 17" marine touch panel computers and operator interface terminals comply with marine equipment standards meeting the demands of IEC 60945, DNV 2.4, and IACS-E10 (international standard for maritime navigation, radio communications equipment and systems) needed to withstand the harsh maritime environment requiring low EMI or long-term vibration resilience. These are designed for bridge control display, navigation, monitoring and surveillance, and ship automation applications; and comply with anti-shock, anti-vibration.

Specifications

Display	
Display	17" diagonal, Active matrix TFT LCD
Aspect Ratio	4:3
Active/Area	337 (H) x 270 (V) mm
Native (Optimal) Resolution	1280 x 1024 SXGA
Colors	16.7M, 6 bit
Brightness (Typical)	LCD Panel: 350 nits Resistive Touch: 280 nits
Contrast Ratio	1000:1
Viewing Angle	Horizontal: 170° Total Vertical: 160° Total
Touch Technology	Analog Resistive 5-wire
System Hardware	
Processor	Intel® Atom™ Processor N2600 1.60 GHz
System Chipset	Intel® NM10 Express Chipset
System Memory	2GB DDR3 800/1066 MHz, up to 4GB

Features and Benefits

- Aluminum alloy construction with powder coating, ensuring exceptional stability
- Optional Transflective LCD meets sunlight readability requirements for navigation and transportation systems
- Complies with marine/DNV standards IEC 60945, DNV 2.4, and IACS-E10
- Multiple mounting options, i.e. panel, and VESA mounts
- Technical support for drivers, hardware, troubleshooting procedures and general system issues
- Customer service and sales support for product selection, order management, and warranty status

Storage	32GB SATA SSD
I/O Interfaces	
Serial Ports	1 x RS232/422/485, 2 x RS232
USB Ports	2 x USB 2.0
Ethernet Ports	2 x RJ 45-10/100/1000 Mbps
VGA Port	1 x VGA
Environmental Conditions	
Temperature	Operating: -10°C to 55°C (14°F to 131°F) Storage: -20°C to 60°C (-4°F to 140°F)
Humidity (Non-condensing)	10 to 95% RH @ 40° C
Vibration Protection	5Hz~500Hz / 1Grms / 3 Axis
General	
Power Input	9V to 36V DC
Operation System Support	Windows Embedded Standard 7 Windows XP Embedded
Mounting Options	75 x 75 mm VESA Mount
Dimensions (W x L x H)	460.1 x 410 x 77.2 mm
Approvals	
Approvals	CE, FCC (DOC) DNV standards IEC 60945, DNV 2.4, and IACS-E10

Order Information

MR17ID3S-M1-5RT: 17" Intel® Atom™ Dual Core N2600 Marine Touch Panel Computer Compliance with IEC 60945, DNV 2.4, and IACS-E10, 1280 x 1024 SXGA, 1000:1 contrast ratio

MR17ID3S-M1-5RT

Dimensions

Unit: mm

