

FEATURES

- Fixed and Adjustable Versions Available
- Output Current in excess of 150mA
- Very Low Quiescent Current
- Reverse Battery Protection
- Input-output Differential less than 0.6V
- Short Circuit protection
- Internal Thermal Overload Protection
- 60V Load Dump Protection
- -50V Reverse Transient Protection
- Mirror Image Insertion Protection

APPLICATIONS

- Battery Powered Systems
- Portable Consumer Equipment
- Cordless Telephones
- Portable (Notebook) Computers
- Portable Instrumentation
- Radio Control Systems
- Automotive Electronics

PRODUCT DESCRIPTION

The AMS2930 series consists of positive fixed and adjustable voltage regulators ideally suited for use in battery-powered systems. These devices feature very low quiescent current of 1mA or less when supplying 10mA loads. This unique characteristic and the extremely low input -output differential required for proper regulation (0.2V for output currents of 10mA) make the AMS2930 ideal to use for standby power systems.

Originally designed for automotive applications, the AMS2930 and all regulated circuitry are protected from input fault conditions caused by reverse battery installation or two battery jump starts. During line transients, such as load dump (60V) when the input voltage to the regulator can momentarily exceed the specified maximum operating voltage, the regulator will automatically shut down to protect both internal circuits and the load. The AMS2930 series also includes internal current limiting, thermal shutdown, and is able to withstand temporary power-up with mirror-image insertion.

The AMS2930 is offered in the 3-pin TO-92 package, 8-pin plastic SOIC, TO-220 and TO-263 packages.

ORDERING INFORMATION

| OUTPUT VOLTAGE | PACKAGE TYPE | | | | OPER. TEMP RANGE |
|-------------------|--------------|-------------|-------------|-------------|---------------------|
| | TO-92 | 8 LEAD SOIC | TO-220 | TO-263 | |
| FIXED* | AMS2930AN-X | AMS2930AS-X | AMS2930AT-X | AMS2930AM-X | -40°C to +85°C |
| | AMS2930N-X | AMS2930S-X | AMS2930T-X | AMS2930M-X | -40°C to +85°C |
| ADJ. | | AMS2930CS | | | -40°C to +85°C |

X = 2.0V, 2.5V, 3.0V, 3.3V, 3.5V, 4.0V, 5.0V

*For additional available fixed voltages contact factory

ABSOLUTE MAXIMUM RATINGS (Note 1)

| | | |
|-------------------------------------|--------------------|--|
| Overvoltage Protection | | |
| AMS2930A-X, AMS2930C | 60V | |
| AMS2930-X | 50V | |
| Maximum Input Voltage | 22V | |
| Internal Power Dissipation (Note 4) | Internally Limited | |
| Reverse Voltage (100ms) | -12V | |
| Storage Temperature | -65°C to +150°C | |

OPERATING CONDITIONS (Note 1)

| | |
|---------------------------------|-----------|
| Input voltage range | 4V to 22V |
| Junction Temperature | +125°C |
| Lead Temperature (Sold. 25 sec) | 265°C |
| ESD | 2000V |

ELECTRICAL CHARACTERISTICS

Electrical Characteristics at $V_{IN}=14V$, $T_J=25^\circ C$, $C_2 = 100\mu F$ unless otherwise specified.

| PARAMETER | CONDITIONS | AMS2930A-X | | | AMS2930-X | | | Units |
|---|--|------------|------|------|-----------|-----------|------|---------------|
| | | Min. | Typ. | Max. | Min. | Typ. | Max. | |
| Fixed Output Voltage Versions | | | | | | | | |
| Output Voltage Tolerance | | -1.0 | | +1.0 | -3.0 | | +3.0 | % |
| | $6V \leq V_{IN} \leq 26V$, $I_O=100\text{ mA}$ $-40^\circ C \leq T_J \leq 125^\circ C$ | -3.0 | | +3.0 | | ± 5.0 | | % |
| Line Regulation | $9V \leq V_{IN} \leq 16V$ | | 2 | 10 | | 2 | 10 | mV |
| | $6V \leq V_{IN} \leq 26V$ | | 4 | 30 | | 4 | 30 | mV |
| Load Regulation | $5\text{mA} \leq I_O \leq 150\text{ mA}$ | | 14 | 50 | | 14 | 50 | mV |
| Dropout Voltage | $I_O = 10\text{ mA}$ | | 50 | 200 | | 50 | 200 | mV |
| | $I_O = 150\text{ mA}$ | | 300 | 600 | | 300 | 600 | mV |
| Quiescent Current | $I_O \leq 10\text{ mA}$, $6V \leq V_{IN} \leq 26V$ $-40^\circ C \leq T_J \leq 125^\circ C$ | | 0.4 | 1.0 | | 0.4 | 1.0 | mA |
| | $I_O = 150\text{ mA}$, $V_{IN} = 14V$, $T_J = 25^\circ C$ | 5 | 15 | 30 | | 15 | | mA |
| Output Noise Voltage | 10Hz-100kHz, $C_{OUT} = 100\mu A$ | | 500 | | | 500 | | μV_{rms} |
| Output Impedance | 100mA _{DC} and 10mA _{rms} , 100Hz=10kHz | | 160 | 200 | | 160 | 200 | m Ω |
| Long Term Stability | T = 1000hr | | 20 | | | 20 | | mV |
| Ripple Rejection | $f_O = 120\text{Hz}$ | 55 | 80 | | | 80 | | dB |
| Maximum Line Transient | $R_L = 500\Omega$, $V_O \leq 5.5V$ T = 1ms, $\tau \leq 100\text{ms}$ | 60 | 70 | | 50 | 70 | | V |
| Reverse Polarity Input Voltage, D/C | | -15 | -30 | | -15 | -30 | | V |
| Reverse Polarity Input Voltage, Transient | $R_L = 500\Omega$, T = 1ms, $\tau \leq 100\text{ms}$ | -50 | -80 | | -50 | -80 | | V |

Electrical Characteristics

Electrical Characteristics at $V_{IN}=14V$, $V_{OUT}=3V$, $I_O=150mA$, $T_J=25^\circ C$, $R1=27k$, $C2=100\mu F$ unless otherwise specified.

| PARAMETER | CONDITIONS (Note 2) | Min. | AMS2930C | | Units |
|---|--|-------------|-------------|----------|-----------------|
| | | | Typ. | Max. | |
| Adjustable Version | | | | | |
| Reference Voltage | | 1.14 | 1.20 | 1.26 | V |
| | $I_O \leq 150\text{ mA}$, $-40^\circ C \leq T_J \leq 125^\circ C$, $R1=27k$, Measured from V_{OUT} to Adjust Pin | 1.08 | 1.32 | | V |
| Output Voltage Range | | 3 | 24 | | V |
| Line Regulation | $V_{OUT} + 0.6V \leq V_{IN} \leq 26V$ | | .02 | 1.5 | mV |
| Load Regulation | $5mA \leq I_O \leq 150\text{ mA}$ | | 0.3 | 1 | % |
| Dropout Voltage | $I_O \leq 10\text{ mA}$ | | 0.05 | 0.2 | V |
| | $I_O = 150\text{ mA}$ | | 0.3 | 0.6 | V |
| Quiescent Current | $I_O = 10\text{ mA}$ | | 0.4 | 1 | mA |
| | $I_O = 150\text{ mA}$ | | 15 | | mA |
| | During Shutdown $R_L = 500\Omega$ | | 0.8 | 1 | mA |
| Output Noise Voltage | 10Hz-100kHz | | 100 | | $\mu V_{rms}/V$ |
| Output Impedance | 100mA _{DC} and 10mA _{rms} , 100Hz=10kHz | | 40 | | m Ω |
| Long Term Stability | T = 1000hr | | 0.4 | | %/1000hr |
| Ripple Rejection | $f_O = 120\text{ Hz}$ | | 0.02 | | %/V |
| Maximum Operating Input Voltage | | | 21 | 22 | V |
| Maximum Line Transient | $I_O = 10\text{ mA}$, Reference Voltage $\leq 1.5V$ T = 1ms, $\tau \leq 100\text{ ms}$ | 60 | 70 | | V |
| Reverse Polarity Input Voltage, D/C | $R_L = 500\Omega$, $V_O \geq -0.3V$ | -15 | -30 | | V |
| Reverse Polarity Input Voltage, Transient | $R_L = 500\Omega$, T = 1ms, $\tau \leq 100\text{ ms}$ | -50 | -80 | | V |
| On/Off Threshold Voltage | $V_O = 3V$ | | | | |
| | | On | | 2.0 | 1.2 |
| Off | | 3.25 | 2.2 | | V |
| On/Off Threshold Current | | | 20 | 50 | μA |

Note 1: Absolute Maximum Ratings are limits beyond which damage to the device may occur. For guaranteed performance limits and associated test conditions, see the Electrical Characteristics tables.

Note 2: See Circuit in Typical Applications. To ensure constant junction temperature, low duty cycle pulse testing is used.


Note 3: Limits appearing in **boldface** type apply over the entire junction temperature range for operation. Limits appearing in normal type apply for $T_A = T_J = 25^\circ C$.

Note 4: The junction-to-ambient thermal resistance are as follows: $195^\circ C/W$ for the TO-92 (N) package, $160^\circ C/W$ for the molded plastic SO-8 (S), $50^\circ C/W$ for the TO-220 package and $73^\circ C/W$ for the TO-263 package. If the TO-220 package is used with a heat sink, θ_{JA} is the sum of the package thermal resistance junction-to-case of $3^\circ C/W$ and the thermal resistance added by the heat sink and the thermal interface. The thermal resistance of the TO-263 package can be reduced by increasing the PCB copper area thermally connected to the package: using 0.5 square inches of copper area, ϕ_{JA} is $50^\circ C/W$; with 1 square inch of copper area ϕ_{JA} is $37^\circ C/W$; and with 1.6 or more square inches of copper area ϕ_{JA} is $32^\circ C/W$.

PIN CONNECTIONS


FIXED OUTPUT VOLTAGE

**TO-92
Plastic Package (N)**




Bottom View

**8L SOIC
SO-Package (S)**




Top View

TO-220 (T)



Front View


TO-263 (M)



Top View

ADJUSTABLE OUTPUT VOLTAGE


**8L SOIC
SO-Package (S)**



Top View

TYPICAL APPLICATIONS


AMS2930-X (Fixed Output)



*Required if regulator is located far from power supply filter.

**C2 must be at least 100µF to maintain stability; it can be increased without bound to maintain regulation during transients and it should be located as close as possible to the regulator. This capacitor must be rated over the same operating temperature range like the regulator. The ESR of this capacitor is critical (see curve) and it should be less than 1Ω over the expected operating temperature range.










AMS2930C (Adjustable Output)












$$V_{OUT} = V_{REF} \times (R_1 + R_2) / R_1$$

Note: Using 27k for R1 will automatically compensate for errors in V_{OUT} due to the input bias current of the Adjust Pin (approx. 1µA)


TYPICAL PERFORMANCE CHARACTERISTICS



TYPICAL PERFORMANCE CHARACTERISTICS (Continued)



TYPICAL PERFORMANCE CHARACTERISTICS (Continued)



APPLICATION HINTS

The AMS2930 series require an output capacitor for device stability. The value required depends on the application circuit and other factors.

Because high frequency characteristics of electrolytic capacitors depend greatly on the type and even the manufacturer, the value of capacitance that works well with AMS2930 for one brand or type may not necessary be sufficient with an electrolytic of different origin. Sometimes actual bench testing will be the only means to determine the proper capacitor type and value. To obtain stability in all general applications a high quality 100 μF aluminum electrolytic or a 47 μF tantalum electrolytic can be used.

A critical characteristic of the electrolytic capacitors is their performance over temperature. The AMS2930 is designed to operate to -40°C, but some electrolytics will freeze around -30°C therefore becoming ineffective. In such case the result is oscillation at the regulator output. For all application circuits where cold operation is necessary, the output capacitor must be rated to operate at the minimum temperature. In applications where the regulator junction temperature will never be lower than 25°C the output capacitor value can be reduced by a factor of two over the value required for the entire temperature range (47 μF for a high quality aluminum or 22 μF for a tantalum electrolytic capacitor).

With higher output currents, the stability of AMS2930 decreases. Considering the fact that in many applications the AMS2930 is operated at only a few milliamps (or less) of output current, the output capacitor value can be reduced even further. For example, a circuit that is required to deliver a maximum of 10mA of output current from the regulator output will need an output capacitor of only half the value compared to the same regulator required to deliver the full output current of 150mA.

In the case of AMS2930C (adjustable), the minimum value of output capacitance is a function of the output voltage. As a general rule, with higher output voltages the value of the output capacitance decreases, since the internal loop gain is reduced.

In order to determine the minimum value of the output capacitor, for an application circuit, the entire circuit including the capacitor should be bench tested at minimum operating temperatures and maximum operating currents. To maintain internal power dissipation and die heating to a minimum, the input voltage should be maintain at 0.6V above the output. Worst-case occurs just after input power is applied and before the die had the chance to heat up. After the minimum capacitance value has been found for the specific brand and type of electrolytic capacitor, the value should be doubled for actual use to cover for production variations both in the regulator and the capacitor.

