


Standard Nylon Cable Ties




Features

- Low Insertion and Pull Through Force
- One Piece Design for High Tensile Strength
- Advanced Pawl and Teeth Design
- Angled Tail for Quicker Initial Insertion Alignment
- Tail Finger Grips for Easier Handling and Tightening
- Rounded Safety Edges Eliminate Insulation Damage



WT-01



Color Code Chart

0	UV Black	11	Fluorescent Green
1	Brown	12	Fluorescent Pink
2	Red	13	Fluorescent Yellow
3	Orange	14	Fluorescent Orange
4	Yellow	15	Fluorescent Blue
5	Green	30	Heat Stabilized Black
6	Blue		
7	Purple		
8	Gray		
9	Natural		

18 lb. Miniature (4" ties available in all colors, **ALL OTHERS** available in colors 0, 9, and 30 **ONLY**, Note 5)

NTE Type No.	Length	Width	Thickness	Max. Bundle Dia. (Note 3)	Mil Spec (Note 4)	Qty. per Bag	Diag No.
04-0418xx	4.12 / 104.77	.095 / 2.413	.042 / 1.066	.875 / 22.225	MS3367-4	100	WT-01
04-0418xxM	4.12 / 104.77	.095 / 2.413	.042 / 1.066	.875 / 22.225	MS3367-4	1000	WT-01
04-0618xx	6.18 / 157.14	.095 / 2.413	.042 / 1.066	1.500 / 38.10	MS3367-4	100	WT-01
04-0618xxM	6.18 / 157.14	.095 / 2.413	.042 / 1.066	1.500 / 38.10	MS3367-4	1000	WT-01
04-0818xx	8.18 / 207.94	.095 / 2.413	.042 / 1.066	2.187 / 55.562	MS3367-4	100	WT-01
04-0818xxM	8.18 / 207.94	.095 / 2.413	.042 / 1.066	2.187 / 55.562	MS3367-4	1000	WT-01

40 lb. Intermediate (Available in colors 0, 2, 4, 5, 6, and 9 **ONLY**, Note 5)

NTE Type No.	Length	Width	Thickness	Max. Bundle Dia. (Note 3)	Mil Spec (Note 4)	Qty. per Bag	Diag No.
04-0540xx	5.84 / 148.33	.140 / 3.556	.049 / 1.244	1.437 / 36.512	MS3367-5	100	WT-01
04-0540xxM	5.84 / 148.33	.140 / 3.556	.049 / 1.244	1.437 / 36.512	MS3367-5	1000	WT-01

50 lb. Standard (17" ties available in colors 0 and 9 **ONLY**, All other lengths available in all colors, Note 5)

NTE Type No.	Length	Width	Thickness	Max. Bundle Dia. (Note 3)	Mil Spec (Note 4)	Qty. per Bag	Diag No.
04-0750xx	7.56 / 192.07	.180 / 4.572	.052 / 1.320	1.875 / 47.625	MS3367-1	100	WT-01
04-0750xxM	7.56 / 192.07	.180 / 4.572	.052 / 1.320	1.875 / 47.625	MS3367-1	1000	WT-01
04-1150xx	11.25 / 285.75	.180 / 4.572	.052 / 1.320	3.062 / 77.787	MS3367-7	100	WT-01
04-1150xxD	11.25 / 285.75	.180 / 4.572	.052 / 1.320	3.062 / 77.787	MS3367-7	500	WT-01
04-1150xxM	11.25 / 285.75	.180 / 4.572	.052 / 1.320	3.062 / 77.787	MS3367-7	1000	WT-01
04-1450xx	14.56 / 369.87	.180 / 4.572	.052 / 1.320	4.125 / 104.775	MS3367-2	100	WT-01
04-1450xxD	14.56 / 369.87	.180 / 4.572	.052 / 1.320	4.125 / 104.775	MS3367-2	500	WT-01
04-1750xx	17.09 / 434.16	.187 / 4.749	.060 / 1.524	4.750 / 120.65	N/A	100	WT-01

120 lb. Heavy Duty (Available in colors 0, 9, and 30 **ONLY**)

NTE Type No.	Length	Width	Thickness	Max. Bundle Dia. (Note 3)	Mil Spec (Note 4)	Qty. per Bag	Diag No.
04-08120xx	8.70 / 220.98	.300 / 7.620	.076 / 1.930	2.060 / 52.38	N/A	100	WT-01
04-14120xxL	15.09 / 383.36	.300 / 7.620	.076 / 1.930	4.060 / 103.18	MS3367-3	50	WT-01
04-14120xx	15.09 / 383.36	.300 / 7.620	.076 / 1.930	4.060 / 103.18	MS3367-3	100	WT-01

175 lb. Extra Heavy Duty (Available in colors 0 and 9 **ONLY**)

NTE Type No.	Length	Width	Thickness	Max. Bundle Dia. (Note 3)	Mil Spec (Note 4)	Qty. per Bag	Diag No.
04-24175x	25.25 / 641.35	.340 / 8.636	.090 / 2.286	7.180 / 182.56	MS3367-8, 9 & 10	100	WT-01

Note 1. Replace "x" or "xx" in device number with corresponding color code from the "Color Code Chart".

Note 2. Dimensions are listed as "inch / millimeter".

Note 3. "Max. Bundle Dia." is defined as the maximum bundle diameter achieved after insertion for 3 "clicks" due to having a 3 tooth pawl.

Note 4. Mil Spec not available for fluorescent and heat stabilized types.

Note 5. Colored and Fluorescent types available in 100 per bag **ONLY**.