

SLE 88CFX4000P

SOLID FLASH™ 32-bit Security Controller
Optimized for multi-application cards with high level of security

400 kByte SOLID FLASH™
16 kByte RAM

Short Product Overview

May 2012

Edition 2012-05-08

Published by

Infineon Technologies AG

81726 Munich, Germany

© 2012 Infineon Technologies AG

All Rights Reserved.

Legal Disclaimer

The information given in this document shall in no event be regarded as a guarantee of conditions or characteristics. With respect to any examples or hints given herein, any typical values stated herein and/or any information regarding the application of the device, Infineon Technologies hereby disclaims any and all warranties and liabilities of any kind, including without limitation, warranties of non-infringement of intellectual property rights of any third party.

Information


For further information on technology, delivery terms and conditions and prices, please contact the nearest Infineon Technologies Office (www.infineon.com).

The term "Mifare" in this document is only used as an indicator of product compatibility to the corresponding established technology. This applies to the entire document wherever the term is used.

Warnings

Due to technical requirements, components may contain dangerous substances. For information on the types in question, please contact the nearest Infineon Technologies Office.

Infineon Technologies components may be used in life-support devices or systems only with the express written approval of Infineon Technologies, if a failure of such components can reasonably be expected to cause the failure of that life-support device or system or to affect the safety or effectiveness of that device or system. Life support devices or systems are intended to be implanted in the human body or to support and/or maintain and sustain and/or protect human life. If they fail, it is reasonable to assume that the health of the user or other persons may be endangered.

Product name	SLE 88CFX4000P  SOLID FLASH™
Product description	Security Controller
Interfaces	ISO 7816
User-ROM	–
NVM	400 kByte
EEPROM	–
RAM	16 kByte + 880 Byte crypto
CPU	32-bit
Symmetrical Cryptography	3DES
Asymmetrical Cryptography	RSA up to 2048-bit, ECC up to 521-bit
Ambient temperature	-25 to +85 °C
Delivery forms	Wafer, Bare Die, ChipCard Module, SMD (DSO-20, VQFN-10, SSOP-20)
Typical applications	SIM/UICC, Digital Signature, Embedded Security
Certifications	CC EAL5+ High

For further information on technology, delivery forms and conditions please contact your nearest Infineon Technologies sales representative (www.infineon.com).

Infineon Technologies – innovative semiconductor solutions for energy efficiency, mobility and security.

