




ELECTRICAL CHARACTERISTICS @ 25°C

ELECTRICAL SPECIFICATIONS:

1.0	TURNS RATIO (P6-P8-P3) : (J6-J3)	: 1CT : 1 ± 3%
	(P2-P7-P1) : (J2-J1)	: 1CT : 2 ± 3%
2.0	INDUCTANCE (P6-P3)=(J6-J3)	: 98uH MIN. @ 0.01V, 10KHz
	(P2-P1)	: 18uH MIN. @ 0.01V, 10KHz
3.0	LEAKAGE INDUCTANCE P6-P3 (WITH J6 AND J3 SHORT)	: 0.3uH MAX. @ 1MHz
	P2-P1 (WITH J2 AND J1 SHORT)	: 0.08uH MAX. @ 1MHz
4.0	INTERWINDING CAPACITANCE (P6,P3) TO (J6,J3)	: 8pF MAX @ 1MHz
	(P2,P1) TO (J2,J1)	: 6pF MAX. @ 1MHz
5.0	DC RESISTANCE (J6-J3)=(J2-J1)	: 0.7 ohms Max.
	(P6-P8)=(P8-P3)	: 0.3 ohms Max.
	(P2-P7)=(P7-P1)	: 0.3 ohms Max.
6.0	DIELECTRIC WITHSTAND (P6,P3) TO (J6,J3)	: 1500Vrms
	(P2,P1) TO (J2,J1)	: 1500Vrms



NOTES



- 1.0 PINS WITHOUT ELECTRICAL CONNECTION ARE OMITTED.
- 2.0 Ref. MG06

ORIGINATED BY	DATE	TITLE	PART NO. / DRAWING NO.	STANDARD DIM.	[] METRIC DIM. AS REFERENCE		 COMPONENTS FOR A CONNECTED PLANET
ZL WANG	10-27-09	 TAB DOWN, SHIELDED	SI-60148-F	TOL. IN INCH	UNIT : INCH [mm]	REV. : X1	
DRAWN BY	DATE		FILE NAME	.X	SCALE : N/A	SIZE : A4	
RS ZHANG	10-27-09		SI-60148-F.DWG	.XX		PAGE : 2	
				.XXX	±0.005		

RoHS
2002/95/EC

THE INFORMATION CONTAINED HEREIN IS CONSIDERED "PROPRIETARY" TO BEL FUSE INC. AND SHALL NOT BE COPIED, REPRODUCED OR DISCLOSED WITHOUT THE WRITTEN APPROVAL OF BEL FUSE INC.

RoHS
2002/95/EC



1. THE SUGGESTED PANEL OPENING IS INTENDED TO GIVE THE USER THE ABILITY TO HAVE REASONABLE JACK / PANEL CLEARANCES YET MAINTAIN RELIABLE GROUNDING CAPABILITY.
2. ALL TOLERANCES NOT OTHERWISE SPECIFIED TO BE ± 0.005 [0.13]

ORIGINATED BY	DATE	TITLE MagJack® 10BT TAB DOWN, SHIELDED	PART NO. / DRAWING NO.	STANDARD DIM.		[] METRIC DIM. AS REFERENCE		 COMPONENTS FOR A CONNECTED PLANET
ZL WANG	10-27-09		SI-60148-F	TOL. IN INCH		UNIT : INCH [mm]	REV. : X1	
DRAWN BY	DATE		FILE NAME	.X		SCALE : N/A	SIZE : A4	
RS ZHANG	10-27-09		SI-60148-F.DWG	.XX			PAGE : 4	
				.XXX	± 0.005			