

THE INFORMATION CONTAINED HEREIN IS CONSIDERED
"PROPRIETARY" TO BEL FUSE INC. AND SHALL NOT BE
COPIED, REPRODUCED OR DISCLOSED WITHOUT THE
WRITTEN APPROVAL OF BEL FUSE INC.

PRELIMINARY


RoHS
2002/95/EC



ELECTRICAL CHARACTERISTICS @ 25°C

URNS RATIO	1CT : 1CT ±2%
ACL @ 0.1V, 100KHz	350µH MIN.
8mA DC BIAS (0°C - 70°C)	
INSERTION LOSS	
100KHz TO 100MHz	-1.2 dB MAX.
RET. LOSS (MIN) @ 100ΩHMS ±15%	
2MHz-30MHz	-16 dB MIN.
60MHz-80MHz	-10 dB MIN.
LEAKAGE INDUCTANCE	
PRIMARY W/ SECONDARY SHORTED	0.25µH MAX. @ 1MHz
D.C. RESISTANCE	
(1-2)=(3-4)	1.40 ΩHMS MAX.
(RJ1-RJ2)=(RJ3-RJ6)	1.0 ΩHMS MAX.
INTERWINDING CAPACITANCE	
PER CHANNEL (PRI. to SEC.)	40 pF MAX.
XTALK	
100KHz TO 100MHz	-30 dB MIN.
HIPOT (Isolation Voltage):	2250 VDC
100% OF PRODUCTION TESTED TO COMPLY WITH IEEE 802.3 ISOLATION REQUIREMENTS	
BALANCED DC LINE CURRENT	350mA MAX. @ 57 VDC CONTINUOUS 500mA MAX. @ 57 VDC FOR 200 MILLSECONDS
OPERATING TEMPERATURE:	-40° TO +85°C

SCHEMATIC








ORIGINATED BY	DATE	TITLE Vertical SMT MagJack® (EXT. TEMP.)	PART NO. / DRAWING NO.	STANDARD DIM.		[] METRIC DIM. AS REFERENCE		
CHOW WANCHUNG	06-12-08		V895-1001-AW	TOL. IN INCH		UNIT : INCH [mm]	REV. : PB	
DRAWN BY	DATE		FILE NAME	.X		SCALE : N/A	SIZE : A4	
DENG PING	06-12-08		V895-1001-AW_PB.DWG	.XX			PAGE : 2	
			.XXX					

THE INFORMATION CONTAINED HEREIN IS CONSIDERED "PROPRIETARY" TO BEL FUSE INC. AND SHALL NOT BE COPIED, REPRODUCED OR DISCLOSED WITHOUT THE WRITTEN APPROVAL OF BEL FUSE INC.

MECHANICAL SPECIFICATION

PRELIMINARY

RoHS
2002/95/EC



NOTES:

- PLASTIC HOUSING: THERMOPLASTIC PA, FLAMMABILITY RATING UL 94V-0
- CONTACTS: 30 MICRO-INCH HARD GOLD PLATING
- OUTPUT PINS: TIN-COATED COPPER WIRE, 0.016INCH*0.016INCH, SQUARE, SMD PINS
- METAL SHIELD: NICKEL PLATED ON COPPER ALLOY
- 1 MARK PART WITH MFG LOGO, MFG NAME, PART NUMBER AND DATE CODE.
- 2 THE 4 PADS ARE NOT FOR GROUNDING, BUT TO STRENGTHEN THE RETENTION FORCE ONTO CUSTOMER PCB.
3. RoHS COMPLIANCE, PER EU DIRECTIVE 2002/95/EC.
4. JACK CAVITY CONFORMS TO FCC RULES AND REGULATIONS.


c US UL RECOGNIZED - FILE #E132408.

ORIGINATED BY	DATE	TITLE	PART NO. / DRAWING NO.	STANDARD DIM. TOL. IN INCH	[] METRIC DIM. AS REFERENCE	
ZX HUANG	06-12-08	Vertical SMT MagJack® (EXT. TEMP.)	V895-1001-AW		UNIT : INCH [mm]	REV. : PB
DRAWN BY	DATE		FILE NAME	.X	SCALE : N/A	SIZE : A4
LU XUEPING	06-12-08		V895-1001-AW_PB.DWG	.XX		PAGE : 3
				.XXX	±0.010	

bel
COMPONENTS FOR A
CONNECTED
PLANET



RECOMMENDED PCB FOOTPRINT
 COMPONENT SIDE VIEW
 (SHADED AREA ARE SOLDER PADS)



PACKING INFORMATION

PACKING TRAY : 0200-9999-I5(TOP)

0200-9999-I6(BOTTOM)

PACKING QUANTITY : 88 PCS FINISHED GOODS PER TRAY
 11 TRAY (968 PCS FINISHED GOODS)
 PER CARTON BOX

NOTE: CARDBOARDS ARE PLACED BETWEEN LAYERS
 OF PACKING TRAY INSIDE CARTON BOX
 (INCLUDE THE UPPERMOST AND LOWERMOST TRAY)

ORIGINATED BY	DATE	TITLE	PART NO. / DRAWING NO.	STANDARD DIM. TOL. IN INCH	[] METRIC DIM. AS REFERENCE	
ZX HUANG	06-12-08	Vertical SMT MagJack® (EXT. TEMP.)	V895-1001-AW	.X	UNIT : INCH [mm]	REV. : PB
DRAWN BY	DATE		FILE NAME	.XX	SCALE : N/A	SIZE : A4
LU XUEPING	06-12-08		V895-1001-AW_PB.DWG	.XXX ±0.010	⊕	PAGE : 4