

**Description**

The S4560P is dual operational amplifiers which achieve approximately twice the high output current of the S4560P, as well as featuring a higher slew rate of 4V/us, a gain band width of 10MHz, and an improved frequency characteristic.

**Features**

- Built-in output short-circuit protection circuit.
- Internal phase correction.
- No latch-up
- Wide same phase mode and differential voltage ranges
- High gain. low noise

**Applications**


- Active filters
- Audio amplifiers
- VCOs
- Other electronic circuits

**Ordering Information**

Type NO.	Marking	Package Code
S4560P	S4560P	DIP-8

**Outline Dimensions**

unit : mm



## Absolute maximum ratings

(Ta = 25 °C)

Characteristic	Symbol	Ratings	Unit
Supply voltage	V <sub>CC</sub>	±18	V
Differential input voltage	V <sub>ID</sub>	±30	V
Input voltage	V <sub>IC</sub>	-V <sub>CC</sub> ~ V <sub>CC</sub>	V
Power Dissipation	P <sub>D</sub>	800	mW
Operating temperature	T <sub>opr</sub>	-40 ~ +85	°C
Storage temperature	T <sub>stg</sub>	-55 ~ +125	°C

\* Refer to Pd characteristics diagram. The values for the S4560 are those when it is mounted on a glass epoxy PCB(50 mm×50 mm×1.6 mm).

## Electrical Characteristics

(Unless otherwise specified. V<sub>CC</sub> = +15V, V<sub>EE</sub> = -15V and Ta = 25 °C)

Characteristic	Symbol	Test Condition	Min.	Typ.	Max.	Unit
Input offset voltage	V <sub>IOS</sub>	R <sub>g</sub> ≤ 10 kΩ	-	0.5	6	mV
Input offset current	I <sub>IOS</sub>	-	-	5	200	nA
Input bias current	I <sub>IB</sub>	-	-	50	500	nA
Input common mode Voltage Range	V <sub>ICR</sub>	-	±12	±14	-	V
Maximum Output Voltage	V <sub>OM</sub>	R <sub>L</sub> ≥ 10 kΩ	±12	±14	-	V
		R <sub>L</sub> ≥ 2 kΩ	±10	±13	-	V
Large signal Voltage Gain	G <sub>V</sub>	V <sub>out</sub> = ±10V, R <sub>L</sub> ≥ 2 kΩ	86	100	-	dB
Common mode rejection ratio	CMRR	R <sub>g</sub> ≤ 10 kΩ	70	90	-	dB
Power supply rejection ratio	PSRR	R <sub>g</sub> ≤ 10 kΩ	-	30	150	uV/V
Slew Rate	SR	G <sub>V</sub> = 1, R <sub>L</sub> ≥ 2 kΩ	-	4.0	-	V/us
Input conversion noise voltage	V <sub>n</sub>	-	-	-	2.2	uV
Gain band width product	GBW	f = 10kHz	-	10	-	MHz

## Electrical Characteristic Curves

Fig. 1  $G_V - f$




Fig. 2  $V_{OP-P} - f$




Fig. 3  $I_{IB} - T_a$




Fig. 4  $V_{ICR} - V_{CC} / V_{EE}$




Fig. 5  $I_Q - V_{CC} / V_{EE}$





Fig. 6  $I_{IB} - V_{CC}$



**The AUK Corp. products are intended for the use as components in general electronic equipment (Office and communication equipment, measuring equipment, home appliance, etc.).**

**Please make sure that you consult with us before you use these AUK Corp. products in equipments which require high quality and / or reliability, and in equipments which could have major impact to the welfare of human life(atomic energy control, airplane, spaceship, transportation, combustion control, all types of safety device, etc.). AUK Corp. cannot accept liability to any damage which may occur in case these AUK Corp. products were used in the mentioned equipments without prior consultation with AUK Corp..**

**Specifications mentioned in this publication are subject to change without notice.**