

Description

The SN34063 is a monolithic control circuit containing the primary functions required for DC-to-DC converters. These devices consist of an internal temperature compensated reference, comparator, controlled duty cycle oscillator with an active current limit circuit, driver and high current output switch. This series was specifically designed to be incorporated in Step-Down and Step-Up and Voltage-Inverting applications with a minimum number of external components.

Features

- Operation from 3.0V to 40V input.
- Low Standby Current
- Current Limiting
- Output Switch Current to 1.5A
- Output Voltage Adjustable
- Frequency Operation to 100kHz
- Precision 2% Reference

▲ Marking Information

SN34063 (1)

YYWW (2)


(1)Device Code

(2)Year & Week Code


Ordering Information

Type NO.	Marking	Package Code
SN34063	S34063	SOP-8
SN34063P	S34063	DIP-8


Pin Connection




SOP-8



DIP-8



Block Diagram



Absolute Maximum Ratings

[Ta=25 °C]

Characteristic	Symbol	Rating	Unit
Power Supply Voltage	V _{CC}	40	V
Comparator Input Voltage Range	V _{IR}	-0.3~+40	V
Switch Collector Voltage	V _{C(Switch)}	40	V
Switch Emitter Voltage (V _{pin 1} = 40 V)	V _{E(Switch)}	40	V
Switch Collector to Emitter Voltage	V _{CE(Switch)}	40	V
Driver Collector Voltage	V _{C(Driver)}	40	V
Driver Collector Current (Note 1)	I _{C(Driver)}	100	mA
Switch Current	I _{SW}	1.5	A
Power Dissipation	P _D	500	mW
Operating Junction Temperature	T _J	+150	°C
Operating Ambient Temperature Range	T _A	-40~+85	°C
Storage Temperature Range	T _{stg}	-65~+150	°C

* Note 1 : Maximum package power dissipation limits must be observed.

Electrical Characteristics

($V_{CC} = 5.0\text{ V}$, $T_A = -40^\circ\text{C}$ to $+85^\circ\text{C}$, unless otherwise specified.)

Characteristic	Symbol	Min	Typ	Max	Unit
----------------	--------	-----	-----	-----	------

OSCILLATOR

Frequency ($V_{Pin5} = 0\text{ V}$, $C_T = 1.0\text{ nF}$, $T_A = 25^\circ\text{C}$)	f_{osc}	24	33	42	kHz
Charge Current ($V_{CC} = 5.0\text{ V}$ to 40 V , $T_A = 25^\circ\text{C}$)	I_{chg}	24	33	42	uA
Discharge Current ($V_{CC} = 5.0\text{ V}$ to 40 V , $T_A = 25^\circ\text{C}$)	I_{dischg}	140	200	260	uA
Discharge to Charge Current Ratio (Pin 7 to V_{CC} , $T_A = 25^\circ\text{C}$)	I_{dischg}/I_{chg}	5.2	6.2	7.5	-
Current Limit Sense Voltage ($I_{chg} = I_{dischg}$, $T_A = 25^\circ\text{C}$)	$V_{Ipk(sense)}$	250	300	350	mV

OUTPUT SWITCH (Note 2)

Saturation Voltage, Darlington Connection ($I_{SW} = 1.0\text{ A}$, Pins 1, 8 connected)	$V_{CE(sat)}$	-	1.0	1.3	V
Saturation Voltage (Note 3) ($I_{SW} = 1.0\text{ A}$, $R_{Pin8} = 82\Omega$ to V_{CC} , Forced $\beta = 20$)	$V_{CE(sat)}$	-	0.45	0.7	V
DC Current Gain ($I_{SW} = 1.0\text{ A}$, $V_{CE} = 5.0\text{ V}$, $T_A = 25^\circ\text{C}$)	h_{FE}	50	120	-	-
Collector Off – State Current ($V_{CE} = 40\text{ V}$)	$I_{C(off)}$	-	0.01	100	uA

COMPARATOR

Threshold Voltage $T_A = 25^\circ\text{C}$ $T_A = -40^\circ\text{C}$ to $+85^\circ\text{C}$	V_{th}	1.225 1.210	1.25 1.25	1.275 1.290	V
Threshold Voltage Line Regulation ($V_{CC} = 3.0\text{ V}$ to 40 V)	Regline	-	1.4	5.0	mV
Input Bias Current ($V_{IN} = 0\text{ V}$)	I_{IB}	-	-40	-400	nA

TOTAL DEVICE

Supply Current ($V_{CC} = 5.0\text{ V}$ to 40 V , $C_T = 1.0\text{ nF}$, Pin 7 = V_{CC} , $V_{Pin5} > V_{th}$, Pin 2 = GND, remaining pins open)	I_{CC}	-	2.5	4.0	mA
---	----------	---	-----	-----	----

Note 2 : Maximum package power dissipation limits must be observed.

Note 3 : If the output switch is driven into hard saturation (Non–Darlington configuration) at low switch currents ($\leq 300\text{ mA}$) and high driver currents ($\geq 30\text{ mA}$), it may take up to $2.0\mu\text{s}$ for it to come out of saturation. This condition will shorten the off time at frequencies $\geq 30\text{ kHz}$, and is magnified at high temperatures. This condition does not occur with a Darlington configuration, since the output switch cannot saturate. If a Non–Darlington configuration is used, the following output drive condition is recommended:

$$\text{Forced } \beta \text{ of output switch : } \frac{\text{IC output}}{\text{IC driver} - 7.0\text{mA}} \geq 10$$

* The 100Ω resistor in the emitter of the driver device requires about 7.0 mA before the output switch conducts.

Electrical Characteristic Curves

Fig.1 C_T vs. $t_{On}-t_{Off}$




Fig.2 Timing Capacitor Waveform




Fig.3 I_E vs. $V_{CE(sat)}$




Fig.4 I_C vs. $V_{CE(sat)}$




Fig.5 T_A vs. $V_{IPK(sense)}$





Fig.6 V_{CC} vs. I_{CC}



Typical Application Circuit

Step Up Converter




Fig.7 Step Up Converter

Test Condition

Test	Condition	Value (Typ)	Unit
Line Regulation	$V_{IN}=8.0V$ to $16V$, $I_O=175mA$	30	mV
Load Regulation	$V_{IN}=12V$, $I_O=75mA \sim 175mA$	10	mV
Output Ripple	$V_{IN}=12V$, $I_O=175mA$	300	mV
Efficiency	$V_{IN}=12V$, $I_O=175mA$	89	%




Fig.8 External Current Boost Connections for IC Peak Greater than

8-a. External NPN

8-b. External NPN Saturated

Typical Application Circuit

Step Down Converter




Fig.9 Step Down Converter

Test Condition

Test	Condition	Value (Typ)	Unit
Line Regulation	$V_{IN}=15V$ to $25V$, $I_O=500mA$	5	mV
Load Regulation	$V_{IN}=25V$, $I_O=50mA \sim 500mA$	30	mV
Output Ripple	$V_{IN}=25V$, $I_O=500mA$	100	mV
Efficiency	$V_{IN}=25V$, $I_O=500mA$	80	%
Short Circuit Current	$V_{IN}=25V$, $R_{LOAD}=0.1\Omega$	1.2	A




Fig.10 External Current Boost Connections for IC Peak Greater than

10-a. External NPN

10-b. External NPN Saturated

Typical Application Circuit

Voltage Inverting Converter




Fig.11 Voltage Inverting Converter

Test Condition

Test	Condition	Value (Typ)	Unit
Line Regulation	$V_{IN}=4.5V$ to $6.0V$, $I_O=100mA$	15	mV
Load Regulation	$V_{IN}=5.0V$, $I_O=10mA \sim 100mA$	20	mV
Output Ripple	$V_{IN}=5.0V$, $I_O=100mA$	280	mV
Efficiency	$V_{IN}=5.0V$, $I_O=100mA$	58	%
Short Circuit Current	$V_{IN}=5.0V$, $R_{LOAD}=0.1\Omega$	0.9	A




Fig.12 External Current Boost Connections for IC Peak Greater than

12-a. External NPN

12-b. External NPN Saturated

Calculation

Calculation	Step-Up	Step-Down	Voltage-Inverting
t_{ON}/t_{OFF}	$\frac{V_{OUT} + V_F - V_{IN(min)}}{V_{IN(min)} - V_{sat}}$	$\frac{V_{OUT} + V_F}{V_{IN(min)} - V_{sat} - V_{OUT}}$	$\frac{ V_{OUT} + V_F}{V_{IN} - V_{sat}}$
$(t_{ON} + t_{OFF})$	$1/f$	$1/f$	$1/f$
t_{OFF}	$\frac{t_{ON} + t_{OFF}}{\frac{t_{ON}}{t_{OFF}} + 1}$	$\frac{t_{ON} + t_{OFF}}{\frac{t_{ON}}{t_{OFF}} + 1}$	$\frac{t_{ON} + t_{OFF}}{\frac{t_{ON}}{t_{OFF}} + 1}$
t_{ON}	$(t_{ON} + t_{OFF}) - t_{OFF}$	$(t_{ON} + t_{OFF}) - t_{OFF}$	$(t_{ON} + t_{OFF}) - t_{OFF}$
C_T	$4.0 \times 10^{-5} t_{ON}$	$4.0 \times 10^{-5} t_{ON}$	$4.0 \times 10^{-5} t_{ON}$
$I_{PK(switch)}$	$2I_{OUT(max)} \left(\frac{t_{ON}}{t_{OFF}} + 1 \right)$	$2I_{OUT(max)}$	$2I_{OUT(max)} \left(\frac{t_{ON}}{t_{OFF}} + 1 \right)$
R_{SC}	$0.3/I_{PK(switch)}$	$0.3/I_{PK(switch)}$	$0.3/I_{PK(switch)}$
$L_{(min)}$	$\left(\frac{V_{IN(min)} - V_{sat}}{I_{PK(switch)}} \right) \times t_{ON(max)}$	$\left(\frac{V_{IN(min)} - V_{sat} - V_{OUT}}{I_{PK(switch)}} \right) \times t_{ON(max)}$	$\left(\frac{V_{IN(min)} - V_{sat}}{I_{PK(switch)}} \right) \times t_{ON(max)}$
C_O	$9 \frac{I_{OUT} t_{ON}}{V_{ripple(pp)}}$	$\frac{I_{PK(switch)} (t_{ON} + t_{OFF})}{8V_{ripple(pp)}}$	$9 \frac{I_{OUT} t_{ON}}{V_{ripple(pp)}}$

Note

V_{sat} = Saturation voltage of the output switch.

V_F = Forward voltage drop of the output rectifier.

The following power supply characteristics must be chosen:

V_{IN} – Nominal input voltage.


V_{OUT} – Desired output voltage, $|V_{OUT}| = 1.25 \times (1 + R_2/R_1)$

I_{OUT} – Desired output current.

f_{min} – Minimum desired output switching frequency at the selected values of V_{in} and I_O .


$V_{ripple(pp)}$ – Desired peak-to-peak output ripple voltage. In practice, the calculated capacitor value will need to be increased due to its equivalent series resistance and board layout. The ripple voltage should be kept to a low value since it will directly affect the line and load regulation.

Outline Dimension (Unit : mm) [SOP-8]




SYMBOL	MILLIMETER(mm)			NOTE
	MINIMUM	NOMINAL	MAXIMUM	
A	1.245	—	1.445	
A1	0.125	0.175	0.275	
b	0.320	0.420	0.520	
c	0.170	0.220	0.270	
D	4.802	4.902	5.002	
E	5.870	6.020	6.170	
E1	3.761	3.861	3.961	
e	1.270 BSC			
L	0.462	0.562	0.662	
θ	0 °	—	8 °	

※ Recommend PCB solder land (Unit : mm)



Outline Dimension (Unit : mm) [DIP-8]



SYMBOL	MILLIMETERS			NOTE
	MINIMUM	NOMINAL	MAXIMUM	
A	3.20	3.40	3.60	
b	0.36	0.46	0.56	
b1	1.42	1.52	1.62	
c	0.20	0.25	0.35	
D	9.00	9.20	9.40	
E	7.37	7.62	7.87	
E1	6.20	6.40	6.60	
e	2.54 TYP			
e1	0.79 TYP			
L1	0.33	—	—	
L2	3.00	3.30	3.60	
θ	0°	—	15°	

The AUK Corp. products are intended for the use as components in general electronic equipment (Office and communication equipment, measuring equipment, home appliance, etc.).

Please make sure that you consult with us before you use these AUK Corp. products in equipments which require high quality and / or reliability, and in equipments which could have major impact to the welfare of human life(atomic energy control, airplane, spaceship, transportation, combustion control, all types of safety device, etc.). AUK Corp. cannot accept liability to any damage which may occur in case these AUK Corp. products were used in the mentioned equipments without prior consultation with AUK Corp..

Specifications mentioned in this publication are subject to change without notice.