

Power Supplies

- Mini Redundant Power

PS300-HRP

Model Name	P/N: 50914709620E						
PS300-HRP Redundant Power ATX 300W	Input Range	90 ~ 264Vac Full Range					
	Output Voltage	+5V	+3.3V	+12V	-12V	-5V	+5Vsb
		25A (3A min)	18A (1A min)	16A (2A min)	0.5A	0.5A	2A (0.1A min)
	MTBF (hours)	100,000h					
	Safety	UL, UL+C, TUV, CB, CE					
	Dimensions	185 x 150 x 86 mm					
Compatible with Axiomtek Products		AX61220/AX6156LE					



Overview

Embedded
Systems

Embedded
Systems for
Transportation

Embedded
Field
Controllers

Embedded
MicroBoxes

Industrial
Barebone
Systems

Industrial
Chassis

Backplanes

Power
Supplies

Peripherals &
Accessories

PS400-HRP

Model Name	P/N: 50914B09620E						
PS400-HRP Redundant Power ATX 400W	Input Range	90 ~ 264Vac Full Range					
	Output Voltage	+5V	+3.3V	+12V	-12V	-5V	+5Vsb
		35A (3A min)	25A (1A min)	28A (2A min)	1.2A	0.5A	2A (0.1A min)
	MTBF (hours)	100,000h					
	Safety	UL, UL+C, TUV, CB, CE					
	Dimensions	185 x 150 x 86 mm					
Compatible with Axiomtek Products		AX6156LE/AX61220					



PS501-HRP (AC inlet in front)

Model Name	P/N: 50904C09010E					
PS501-HRP Redundant Power ATX500W	Input Range	100 ~ 240Vac Full Range				
	Output Voltage	+5V	+3.3V	+12V	-12V	+5Vsb
		25A	25A	41A	0.8A	3.5A
	MTBF (hours)	AT 25°C 100,000h				
	Safety	CB, CCC, UL, TUV, CE, FCC				
	Dimensions	185 x 150 x 86 mm				
Compatible with Axiomtek Products		AX6156LE/AX61220				



Power Supplies

- Mini Redundant Power

PS500-HRP

Model Name	P/N: 50904C09000E					
PS500-HRP Redundant Power ATX 500W	Input Range	100 ~ 240Vac Full Range				
	Output Voltage	+5V	+3.3V	+12V	-12V	+5Vsb
		25A (1A min)	25A (1A min)	41A (1A min)	0.8A	3.5A (0.1A min)
	MTBF (hours)	AT 25°C 100,000h				
	Safety	UL, TUV, CB, CCC, RFI/EMI Standards, FCC Class B, CISPR22 Class B				
	Dimensions	185 x 150 x 86 mm				
	Compatible with Axiomtek Products	AX61492				

