

OPS860-HM

Socket G2 2nd Gen Intel® Core™ Open Pluggable Specification (OPS) Digital Signage Player with Intel® HM65 Chipset



1. 2.5" HDD Slot
2. USB 2.0 x 2
3. Ethernet
4. VGA
5. Power switch
6. Reset
7. Audio (Line-out)
8. Audio (Mic-in)
9. Power indicator
10. HDD indicator
11. JAE TX-25
12. WiFi antenna (optional)



Specifications

Main System	CPU	Supports socket G2 (rPGA 988B) 2nd Generation Intel® Core™ i5/ i3 processors (Sandy Bridge) (optional)
	Chipset	Intel® HM65 PCH
	System Memory	1 x DDR3 1333 SO-DIMM max. up to 4 GB
	Storage	1 x 2.5" SATA HDD tray
IO	Watchdog Timer	255 levels, 1 ~ 255 sec.
		2 x USB 2.0
		1 x 10/100/1000Mbps Ethernet
		1 x VGA
Indicator		1 x power on/off button
		1 x reset button
		1 x Audio (Line-out/ Mic-in)
		1 x DVI/HDMI (via OPS JAE interconnector)
Expansion Slot		1 x DisplayPort (via OPS JAE interconnector)
		3 x USB 2.0 (via OPS JAE interconnector)
		1 x Audio (Line-out, via OPS JAE interconnector)
		1 x UART (TX/RX via OPS JAE interconnector)
Indicator		1 x LED for system power ON
		1 x LED for HDD active
WiFi		Supports 802.11 a/b/g/n (optional)
Expansion Slot		1 x PCI Express Mini Card
Dimensions		200 mm (7.87") (W) x 119 mm (4.68") (D) x 30 mm (1.18") (H)
		Packing Dimensions 270 mm (10.63") (W) x 197 mm (7.76") (D) x 70 mm (2.76") (H)
Weight (net/gross)		1 kg (2.2 lb)/1.5 kg (3.3 lb)
Environmental		0° ~ +54°C (32°F ~ 130°F) (With airflow 0.7m/s)

Packing

- 1 x driver CD
- 1 x HDD mylar x 1
- 1 x thermal grease (syringe 1G)
- 2 x M3 x 4 screw
- 2 x M4 x 6 screw

* All specifications and photos are subject to change without notice.
© 2013 Axiomtek Co., Ltd. All rights reserved.

Features

- Open Pluggable Specification (OPS) compliance
- Supports socket G2 (rPGA 988B) 2nd Generation Intel® Core™ i5/ i3 processors (Sandy Bridge) (optional)
- DDR3 1333 SO-DIMM max. up to 4 GB
- PCIe Mini Card
- Easy maintenance: pluggable HDD and easy-to-change DRAM
- VGA connector



▲ Rear view

Optional EOS Installation

Windows® 7 Embedded

Optional OS Installation

Windows® XP, Windows® 7

Ordering Information

Standard

OPS860-HM (P/N: E22M860101)	Intel® OPS digital signage player supports socket G2 processor (Sandy Bridge)
--------------------------------	--

Optional

OPF320	31.5" full HD digital signage display
OPF321	31.5" LED backlight full HD digital signage display
AX93157	OPS docking board

* Specification and certifications are based on options and may vary.

Dimensions

