
P1158-831

15" TFT Intel[®] Core™2 Duo Slim Industrial Panel Computer





- 1. IEEE 1394a 2. COM 2/3 (RS-232) 3. Power switch 4. PS/2 KB+MS x 2 5. VGA
- 6. Ethernet x 2 7. USB 2.0 x 4 8. Audio (Mic-in/Line-out) 9. COM 1 (RS-232/422/485)



Introduction

The P1158-831 is a 15[°] multi-media panel PC for Kiosk application. It has a fashionable mechanism design and industrial-grade material front bezel which can avoid damage from chemical corrosion. To meet the demand of multi-media application, the P1158-831 supports Intel[®] Core[™]2 Duo processor and operating system of Windows Vista, and is equipped with built-in speakers, two Gigabit LAN, IEEE 1394a and WLAN module for wireless network connection. This slim industrial panel PC is most suitable for kiosk, factory automation and more.

Powerful computing: Intel[®] Core[™]2 Duo processor

The P1158-831 features Intel[®] Core™2 Duo and Intel[®] 945GME chipset which deliver high computing capability. The Mobile CPU offers reliable and stable performance for rugged environment.

Industrial-grade material front bezel

The P1158-831 adopts industrial-grade material front bezel which incorporates the advantages of light weight, high degree of hardness, better heat releasing, easy-to-shape and anti-corrosion ability. Therefore, the PANEL1158-831 is especially suitable for most rugged industrial environments.

Speaker & WLAN antenna supported

P1158-831 features built-in speakers for kiosk application to display multimedia program. It also supports WLAN module (optional) & antenna for wireless network connectivity.

Features

- 15" XGA TFT LCD display
- Intel[®] Core[™]2 Duo processor
- Industrial-grade material front bezel: anti-corrosion
- Slim design: thickness 86.4 mm
- Built-in speakers & optional WLAN module
- Windows[®] Vista and 7 supported
- Supports panel mount, wall mount, rack mount, VESA arm, desktop stand
- Supports dimming control



▲ Side view

Specifications

Front Bezel	Industrial-grade material w/ IP65/NEMA 4 rugged protection		
LCD Panel	Display Type	15" XGA TFT	
	Brightness (cd/m ²)	250 nits	
	Resolution	1024 x 768 pixels	
	Viewing Angle (H/V)	140°/120°	
Main system	CPU	Socket M for Intel [®] Core™2 Duo/ Core™ Duo/ Core™ Solo processor with FSB 533/667 MHz	
	Chipset	Intel® 945GME + ICH7M/-DH	
	System Memory	2 x 240-pin DDR2 DIMM max. up to 4 GB	
	BIOS	Phoenix-Award 4Mbit with RPL/PXE LAN Boot ROM, SmartView and customer CMOS backup	
	Storage	1 x 3.5" or 2 x 2.5" IDE/SATA HDD	
	Watchdog Timer	255 levels, 1~255 sec.	

Specifications

I/O Connector	2 x RS-232 (COM 2/3)	
	1 x RS-232/422/485 (COM 1)	
	2 x IEEE 1394a	
	4 x USB 2.0	
	2 x PS/2 keyboard/mouse	
	2 x 10/100/1000Mbps Ethernet	
	1 x VGA	
	1 x Audio (Mic-in/Line-out)	
Touchscreen	Resistive type	
	Light Transmission 79%	
	1 million activations (typical) at a single point	
Power supply	100 ~ 240VAC, 180W	
Dimensions	420 mm (16.54) (W) x 86.4 mm (3.40) (D) x 335 mm (13.2) (H)	
Packing Dimensions	610 mm (24.02") (W) x 260 mm (10.24") (D)	
-	x 590 mm (23.23") (H)	
Weight (net/gross)	5.5 kg (12.1 lb)/9.3 kg (20.5 lb)	
Environment	Operating temperature: 0° ~ +45°C (32°F ~ 113°F)	
	Storage Temperature: -20°C ~ +65°C (-4°F ~ +149°F)	
	Relative humidity:: 10 ~ 95% @ 40°C, non-condensing	
	Operation vibration: 1.0G, 5~500Hz, random	
Certification	CE	

Ordering Information

panel PC	P1158-831 15" XGA TFT socket M Intel [®] Core™2 Duo slim industrial
----------	--

* Specification and certifications are based on options and may vary.

-								
0		0	r	ς.			ŝ.	Å.
0	v		L	V	1	C	1	()

Industrial Panel

Optional Accessories

E202003330	VM-101 (VESA ARM clamp type)	Computers & Monitors
E202003329	VM-105 (VESA ARM wall-mount)	
82211580080E	2 x 2.5 HDD kit	Heavy-duty Fanless Touch Panel
82211580090E	VESA/Wall mount kit	Computers
82211530110E	Wireless LAN kit	
82261580070E	Rack mount kit	Digital Signage

Optional EOS Installation

Optional EOS Installation	Healthcare & Medical Solutions
Windows [®] XP Embedded	Solutions
Windows [®] CE.NET	Open Frame
	Panel Computers
Optional OS Installation	Accessories

Windows® 2000/XP/Vista/7

Dimensions

