


EX78000 Series

Managed Hardened 10-port 10/100BASE (8 x PoE) and 2-port Gigabit Ethernet Switch



Value

- › Provides flexibility of 10-port 10/100BASE-TX/FX/BX/SFP plus 2-port Gigabit-TX/SX/LX/SFP
- › Port 1 to 8 supports PoE function
- › IEEE802.3af/ IEEE802.3at Power over Ethernet(PoE) support for 8 or 4 10/100BASE-TX ports
- › Wide temp range for extreme environments



15.4 W/ea
or 30 W/ea

SFP
Option

Fanless

Features

- › Supports PoE Power Sourcing Equipment (PSE)
- › PoE control and Scheduling
- › Supports α-ring and RSTP/MSTP/STP for Ethernet redundancy
- › IP Multicast Filtering through IGMP Snooping V1, V2 & V3
- › Supports port-based VLAN and IEEE802.1Q VLAN Tagging and GVRP
- › IEEE802.1p QoS with four priority queues
- › MAC-based trunking and LACP
- › IEEE802.1x Security
- › Bandwidth Rate Control
- › Per-port programmable MAC address locking
- › Up to 24 Static Secure MAC addresses per port
- › Port mirroring
- › Supports NTP
- › DHCP Client/Server
- › 1000Mbps-Full-duplex, 10/100Mbps-Full/Half-duplex, Auto-Negotiation, Auto-MDI/MDIX
- › RS-232 console, Telnet, SNMP V1, V2c & V3, RMON, Web Browser, and TFTP Management
- › Full wire-speed forwarding rate
- › -40°C to 75°C (-40°F to 167°F) operating temperature range, tested for functional operation @ -40°C to 85°C (-40°F to 185°F)

Ordering Information

EX78400-00Z-P	4-port 10/100BASE-TX PoE Hardened Managed Ethernet Switch
EX78401-0YZ-P	4-port 10/100BASE-TX PoE + 1-port Gigabit Hardened Managed Ethernet Switch
EX78402-0YZ-P	4-port 10/100BASE-TX PoE + 2-port Gigabit Hardened Managed Ethernet Switch
EX78440-X0Z-P	4-port 10/100BASE-TX PoE + 4-port 100BASE-FX Hardened Managed Ethernet Switch
EX78441-XYZ-P	4-port 10/100BASE-TX PoE + 4-port 100BASE-FX + 1-port Gigabit Hardened Managed Ethernet Switch
EX78442-XYZ-P	4-port 10/100BASE-TX PoE + 4-port 100BASE-FX + 2-port Gigabit Hardened Managed Ethernet Switch
EX78800-00Z-P	8-port 10/100BASE-TX PoE Hardened Managed Ethernet Switch
EX78801-0YZ-P	8-port 10/100BASE-TX PoE + 1-port Gigabit Hardened Managed Ethernet Switch
EX78802-0YZ-P	8-port 10/100BASE-TX PoE + 2-port Gigabit Hardened Managed Ethernet Switch
EX78820-X0Z-P	8-port 10/100BASE-TX PoE + 2-port 100BASE-FX Hardened Managed Ethernet Switch
EX78821-XYZ-P	8-port 10/100BASE-TX PoE + 2-port 100BASE-FX + 1-port Gigabit Hardened Managed Ethernet Switch
EX78822-XYZ-P	8-port 10/100BASE-TX PoE + 2-port 100BASE-FX + 2-port Gigabit Hardened Managed Ethernet Switch

100FX Fiber Options :

(X) = 1 : Multi Mode (SC) - 2Km
 2 : Multi Mode (ST) - 2Km
 6 : Multi Mode (SC) WDM-TX:1310nm/RX:1550nm - 2Km
 7 : Multi Mode (SC) WDM-TX:1550nm/RX:1310nm - 2Km
 8 : Multi Mode (SC) WDM-TX:1310nm/RX:1550nm - 5Km
 9 : Multi Mode (SC) WDM-TX:1550nm/RX:1310nm - 5Km
 A : Single Mode (SC) - 20Km
 *More 100FX Fiber options also available upon request.

B : Single Mode (SC) - 40Km
 F : Single Mode (FC) - 20Km
 H : Single Mode (ST) - 20Km
 P : Single Mode (SC) WDM-TX:1310nm/RX:1550nm - 20Km
 Q : Single Mode (SC) WDM-TX:1550nm/RX:1310nm - 20Km
 R : Single Mode (SC) WDM-TX:1310nm/RX:1550nm - 40Km
 S : Single Mode (SC) WDM-TX:1550nm/RX:1310nm - 40Km
 V : Support 2-port 100BASE SFP

Gigabit Port Options :

(Y) = 1 : 10/100/1000BASE-TX
 3 : 1000BASE-SX (SC) - 550m
 4 : 1000 BASE-SX(SC) - 2Km
 5 : 1000 BASE-SX(ST) - 550m
 *More Gigabit options also available upon request.

A : 1000BASE-LX (SC) - 10Km
 B : 1000BASE-LX (SC) - 20Km
 R : 1000BASE-BX (SC) WDM-TX:1310nm/RX:1550nm - 20Km
 S : 1000BASE-BX (SC) WDM-TX:1550nm/RX:1310nm - 20Km
 V : Support 2-port 1000BASE SFP

Power Input Interface :

(Z) = B : DC Jack & Terminal Block

PoE Type: (P) = n/a : IEEE802.3af

T : IEEE802.3at

T6 : 6 ports IEEE802.3at

Power Supply : (Optional)

*Option A - Terminal Block power supply(s), part numbers:

15.4W 802.3af: DD-85-48, DR-75-48, DR-120-48, SDR-240-4838

30W 802.3at high power: DD-85-55, DR-75-48, DR-120-48, SDR-240-48

**Option B - DC Jack power supplies kit(s), part numbers: AS-120P-48

Installation Type : DIN Rail (mounting kit is included), Optional Panel Mount kits (KP-AA96-480) are available for ordering.

Specifications

Technology	
Standards	IEEE802.3 10BASE-T, IEEE802.3u 100BASE-TX/100BASE-FX, IEEE802.3ab 1000BASE-T, IEEE802.3z 1000BASE-SX/1000BASE-LX, IEEE802.3x, IEEE802.1p, IEEE802.1Q, IEEE802.1w, IEEE802.1x, IEEE802.3af
Forward and Filtering Rate	14,880pps for 10Mbps 148,810pps for 100Mbps 1,488,100pps for 1000Mbps
Packet Buffer Memory	2M bits
Processing Type	- Store-and-Forward - Half-duplex back-pressure and IEEE802.3x full-duplex flow control
Address Table Size	8192 MAC addresses

Power	
Power Input	- Redundant power inputs: - Terminal Block: 47 - 57VDC - DC Jack: 47 - 57VDC
Power Consumption	- Device: Max. 15W (without PoE) - PoE power budget (depends on power input): 181.6W Max.
PoE Power Output	- Port 1 to 8 - IEEE802.3af: up to 15.4W/port, 47 - 57VDC. - IEEE802.3at: up to 30W/port, 50 - 57VDC
- Supports overload current protection - Supports reverse polarity protection	

Mechanical	
Casing	- Metal case - IP30
Dimensions	71.4mm (W) x 140mm (D) x 170mm (H) (2.85" (W) x 5.6" (D) x 6.8" (H))
Weight	1.7Kg (3.74lbs.)
Installation	Din-Rail (Top hat type35mm), Wall Mount

Interface	
Ethernet Port	10/100BASE-TX (PoE): 8 or 4 ports 100BASE-FX: 0, 2 or 4 ports - Gigabit: 0, 1 or 2 ports
Console Port	Port: One DB9 RS-232 port
LED Indicators	- Per Unit: Power Status (Power 1, Power 2, Power 3) - Per Port: PoE (Amber) for 10/100TX, 10/100TX, 100FX: Link/Activity (Green), Gigabit: Link/Activity (Green)

Environment	
Operating Temperature	-40°C to 75°C (-40°F to 167°F) - Tested @ -40°C to 85°C (-40°F to 185°F)
Storage Temperature	-40°C to 85°C (-40°F to 185°F)
Ambient Relative Humidity	5% to 95% (non-condensing)

Regulatory Approvals	
ISO	Manufactured in an ISO9001 facility
Safety	UL508
EMI	- FCC Part 15, Class A - EN61000-6-4 - EN55022 - EN61000-3-2 - EN61000-3-3
EMS	- EN61000-6-2 - EN61000-4-2 (ESD Standards) - Contact: + / - 6KV - Air: + / - 8KV - EN61000-4-3 (Radiated RFI Standards) 10V/m, 80 to 1000MHz; 80% AM - EN61000-4-4 (Burst Standards) - Signal Ports: + / - 4KV - D.C. Power Ports: + / - 4KV - EN61000-4-5 (Surge Standards) - Signal Ports: + / - 1KV; Line-to-Line - D.C. Power Ports: + / - 0.5KV; Line-to-Earth - EN61000-4-6 (Induced RFI Standards) - Signal Ports: 10Vrms @ 0.15 - 80MHz; 80% AM - D.C. Power Ports: 10Vrms @ 0.15 - 80MHz; 80% AM - EN61000-4-8 (Magnetic Field Standards) 30A/m @ 50, 60Hz
Environmental Test Compliance	- IEC60068-2-6 Fc (Vibration Resistance) 5g @ 10 - 150Hz, Amplitude 0.35mm (Operation/Storage/Transport) - IEC60068-2-27 Ea (Shock) 25g @ 11ms (Half-Sine Shock Pulse; Operation) 50g @ 11ms (Half-Sine Shock Pulse; Storage/Transport) - FED STD 101C Method 5007.1 (Free fall w/ package) -Tested with Cross Weight and Drop High standard table

Diagrams

Unit: mm

