


ED3341 Series

Hardened 10/100BASE-TX Ethernet Extender over Coaxial Cable



Value

- › Complies with EN50155 standard requirement for Rolling Stock Ethernet applications
- › Complies with EN50121-4 standard requirement for Railway stationary Ethernet applications
- › Alternative long-distance Ethernet solution to reduce infrastructure cost and shorten the project schedule by using existing coaxial cable

Features

- › Complies with NEMA TS1 & TS2 Environmental requirements for Traffic control equipment
- › Specific design for industrial communication application with UL508 safety certification
- › Complies with IEC61000-6-2 EMC Generic standard immunity for Industrial environment
- › Ethernet Port: 10/100Mbps-Full-duplex, Auto-Negotiation, Auto-MDI/MDIX
- › Ethernet Extender Port: Symmetrical on the VDSL, High-speed full-duplex up to 170 Mbps communications link over existing coaxial cable
- › IEEE802.3x Flow control for full duplex
- › Ten speeds with speed indicator LEDs on front panel of unit,
 - Up to 85Mbps @ about 200meters (656ft.)
 - 1Mbps @ about 2,600meters (8,530ft.)
- › -40°C to 70°C (-40°F to 158°F) operating temperature range
- › Redundant power inputs with Terminal Block and DC Jack
- › DIP switch to select Local or Remote side
- › Hardened aluminum case
- › Compatible with ED3331, ED3344 and ED3371
- › Supports DIN-Rail, Panel and Rack Mounting installation

Ordering Information

ED3341-00B	Hardened 10/100BASE-TX Ethernet Extender over Coaxial Cable
------------	---

Power Supply : (Optional)

*Option A - The Terminal Block type external power supplies are not included. Please order the following part numbers:

DR-30-24, DR-60-24, DR-75-24, DR-120-24 or 41-136046-X (X)=1: US, 2: EU, 3: UK, 4: AU, 5: JP

**Option B - The external power adapters and power cords are not included. Please order the following part numbers:

41-136044-X (X)=1: US, 2: EU, 3: UK, 4: AU, 5: JP

Installation Type : Optional Panel mount kit, part number: KP-AA96-480



Specifications

Technology	
Standards	<ul style="list-style-type: none"> IEEE802.3 10BASE-T, IEEE802.3u 100BASE-TX, IEEE802.3x
Protocols	<ul style="list-style-type: none"> Transparent to higher layer protocols
Processing Type	<ul style="list-style-type: none"> IEEE802.3x Full-duplex flow control

Power	
Input	<ul style="list-style-type: none"> Input Voltage: 12 to 48VDC (Terminal Block); 12VDC (DC Jack)
Power Consumption	<ul style="list-style-type: none"> 7.2W Max. 0.6A @ 12VDC, 0.15A @ 48VDC
Overload Current Protection	<ul style="list-style-type: none"> Present
Reverse Polarity Protection	<ul style="list-style-type: none"> Present

Mechanical	
Casing	<ul style="list-style-type: none"> Aluminum case IP30
Dimensions	<ul style="list-style-type: none"> 50mm (W) x 110mm (D) x 135mm (H) (1.97" (W) x 4.33" (D) x 5.31" (H))
Weight	<ul style="list-style-type: none"> 0.8Kg (1.76lbs.)
Installation	<ul style="list-style-type: none"> DIN-Rail (Top hat type 35mm), Panel, Rack Mounting

Interface		
Ethernet Port	<ul style="list-style-type: none"> Port: One RJ-45 port, 10/100BASE-TX Full-duplex Auto-Negotiation, Auto-MDI/MDIX Speed: 10/100Mbps Distance: 100meters (328ft.) Cable: 10BASE-T: UTP CAT. 3, 4, 5 (2-pair wire) 100BASE-TX: UTP CAT. 5 (4-pair wire) 	
Ethernet Extender Port	<ul style="list-style-type: none"> Port: One 75Ω BNC Port (with F-type connector) Speed Display: 1/5/10/20/30/40/50/60/70/75Mbps Max. Distance: 2,600meters (8,530ft.) Cable: Coaxial Cable (5C2V / RG6AU) 	
Speed / Distance Reference	Speed	Distance
	1-5Mbps	2,600M(8,530ft.)
	6-10Mbps	2,400M(7,874ft.)
	11-16Mbps	2,000M(6,561ft.)
	17-20Mbps	1,800M(5,905ft.)
	21-29Mbps	1,600M(5,249ft.)
	30-43Mbps	1,400M(4,593ft.)
	44-54Mbps	1,200M(3,937ft.)
	55-63Mbps	1,000M(3,280ft.)
	64-74Mbps	600M(1,968ft.)
	75-85Mbps	200M(656ft.)

DIP switch	<ul style="list-style-type: none"> One DIP Switch: Local (CO) or Remote (CPE)
LED Indicators	<ul style="list-style-type: none"> Per Unit: Power Status (Power) Per Port: 10/100TX: Link/Activity, Full-duplex Line: Error, Link, Local, Remote <p>NOTE: All speed selections are Symmetrical on the DSL and.</p>

Environment	
Operating Temperature	<ul style="list-style-type: none"> -40°C to 70°C (-40°F to 158°F) Tested @ -40°C to 85°C (-40°F to 185°F)
Storage Temperature	<ul style="list-style-type: none"> -40°C to 85°C (-40°F to 185°F)
Ambient Relative Humidity	<ul style="list-style-type: none"> 5% to 95% (non-condensing)

Regulatory Approvals	
ISO	<ul style="list-style-type: none"> Manufactured in an ISO9001 facility
Safety	<ul style="list-style-type: none"> UL508
EMI	<ul style="list-style-type: none"> FCC Part 15, Class A EN61000-6-4 - EN55022 - EN61000-3-2 - EN61000-3-3
EMS	<ul style="list-style-type: none"> EN61000-6-2 - EN61000-4-2 (ESD Standards) Contact: +/- 4KV Air: +/- 8KV EN61000-4-3 (Radiated RFI Standards) 10V/m, 80 to 1000MHz; 80% AM EN61000-4-4 (Burst Standards) Signal Ports: +/- 4KV D.C. Power Ports: +/- 4KV EN61000-4-5 (Surge Standards) Signal Ports: +/- 2KV; Line-to-Line D.C. Power Ports: +/- 0.5KV; Line-to-earth EN61000-4-6 (Induced RFI Standards) Signal Ports: 10Vrms @ 0.15 - 80MHz; 80% AM D.C. Power Ports: 10Vrms @ 0.15 - 80MHz; 80% AM EN61000-4-8 (Magnetic Field Standards) 30A/m @ 50, 60Hz
Environmental Test Compliance	<ul style="list-style-type: none"> IEC60068-2-6 Fc (Vibration Resistance) 5g @ 10 - 150Hz, Amplitude 0.35mm (Operation/Storage/Transport) IEC60068-2-27 Ea (Shock) 25g @ 11ms (Half-Sine Shock Pulse; Operation) 50g @ 11ms (Half-Sine Shock Pulse; Storage/Transport) FED STD 101C Method 5007.1 (Free fall w/ package) -Tested with Cross Weight and Drop High standard table

Diagrams

Unit: mm

