


ED3141 Series

Hardened 10/100BASE-TX Ethernet Extender



Value

- › Specific design for industrial communication applications with UL508 safety certification
- › ISA 12.12.01 (UL1604) Certified for Class I, Division 2 Classified for use in hazardous locations
- › Alternative long-distance Ethernet solution to reduce infrastructure cost and shorten the project schedule by using existing copper wires

Features

- › Complies with NEMA TS1 & TS2 Environmental requirements for Traffic control equipment
- › Complies with IEC61000-6-2 EMC Generic standard immunity for Industrial environment
- › Operates transparent to higher layer protocols such as TCP/IP
- › Ethernet Port: 10/100Mbps-Full/Half-duplex, Auto-Negotiation, Auto-MDI/MDIX
- › Support DIP switch to select Local or Remote side
- › Ethernet Extender (RJ-11 and Terminal Block) Port: Symmetrical on the VDSL, High-speed Full-duplex up to 100Mbps communications link over existing copper telephone wire
- › Ten speeds with speed indicator LEDs on front panel of unit,
 - Up to 50Mbps @ about 300meters (984ft.),
 - 1Mbps @ about 1,900meters (6,232ft.)
- › Redundant power inputs with Terminal Block and DC Jack
- › -40°C to 75°C (-40°F to 167°F) operating temperature range
- › Hardened aluminum case
- › Supports DIN-Rail , Panel, and Rack Mounting installation

Ordering Information

ED3141-00B	Hardened 10/100BASE-TX Ethernet Extender
------------	--

Power Supply : (Optional)

*Option A - The Terminal Block type external power supplies are not included. Please order the following part numbers:

DR-30-24, DR-60-24, DR-75-24, DR-120-24 or 41-136046-X (X)=1: US, 2: EU, 3: UK, 4: AU, 5: JP

**Option B - The external power adapters and power cords are not included. Please order the following part numbers:

41-136044-X (X)=1: US, 2: EU, 3: UK, 4: AU, 5: JP

Installation Type : Optional Panel mount kit, part number: KP-AA96-480



Specifications

Technology	
Standards	<ul style="list-style-type: none"> IEEE802.3 10BASE-T, IEEE802.3u 100BASE-TX, IEEE802.3x
Protocols	<ul style="list-style-type: none"> Transparent to higher layer protocols
Processing Type	<ul style="list-style-type: none"> Half-duplex back-pressure and IEEE802.3x Full-duplex flow control

Power	
Input	<ul style="list-style-type: none"> Input Voltage: 12 to 30VDC (Terminal Block); 12VDC (DC Jack)
Power Consumption	<ul style="list-style-type: none"> 4.2W Max. 0.35A @ 12VDC, 0.175A @ 24VDC
Overload Current Protection	<ul style="list-style-type: none"> Present
Reverse Polarity Protection	<ul style="list-style-type: none"> Present

Mechanical	
Casing	<ul style="list-style-type: none"> Aluminum case IP30
Dimensions	<ul style="list-style-type: none"> 50mm (W) x 110mm (D) x 135mm (H) (1.97" (W) x 4.33" (D) x 5.31" (H))
Weight	<ul style="list-style-type: none"> 0.8Kg (1.76lbs.)
Installation	<ul style="list-style-type: none"> DIN-Rail (Top hat type 35mm), Panel, Rack Mounting

Interface	
Ethernet Port	<ul style="list-style-type: none"> Port: One RJ-45 port, 10/100BASE-TX Full/Half-duple Auto-Negotiation, Auto-MDI/MDIX PoE Port: complies with IEEE802.3af and IEEE802.3at standard Speed: 10/100Mbps Distance: 100meters (328ft.) Cable: 10BASE-T: UTP CAT. 3, 4, 5 (2-pair wire) 100BASE-TX: UTP CAT. 5 (4-pair wire)
Ethernet Extender Port	<ul style="list-style-type: none"> Port: One RJ-11 and Terminal Block port Speed: 1/3/5/10/15/20/25/30/40/50Mbps Distance: 1900meters (6,232ft.) Cable: Telephone wire 24 AWG (0.5mm diameter, 1-pair wire) or larger
DIP switch	<ul style="list-style-type: none"> One DIP Switch: Local (CO) or Remote (CPE)
LED Indicators	<ul style="list-style-type: none"> Per Unit: Power Status (Power) Per Port: 10/100TX: Link/Activity, Full-duplex Line: Error, Link, Local, Remote

LED Indicators	LED			Speed	Distance
	1	2	3		
1	Green	1Mbps	1,900m(6,232ft.)	3Mbps	1,800m(5,904ft.)
	Amber	3Mbps	1,600m(5,294ft.)		
2	Green	5Mbps	1,400m(4,593ft.)	10Mbps	1,200m(3,936ft.)
	Amber	10Mbps	1,000m(3,280ft.)		
3	Green	15Mbps	800m(2,624ft.)	20Mbps	700m(2,296ft.)
	Amber	25Mbps	600m(1,968ft.)		
4	Green	30Mbps	300m(984ft.)	40Mbps	300m(984ft.)
	Amber	50Mbps			
5	Green				
	Amber				

NOTE:
All speed selections are Symmetrical on the DSL.

Environment	
Operating Temperature	<ul style="list-style-type: none"> -40°C to 75°C (-40°F to 167°F) Tested @ -40°C to 85°C (-40°F to 185°F)
Storage Temperature	<ul style="list-style-type: none"> -40°C to 85°C (-40°F to 185°F)
Ambient Relative Humidity	<ul style="list-style-type: none"> 5% to 95% (non-condensing)

Regulatory Approvals	
ISO	<ul style="list-style-type: none"> Manufactured in an ISO9001 facility
Safety	<ul style="list-style-type: none"> UL508 ISA 12.12.01, Class I, Division 2 Classified for use in hazardous locations
EMI	<ul style="list-style-type: none"> FCC Part 15, Class A EN61000-6-3 <ul style="list-style-type: none"> EN55022 EN61000-3-2 EN61000-3-3
EMS	<ul style="list-style-type: none"> EN61000-6-2 <ul style="list-style-type: none"> EN61000-4-2 (ESD Standards) Contact: +/- 4KV Air: +/- 8KV EN61000-4-3 (Radiated RFI Standards) 10V/m, 80 to 1000MHz; 80% AM EN61000-4-4 (Burst Standards) Signal Ports: +/- 4KV D.C. Power Ports: +/- 4KV EN61000-4-5 (Surge Standards) Signal Ports: +/- 1KV; Line-to-Line D.C. Power Ports: +/- 0.5KV; Line-to-earth EN61000-4-6 (Induced RFI Standards) Signal Ports: 10Vrms @ 0.15 - 80MHz; 80% AM D.C. Power Ports: 10Vrms @ 0.15 - 80MHz; 80% AM EN61000-4-8 (Magnetic Field Standards) 30A/m @ 50, 60Hz
Environmental Test Compliance	<ul style="list-style-type: none"> IEC60068-2-6 Fc (Vibration Resistance) 5g @ 10 - 150Hz, Amplitude 0.35mm (Operation/Storage/Transport) IEC60068-2-27 Ea (Shock) 25g @ 11ms (Half-Sine Shock Pulse; Operation) 50g @ 11ms (Half-Sine Shock Pulse; Storage/Transport) FED STD 101C Method 5007.1 (Free fall w/ package) -Tested with Cross Weight and Drop High standard table

Diagrams

Unit: mm

