


# Reflective Line Reader Sensor

## Type OPB739RWZ



### Features:

- Focused for maximum sensitivity
- Phototransistor Output
- 650nm Visible Red LED to optimize detection of dye based inks
- Low-cost plastic housing
- 24" minimum 26AWG wire leads
- Optimal operating distance range 0.015" [.38mm] to 0.045" [1.14mm]



### Description:



The **OPB739RWZ** is a reflective line reader sensor. The sensor utilizes a visible red (650nm) LED and an NPN silicon phototransistor mounted side by side on converging optical axes in a black plastic housing. The converging light beam makes this sensor capable of detecting line widths as small as 0.004" [0.1mm] at the optimum distance of 0.030" [0.76mm] from the target. The red LED maximizes the reflected signal contrast of black lines on white backgrounds. Recommended line spacing is .050" minimum.

This sensor can be used with Optek's OCB100CZ auto calibration module to reduce variability from sensor to sensor and to achieve a digital output.


Custom electrical, wire, cabling and connectors are available. Contact your local representative or OPTEK for more information.

### Applications:


- Line Reading
- Low Resolution Bar Code Sensing
- Paper edge detection
- Mark detection
- Reflective Optical Encoders



### OPB739RWZ



RoHS



DIMENSIONS ARE  $\pm .005$  [.12] UNLESS OTHERWISE SPECIFIED.

OPTEK reserves the right to make changes at any time in order to improve design and to supply the best product possible.

# Reflective Line Reader Sensor

## Type OPB739RWZ



### Absolute Maximum Ratings ( $T_A=25^{\circ}\text{C}$ unless otherwise noted)

Storage and Operating Temperature Range	-40° C to +85° C
---	------------------

#### Input LED

Forward DC Current	40 mA
Reverse DC Voltage	2 V
Power Dissipation	100 mW

#### Output Phototransistor

Collector-Emitter Voltage	30 V
Emitter-Collector Voltage	5 V
Power Dissipation	100 mW

### Electrical Characteristics ( $T_A = 25^{\circ}\text{C}$ unless otherwise noted)

SYMBOL	PARAMETER	MIN	TYP	MAX	UNITS	TEST CONDITIONS
--------	-----------	-----	-----	-----	-------	-----------------

#### Input IR LED

$V_F$	Forward Voltage	1.2	2.0	2.3	V	$I_F = 20 \text{ mA}$
$I_R$	Reverse Current	-	-	100	$\mu\text{A}$	$V_R = 2 \text{ V}$
$\lambda_P$	Peak Emission Wavelength	-	650	-	nm	$I_F = 20 \text{ mA}$

#### Output Phototransistor

$V_{(BR)CEO}$	Collector Emitter Breakdown Voltage	30	-	-	V	$I_C = 100 \mu\text{A}$
$V_{(BR)ECO}$	Emitter Collector Breakdown Voltage	5	-	-	v	$I_E = 100 \mu\text{A}$
$I_{CEO}$	Collector Dark Current	-	-	100	nA	$V_{CE} = 10 \text{ V}, I_F = 0$
$T_r$	Rise Time	-	300	-	$\mu\text{s}$	$V_{CE} = 5 \text{ Volts}^{(3)}$ $I_C = 1 \text{ mA}$ $R_L = 20 \text{ K}\Omega$
$T_f$	Fall Time	-	300	-	$\mu\text{s}$	

#### Coupled Characteristics


$I_{C(ON)}$	On-State Collector Current	0.25	-	-	mA	$d = 0.030" (.76 \text{ mm})^{(1)(2)}$ $I_F = 20 \text{ mA}, V_{CE} = 5 \text{ V}$
$V_{CE(SAT)}$	Collector Emitter Saturation Voltage	-	-	0.4	V	$d = 0.030" (.76 \text{ mm})^{(1)(2)}$ $I_C = 50 \mu\text{A}, I_F = 20 \text{ mA}$
$I_{CX}$	Crosstalk Collector Current	-	-	0.05	mA	$I_F = 20 \text{ mA}, V_{CE} = 5 \text{ V}$ No reflective test surface present

#### Notes:


1. "d" is the distance from the assembly's lens surface to the reflective surface.
2. Measured using 90% diffuse reflectance white test card as the reflecting surface.
3. Typical values by design. Rise and Fall times are not tested.
4. Methanol or Isopropanol are recommended as cleaning agents. Plastic housing is soluble in chlorinated hydrocarbons and ketones.

OPTEK reserves the right to make changes at any time in order to improve design and to supply the best product possible.


### Typical Drive Circuit



Example reflective target with  
0.004", 0.008", and .012" line  
widths spaced 0.050" apart






### Typical Output Voltage vs Time



OPTEK reserves the right to make changes at any time in order to improve design and to supply the best product possible.

## Typical Performance Curves



OPTEK reserves the right to make changes at any time in order to improve design and to supply the best product possible.