


Optically Coupled Isolator

OPI7002, OPI7002RCE, OPI7010, OPI710RCE
OPI7320, OPI7320RCE, OPI7340, OPI7340RCE



Features:

- ± 6 kV electrical isolation
- Inexpensive plastic housing
- Choice of phototransistor or photodarlington output
- UL registered File No. E8730*



Description:

Each **OPI7002** and **OPI7010** consists of an infrared emitting diode coupled to a NPN silicon phototransistor. The LED and sensor are encased in a black, low-cost plastic housing. Pin spacing is compatible with standard dual-in-line packages.

Each **OPI7320** and **OPI7340** consists of an infrared emitting diode coupled to a NPN silicon photodarlington. The LED and sensor are encased in a high dielectric plastic housing. Pin spacing is compatible with standard dual-in-line packages.

The RCE versions reverses the Phototransistor Emitter and Collector pin-out.


Custom electrical, wire and cabling and connectors are available. Contact your local representative or OPTEK for more information.

Applications:


- Requiring high voltage isolation between input and output
- Electrical isolation in dirty environments
- Industrial equipment
- Medical equipment
- Office equipment

Ordering Information							
Part Number	LED Peak Wavelength	Sensor	Isolation Voltage (,000)	CTR Min	I _F (mA) Typ / Max	V _{CE} (Volts) Max	Lead Length / Spacing
OPI7002	890 nm	Transistor	6	20	10 / 50	30	0.30" / 0.30"
OPI7010				100			
OPI7320	890 nm or 935 nm	Darlington	6	200	5 / 50	15	0.30" / 0.30"
OPI7340				400			


OPI7002, OPI7010





OPI7002RCE, OPI7010RCE





OPI7320, OPI7340



OPI7320RCE, OPI7340RCE



Pin #	LED	Pin #	Transistor/ RCE
2	Cathode	3	Collector / Emitter
1	Anode	4	Emitter / Collector



RoHS

OPTEK reserves the right to make changes at any time in order to improve design and to supply the best product possible.

Optically Coupled Isolator

OPI7002, OPI7002RCE, OPI7010, OPI710RCE

OPI7320, OPI7320RCE, OPI7340, OPI7340RCE



Absolute Maximum Ratings ($T_A = 25^\circ \text{C}$ unless otherwise noted)

Operating Temperature Range	-40°C to $+85^\circ \text{C}$
Storage Temperature Range	-40°C to $+85^\circ \text{C}$
Input-to-Output Isolation Voltage ⁽¹⁾⁽²⁾	$\pm 6 \text{ kVDC}$
Lead Soldering Temperature [1/16 inch (1.6 mm) from the case for 5 seconds with soldering iron] ⁽³⁾	260°C

Input Diode

Forward DC Current	50 mA
Peak Forward current (1 μs pulse width, 300 pps)	3 A
Reverse Voltage	2 V
Power Dissipation ⁽³⁾	100 mW

Output Phototransistor

Collector-Emitter Voltage OPI7002, OPI7010, OPI7002RCE, OPI7010RCE OPI7320, OPI7340, OPI7320RCE, OPI7340RCE	30 V 15 V
Emitter-Collector Voltage	5.0 V
Power Dissipation ⁽³⁾	100 mW

Notes:

- (1) Measured with input leads and output leads shorted.
- (2) RMA flux is recommended. Duration can be extended to 10 seconds maximum when flow soldering.
- (3) Derate linearly 1.66 mW/ $^\circ \text{C}$ above 25°C .

OPTEK reserves the right to make changes at any time in order to improve design and to supply the best product possible.

Optically Coupled Isolator

OPI7002, OPI7002RCE, OPI7010, OPI710RCE

OPI7320, OPI7320RCE, OPI7340, OPI7340RCE



Electrical Characteristics ($T_A = 25^\circ \text{C}$ unless otherwise noted)

SYMBOL	PARAMETER	MIN	TYP	MAX	UNITS	TEST CONDITIONS
--------	-----------	-----	-----	-----	-------	-----------------

Input Diode (See OP140 or OP240 for additional information—for reference only)

V_F	Forward Voltage	-	1.2	1.70	V	$I_F = 10 \text{ mA}$
I_R	Reverse Current	-	-	100	μA	$V_R = 2.0 \text{ V}$

Output Phototransistor (OPI7002, OPI7010) (See OP550 for additional information—for reference only)

Output Photodarlington (OPI7320, OPI7340) (See OP560 for additional information—for reference only)

$V_{(BR)CEO}$	Collector-Emitter Breakdown Voltage OPI7002/RCE, OPI7010/RCE OPI7320/RCE, OPI7340/RCE	30 15	- -	- -	V	$I_C = 100 \mu\text{A}, I_F = 0$
$V_{(BR)ECO}$	Emitter-Collector Breakdown Voltage	5	-	-	V	$I_E = 100 \mu\text{A}, I_F = 0$
I_{CEO}	Collector-Emitter Dark Current	-	-	100	nA	$V_{CE} = 10 \text{ V}, I_F = 0$

Coupled

I_C/I_F	DC Current Transfer Ratio OPI7002, OPI7002RCE OPI7010, OPI7010RCE OPI7320, OPI7320RCE OPI7340, OPI7340RCE	20 100 200 400	- - - -	- - - -	%	$I_F = 10 \text{ mA}, V_{CE} = 5 \text{ V}$ $I_F = 10 \text{ mA}, V_{CE} = 5 \text{ V}$ $I_F = 5 \text{ mA}, V_{CE} = 5 \text{ V}$ $I_F = 5 \text{ mA}, V_{CE} = 5 \text{ V}$
$V_{(SAT)}$	Collector-Emitter Saturation Voltage OPI7002/RCE, OPI7010/RCE OPI7320/RCE, OPI7340/RCE	- -	- -	0.4 1.0	V	$I_F = 10 \text{ mA}, I_C = 0.50 \text{ mA}$ $I_F = 5 \text{ mA}, I_C = 2 \text{ mA}$
V_{ISO}	Isolation Voltage ⁽¹⁾	6	-	-	kVDC	See note 1
$T_{(ON)}$	Turn-On Time OPI7002/RCE, OPI7010/RCE OPI7320/RCE, OPI7340/RCE	- -	4 150	- -	μs	$V_{CE} = 10 \text{ V}, I_C = 10 \text{ mA}, R_L = 100 \Omega$
$T_{(OFF)}$	Turn-Off Time OPI7002/RCE, OPI7010/RCE OPI7320/RCE, OPI7340/RCE	- -	3 125	- -		
C_{IO}	Capacitance Input-to-Output ⁽¹⁾	-	0.2	-	pF	$V_{IO} = 0, F = 1 \text{ MHz}$

Notes:

(1) Measured with input leads and output leads shorted.

OPTEK reserves the right to make changes at any time in order to improve design and to supply the best product possible.