


# Plastic Infrared Emitting Diode

## OP290 Series



### Features:

- Choice of narrow or wide irradiance pattern
- Choice of power ranges
- Choice of T-1¾, TO-18 or T-46 package
- Higher power output than GaAs at equivalent LEDs



### Description:

Each device in this series, is a gallium aluminum arsenide infrared Light Emitting Diode (LED) that is molded in an IR-transmissive package with a wavelength centered at 890 nm, which closely matches the spectral response of silicon phototransistors, except for OP298 (AA, AB, AC, AD), which has either an 850 nm or 875 nm center wavelength. For identification purposes, each LED anode lead is longer than the cathode lead. **Package T-1¾** devices include: **OP290, OP291, OP292, OP294, OP295, OP296, OP297, OP299 (A, B, C) and OP297FAB,** **Plastic Package TO-18 or TO-46** devices include: **OP293 and OP298 (A, B, C, AA, AB, AC, AD).**

Each **OP290, OP291** and **OP292** series come in three electrical parameters options A, B and C. The **OP290** series forward current is specified under pulse conditions up to 1.5 amps, the **OP291** series forward current is specified under pulse conditions up to 100 milliamps and the **OP292** series forward current is specified under pulse conditions up to 1 amp. The Cathode Lead length is 0.06" (1.52 mm) shorter than the Anode Lead. The silver-copper lead frame offers excellent thermal characteristics.

Each **OP293** and **OP298** series come in three electrical parameter options A, B and C. The **OP293** series has an included emission angle of 60° while the **OP298** series has an included emission angle of 25°. The Cathode Lead length is 0.06" (1.52 mm) shorter than the Anode Lead. These devices, which come in a variety of power ranges offering a low cost replacement for TO-18 or TO-46 hermetic packages.

Each **OP298** series come with a high irradiance output versions with four electrical parameter options AA, AB, AC and AD. These power options are in the range of **5X** greater than the A, B or C options. The **OP298** series has an included emission angle of 25°. The Cathode Lead length is 0.06" (1.52 mm) shorter than the Anode Lead. These devices, which come in a variety of power ranges offering a low cost replacement for TO-18 or TO-46 hermetic packages.

**OP294** and **OP299** are designed for low-current or power-limited applications, such as battery supplies. They are similar to the **OP290** and **OP295**, but use a smaller chip that increases output efficiency at low current levels by increasing current density. Light output can be maximized with continuous (D.C.) forward current up to 100 mA or with pulsed forward current up to 750 mA. The Cathode Lead length is 0.06" (1.52 mm) shorter than the Anode Lead.

Each **OP295, OP296** and **OP297** series come in three electrical parameters options A, B and C. The **OP295** series forward current is specified under pulse conditions up to 5 amps, the **OP296** series forward current is specified under pulse conditions up to 2 amps and the **OP297** series forward current is specified under pulse conditions up to 1 amp. The Cathode Lead length is 0.06" (1.52 mm) shorter than the Anode Lead. The **OP297FAB** has a reversed polarity from the **OP297A, B or C**. The silver-copper lead frame offers excellent thermal characteristics.

*All of these devices are spectrally and mechanically matched to the OP593 and OP598 series phototransistors.*

*Please refer to Application Bulletins 208 and 210 for additional design information and reliability (degradation) data.*

### Applications:



- Non-contact reflective object sensor
- Machine automation
- Door sensor
- Assembly line automation
- Machine safety
- Battery-operated applications
- End of travel sensor

RoHS

OPTEK reserves the right to make changes at any time in order to improve design and to supply the best product possible.

# Plastic Infrared Emitting Diode

## OP290 Series



### Part Number Guide — OP290 - OP299 Series

OP 2 9 X X W

Optek Assembly

Photodiode Output Family

Maximum Forward Current

- 0, 5 — 5 amps
- 1, 6 — 2 amps
- 2, 7 — 1 amps
- 3, 8 — 200 milli-amps
- 4, 9 — 750 milli-amps

Electrical Specification Variations:

- A — Parameter A
- B — Parameter B
- C — Parameter C
- D — Parameter D
- AA — Parameter BA
- AB — Parameter BB
- AC — Parameter BC
- AD — Parameter BD




### T-1 $\frac{3}{4}$ Package OP290, OP291, OP292, OP294, OP295, OP296, OP297, OP299

#### Electrical Connection A, B, C, D

| Pin # | LED<br>X=0.060" (1.52 mm) |
|-------|---------------------------|
| 1     | Anode                     |
| 2     | Cathode                   |

#### Electrical Connection OP297AB

| Pin # | LED<br>X=0.060" (1.52 mm) |
|-------|---------------------------|
| 1     | Cathode                   |
| 2     | Anode                     |




### TO-18, TO-46 Package OP293 & OP298



#### Electrical Connection A, B, C, AA, AB, AC, AD

| Pin # | LED<br>X=0.060" (1.52 mm) |
|-------|---------------------------|
| 1     | Anode                     |
| 2     | Cathode                   |



DIMENSIONS ARE IN: [MILLIMETERS]  
INCHES

OPTEK reserves the right to make changes at any time in order to improve design and to supply the best product possible.

# Plastic Infrared Emitting Diode

## OP290 Series



### Absolute Maximum Ratings ( $T_A=25^{\circ}\text{C}$ unless otherwise noted)

|                                                                                                                                                                                                                                    |                                                                         |
|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------|
| Storage and Operating Temperature Range                                                                                                                                                                                            | $-40^{\circ}\text{C}$ to $+100^{\circ}\text{C}$                         |
| Reverse Voltage<br>OP290, OP292, OP294, OP295, OP297, OP299<br>OP291, OP293, OP296, OP298                                                                                                                                          | 5.0 V<br>2.0 V                                                          |
| Continuous Forward Current<br>OP290, OP291, OP292<br>OP294, OP295, OP299<br>OP295, OP296, OP297                                                                                                                                    | 150 mA <sup>(1)</sup><br>100 mA <sup>(1)</sup><br>150 mA <sup>(1)</sup> |
| Continuous Forward Current, OP293, OP298<br>Free Air<br>Board Mounted<br>Full Heat Sink                                                                                                                                            | 100 mA<br>133 mA<br>200 mA                                              |
| Peak Forward Current<br>OP290, OP295 (25 $\mu\text{s}$ pulse width)<br>OP291, OP296 (100 $\mu\text{s}$ pulse width)<br>OP292, OP297 (100 $\mu\text{s}$ pulse width)<br>OP293, OP298 (25 $\mu\text{s}$ pulse width)<br>OP294, OP299 | 5.0 A<br>2.0 A<br>1.00 A<br>2.0 A<br>750 mA                             |

#### Notes:

- For OP290, OP291, OP292, OP295, OP296 and OP297, derate linearly 1.67 mA/ $^{\circ}\text{C}$  above  $25^{\circ}\text{C}$  (free-air). When used with heat sink (see note 5), derate linearly 2.07 mA/ $^{\circ}\text{C}$  above  $65^{\circ}\text{C}$  (normal use). For OP293 and OP298, when measured in free-air, derate power dissipation linearly 1.43 mW/ $^{\circ}\text{C}$  above  $25^{\circ}\text{C}$ . For OP294 and OP299, derate linearly 1.80 mW/ $^{\circ}\text{C}$  above  $25^{\circ}\text{C}$ .

### Absolute Maximum Ratings ( $T_A=25^{\circ}\text{C}$ unless otherwise noted)

|                                                                                               |                                                |
|-----------------------------------------------------------------------------------------------|------------------------------------------------|
| Maximum Duty Cycle<br>OP290 (25 $\mu\text{s}$ pulse width @ 5 A)                              | 1.25% <sup>(1)</sup>                           |
| Lead Soldering Temperature [1/16 inch (1.6 mm) from case for 5 seconds with soldering iron]   | $260^{\circ}\text{C}$ <sup>(2)</sup>           |
| Power Dissipation, Free Air<br>OP290, OP291, OP292, OP295, OP296, OP297<br>OP293, OP298       | 333 mW <sup>(3)</sup><br>142 mW <sup>(3)</sup> |
| Power Dissipation, Board Mounted<br>OP290, OP291, OP292, OP295, OP296, OP297<br>OP293, OP298  | 533 mW <sup>(4)</sup><br>200 mW <sup>(4)</sup> |
| Power Dissipation, Full Heat Sink<br>OP290, OP291, OP292, OP295, OP296, OP297<br>OP293, OP298 | 1.11 W <sup>(5)</sup><br>400 mW <sup>(5)</sup> |
| Power Dissipation<br>OP294, OP299                                                             | 180 mW                                         |

#### Notes:

- For OP290, OP291, OP292, OP295, OP296 and OP297, refer to graph of Maximum Peak Pulse Current vs Pulse Width.
- For all OPs in this series, RMA flux is recommended. Duration can be extended to 10 second maximum when soldering. A maximum of 20 grams force may be applied to the leads when flow soldering.
- For OP290, OP291, OP292, OP295, OP296 and OP297, measured in free-air. Derate linearly 3.33 mW/ $^{\circ}\text{C}$  above  $25^{\circ}\text{C}$ .
- For OP290, OP291 and OP292, mounted on 1/16" (1.6 mm) thick PCBoard with each lead soldered through 80 mil square lands 0.250" (6.35 mm) below flange of device. Derate linearly 5.33 mW/ $^{\circ}\text{C}$  above  $62.5^{\circ}\text{C}$ . For OP293 and OP298, mounted on 1/16" (1.60 mm) thick PCBoard with each lead soldered through 80 mil square lands 0.250" (6.35 mm) below flange of device. Derate power dissipation linearly 2.00 mW/ $^{\circ}\text{C}$  above  $25^{\circ}\text{C}$  (normal use). For OP295, OP296 and OP297, mounted on 1/16" (1.6 mm) thick PCBoard with each lead soldered through 80 mil square lands 0.250" (6.35 mm) below flange of device. Derate linearly 5.33 mW/ $^{\circ}\text{C}$  above  $25^{\circ}\text{C}$ .
- Immersed in silicone fluid to simulate infinite heat sink. For OP290, OP291 and OP292, derate linearly 11.1 mW/ $^{\circ}\text{C}$  above  $95^{\circ}\text{C}$ . For OP293 and OP298, derate power dissipation linearly 2.50 mW/ $^{\circ}\text{C}$  above  $25^{\circ}\text{C}$ . For OP295, OP296 and OP297, derate linearly 11.1 mW/ $^{\circ}\text{C}$  above  $25^{\circ}\text{C}$ .

OPTEK reserves the right to make changes at any time in order to improve design and to supply the best product possible.

# Plastic Infrared Emitting Diode

## OP290 Series



### Electrical Characteristics ( $T_A = 25^\circ\text{C}$ unless otherwise noted)

| SYMBOL             | PARAMETER                   | MIN  | TYP | MAX  | UNITS | TEST CONDITIONS                                                                                                           |
|--------------------|-----------------------------|------|-----|------|-------|---------------------------------------------------------------------------------------------------------------------------|
| <b>Input Diode</b> |                             |      |     |      |       |                                                                                                                           |
| $E_{E(APT)}^{(2)}$ | Apertured Radiant Incidence |      |     |      |       |                                                                                                                           |
|                    | OP290A                      | 210  | -   | -    |       | $I_F = 1.50 \text{ A}^{(1)(2)}$<br>Measured into a 0.250" [6.35mm] aperture<br>0.2" (5.08 mm) from the tip of the lens.   |
|                    | OP290B                      | 180  | -   | 300  |       |                                                                                                                           |
|                    | OP290C                      | 150  | -   | -    |       |                                                                                                                           |
|                    | OP291A                      | 16   | -   | -    |       | $I_F = 100 \text{ mA}^{(1)(2)}$<br>Measured into a 0.250" [6.35mm] aperture<br>0.2" (5.08 mm) from the tip of the lens.   |
|                    | OP291B                      | 13   | -   | 26   |       |                                                                                                                           |
|                    | OP291C                      | 10   | -   | -    |       |                                                                                                                           |
|                    | OP292A                      | 2.7  | -   | -    |       | $I_F = 20 \text{ mA}^{(1)(2)}$<br>Measured into a 0.250" [6.35mm] aperture<br>0.2" (5.08 mm) from the tip of the lens.    |
|                    | OP292B                      | 2.2  | 3.6 | 4.4  |       |                                                                                                                           |
|                    | OP292C                      | 1.7  | -   | -    |       |                                                                                                                           |
|                    | OP293A                      | 16   | -   | -    |       | $I_F = 100 \text{ mA}^{(1)(2)}$<br>Measured into a 0.250" [6.35mm] aperture<br>0.2" (5.08 mm) from the tip of the lens.   |
|                    | OP293B                      | 13   | 22  | 26   |       |                                                                                                                           |
|                    | OP293C                      | 10   | -   | -    |       |                                                                                                                           |
|                    | OP294                       | 0.50 | -   | 1.50 |       | $I_F = 5 \text{ mA}^{(1)(2)}$<br>Measured into a 0.250" [6.35mm] aperture<br>0.200" (5.08mm) from the tip of the lens.    |
|                    | OP295A                      | 44   | -   | -    |       | $I_F = 1.50 \text{ A}^{(1)(2)}$<br>Measured into a 0.250" [6.35mm] aperture<br>1.129" (28.7 mm) from the tip of the lens. |
|                    | OP295B                      | 33   | -   | 77   |       |                                                                                                                           |
|                    | OP295C                      | 22   | -   | -    |       |                                                                                                                           |
|                    | OP296A                      | 3.6  | -   | -    |       | $I_F = 100 \text{ mA}^{(1)(2)}$<br>Measured into a 0.250" [6.35mm] aperture<br>1.129" (28.7 mm) from the tip of the lens. |
|                    | OP296B                      | 2.6  | -   | 6.6  |       |                                                                                                                           |
|                    | OP296C                      | 1.6  | -   | -    |       |                                                                                                                           |
|                    | OP297FAB                    | 2.4  | -   | -    |       | $I_F = 20 \text{ mA}^{(1)(2)}$<br>Measured into a 0.250" [6.35mm] aperture<br>1.129" (28.7 mm) from the tip of the lens.  |
|                    | OP297A                      | 0.7  | -   | -    |       |                                                                                                                           |
|                    | OP297B                      | 0.5  | 1.0 | 1.3  |       |                                                                                                                           |
|                    | OP297C                      | 0.3  | -   | -    |       |                                                                                                                           |
|                    | OP298A                      | 3.0  | -   | -    |       | $I_F = 100 \text{ mA}^{(1)(2)}$<br>Measured into a 0.250" [6.35mm] aperture<br>0.2" (5.08 mm) from the tip of the lens.   |
|                    | OP298B                      | 2.4  | -   | 4.8  |       |                                                                                                                           |
|                    | OP298C                      | 1.8  | -   | -    |       |                                                                                                                           |
|                    | OP298AA                     | 3.5  | -   | -    |       | $I_F = 100 \text{ mA}^{(1)(2)}$<br>Measured into a 0.250" [6.35mm] aperture<br>1.129" (28.7 mm) from the tip of the lens. |
|                    | OP298AB                     | 3.5  | -   | 8.5  |       |                                                                                                                           |
|                    | OP298AC                     | 6.5  | -   | 11.5 |       |                                                                                                                           |
|                    | OP298AD                     | 8.5  | -   | -    |       |                                                                                                                           |
|                    | OP299                       | 0.15 | -   | 0.45 |       | $I_F = 100 \text{ mA}^{(1)(2)}$<br>Measured into a 0.250" [6.35mm] aperture<br>1.129" (28.7 mm) from the tip of the lens. |

#### Notes:

1. Measurement is taken at the end of a single 100  $\mu\text{s}$  pulse. Heating due to increased pulse rate or pulse width will cause a decrease in reading.
2. Measurement of the average apertured radiant energy incident upon a sensing area 0.250" (6.35 mm) in diameter perpendicular to and centered on the mechanical axis of the lens and the specified distance from the end of the device. On all models in this series,  $E_{E(APT)}$  is not necessarily uniform within the measured area.
3. Measurement is taken at the end of a single 10 ms pulse. Heating due to increased pulse rate or pulse width will cause a decrease in reading.

OPTEK reserves the right to make changes at any time in order to improve design and to supply the best product possible.

# Plastic Infrared Emitting Diode

## OP290 Series



### Electrical Characteristics ( $T_A = 25^\circ\text{C}$ unless otherwise noted)

| SYMBOL                       | PARAMETER                                                                                                                                                    | MIN                        | TYP                        | MAX                                          | UNITS                | TEST CONDITIONS                                                                                                                                 |
|------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------------------|----------------------------|----------------------------------------------|----------------------|-------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Input Diode</b>           |                                                                                                                                                              |                            |                            |                                              |                      |                                                                                                                                                 |
| $V_F$                        | Forward Voltage <sup>(3)</sup><br>OP290, OP295<br>OP291, OP296<br>OP292, OP297, OP297FAB<br>OP293, OP298 (A, B, C)<br>OP298 (AA, AB, AC, AD)<br>OP294, OP299 | -<br>-<br>-<br>-<br>-<br>- | -<br>-<br>-<br>-<br>-<br>- | 4.00<br>2.00<br>1.75<br>2.00<br>2.00<br>1.50 | V                    | $I_F = 1.50\text{ A}$<br>$I_F = 100\text{ mA}$<br>$I_F = 20\text{ mA}$<br>$I_F = 1.50\text{ A}$<br>$I_F = 100\text{ mA}$<br>$I_F = 5\text{ mA}$ |
| $I_R$                        | Reverse Current <sup>(3)</sup><br>OP290, OP292<br>OP291, OP293, OP298 (A, B, C), OP296<br>OP298 (AA, AB, AC, AD)<br>OP294, OP299<br>OP295, OP297<br>OP297FAB | -<br>-<br>-<br>-<br>-<br>- | -<br>-<br>-<br>-<br>-<br>- | 10<br>100<br>100<br>10<br>10<br>15           | $\mu\text{A}$        | $V_R = 5\text{ V}$<br>$V_R = 2\text{ V}$<br>$V_R = 2\text{ V}$<br>$V_R = 2\text{ V}$<br>$V_R = 5\text{ V}$<br>$V_R = 5\text{ V}$                |
| $\lambda_P$                  | Wavelength at Peak Emission<br>OP290, OP291, OP292, OP293, OP294,<br>OP295, OP296, OP297, OP298 (A, B, C),<br>OP299<br>OP297FAB, OP298 (AA, AB, AC, AD)      | -<br>-                     | 890<br>875                 | -<br>-                                       | nm                   | $I_F = 10\text{ mA}$                                                                                                                            |
| B                            | Spectral Bandwidth between Half Power Points                                                                                                                 | -                          | 80                         | -                                            | nm                   | $I_F = 10\text{ mA}$                                                                                                                            |
| $\Delta\lambda_P / \Delta T$ | Spectral Shift with Temperature                                                                                                                              | -                          | +0.18                      | -                                            | nm/ $^\circ\text{C}$ | $I_F = \text{Constant}$                                                                                                                         |
| $\theta_{HP}$                | Emission Angle at Half Power Points<br>OP290, OP291, OP292, OP294<br>OP293<br>OP295, OP296, OP297, OP299<br>OP298                                            | -<br>-<br>-<br>-           | 50<br>60<br>20<br>25       | -<br>-<br>-<br>-                             | Degree               | $I_F = 20\text{ mA}$                                                                                                                            |
| $t_r$                        | Output Rise Time                                                                                                                                             | -                          | 500                        | -                                            | ns                   | $I_{F(PK)} = 100\text{ mA}$ , $PW = 10\text{ }\mu\text{s}$ , and<br>D.C. = 10.0%                                                                |
| $t_f$                        | Output Fall Time                                                                                                                                             | -                          | 250                        | -                                            | ns                   |                                                                                                                                                 |





OPTEK reserves the right to make changes at any time in order to improve design and to supply the best product possible.

# Plastic Infrared Emitting Diode

## OP290 Series







### OP290, OP291, OP292, OP293, OP294, (A, C)




OPTEK reserves the right to make changes at any time in order to improve design and to supply the best product possible.

### OP295, OP296, OP297, OP298, OP299



OPTEK reserves the right to make changes at any time in order to improve design and to supply the best product possible.

OP290A/OP593 and OP295/OP598 - Coupling Characteristics



OPTEK reserves the right to make changes at any time in order to improve design and to supply the best product possible.