

REV	ECN. NO.	APP	DATE
A	EDIÇÃO INICIAL		
B	NOVO CÓDIGO		

### Electrical Characteristics

Current Rating: 1.0 Amp. Max..

Dielectric Withstand Voltage:

800V AC RMS for 60Seconds.

Insulation Resistance:

1000M Ohms Min. at 500V DC.

## HOW TO ORDER: 3020[S][ ][ ]DR 1 2 3

1- Version:

(S)-180°

2- N° of Ways:

See Table

3- Terminal Plating:

(D)-FLASH Au

(F)-0,38um Au

(G)-0,76um Au

(C)-0,38um Au/Sn

(H)-0,76um Au/Sn

Pos.	Dimension			Pos.	Dimension		
	A	B	C		A	B	C
06	13.20	12.10	4.00	28	35.20	34.10	26.00
08	15.20	14.10	6.00	30	37.20	36.10	28.00
10	17.20	16.10	8.00	32	39.20	38.10	30.00
12	19.20	18.10	10.00	34	41.20	40.10	32.00
14	21.20	20.10	12.00	36	43.20	42.10	34.00
16	23.20	22.10	14.00	40	47.20	46.10	38.00
18	25.20	24.10	16.00	44	51.20	50.10	42.00
20	27.20	26.10	18.00	50	57.20	56.10	48.00
22	29.20	28.10	20.00	60	67.20	66.10	58.00
24	31.20	30.10	22.00	64	71.20	70.10	62.00
26	33.20	32.10	24.00	68	75.20	74.10	66.00



MATRIX TECNOLOGIA IND. E COM. LTDA.

UNIT  
mm

SCALE


TITLE

DATE DECEMBER 2009

TOLERANCE: ±0.25

BOX HEADER 2,00mm  
PROFILE 5,6mm SMT

APP. BY



MATL

CHK. BY

DWG. NO.

DR. BY Felipe