

REV	ECN. NO.	APP	DATE
A	EDIÇÃO INICIAL		

Specification:
 Current Rating: 3 Amp.
 Withstanding Voltage: AC 500V for 1 Minute.
 Insulation Resistance: 1000MΩ Min. at DC 500V.
 Contact Resistance: 15mΩ Max.
 Operating Temperature: -40°C ~ +105°C.

HOW TO ORDER: 2216[][][][R] 1 2 3 4

1- Pin Style
 (R)-90°
 (S)-180°
 2- Nr. of Ways
 Table

3- Terminal Plating:
 (D)-FLASH Au
 (F)-0,38um Au
 (G)-0,76um Au
 (C)-0,38um Au/Sn
 (H)-0,76um Au/Sn

4- Latch:
 (00)-W/O Latch
 (01)-Short Latch
 (02)-Long Latch

Pos.	Dim. A	Dim. B	Dim. C	Dim. D
10	31.90	21.84	10.16	27.94
14	36.98	26.92	15.24	33.02
16	39.52	29.46	17.78	35.56
20	44.60	34.54	22.86	40.64
24	49.68	39.62	27.94	45.72
26	52.22	42.16	30.48	48.26

Pos.	Dim. A	Dim. B	Dim. C	Dim. D
30	57.30	47.24	35.56	53.34
34	62.38	52.32	40.64	58.42
40	70.00	59.94	48.26	66.04
50	82.70	72.64	60.96	78.74
60	95.40	85.34	73.66	91.44
64	100.48	90.42	78.74	96.52



MATRIX Tecnologia Ind. e Com. Ltda.

UNIT	SCALE	TITLE	DATE
mm		2.54mm Ejector Box Header 180°	September 2007
TOLERANCE: ±0.25			APP. BY
		MATL	CHK. BY
		DWG. NO.	DR. BY Diego