

PC BOARD LAYOUT

REV	ECN. NO.	APP	DATE
A	EDIÇÃO INICIAL		
B	NOVO CÓDIGO		



**ELECTRICAL:**

1. Current Rating : 1,5 AMP
2. Voltage Rating : 150 VAC
3. Contact Resistance : 20 Milliohms MAX
4. Insulation Resistance : 500 Milliohms MIN
5. Dielectric Withstanding Voltage : 1000 VAC, 1min

**HOW TO ORDER:  
2002[8P8C][ ][Y][2]61R**

**1 2 3 4**

- |   |  |
|---|--|
| 1- No. Contact (8P8C)   | 3- Body Option: (Y)-With Fully Shielded  |
| 2- Contact Plating: ( )-Gold 6U" (15)-Gold 15U" (30)-Gold 30U" (50)-Gold 50U" | 4- Stacked Option: (2)-2x1 Jacks (4)-2x2 Jacks (6)-2x3 Jacks (8)-2x4 Jacks (12)-2x6 Jacks (16)-2x8 Jacks |

 <b>MATRIX Tecnologia Ind. e Com. Ltda.</b>			
UNIT mm	SCALE	TITLE	DATE DECEMBER 2009
TOLERANCE: ±0.25		Stacked P.C.B Jack	APP. BY
		MATL	CHK. BY
DWG. NO.		DR. BY <b>Felipe</b>	