

# SOT23 NPN SILICON PLANAR HIGH PERFORMANCE TRANSISTOR


## FMMT455

ISSUE 3 – FEBRUARY 1996

### FEATURES

- \* 140 Volt  $V_{CE0}$
- \* 1 Amp continuous current
- \*  $P_{tot}$  = 500 mW

PARTMARKING DETAIL – 455



SOT23

### ABSOLUTE MAXIMUM RATINGS.

PARAMETER	SYMBOL	VALUE	UNIT
Collector-Base Voltage	$V_{CBO}$	160	V
Collector-Emitter Voltage	$V_{CEO}$	140	V
Emitter-Base Voltage	$V_{EBO}$	5	V
Peak Pulse Current	$I_{CM}$	2	A
Continuous Collector Current	$I_C$	1	A
Base Current	$I_B$	200	mA
Power Dissipation at $T_{amb}=25^{\circ}C$	$P_{tot}$	500	mW
Operating and Storage Temperature Range	$T_j; T_{stg}$	-55 to +150	$^{\circ}C$

### ELECTRICAL CHARACTERISTICS (at $T_{amb} = 25^{\circ}C$ ).

PARAMETER	SYMBOL	MIN.	MAX.	UNIT	CONDITIONS.
Collector-Base Breakdown Voltage	$V_{(BR)CBO}$	160		V	$I_C=100\mu A$
Collector-Emitter Sustaining Voltage	$V_{CEO(sus)}$	140		V	$I_C=10mA^*$
Emitter-Base Breakdown Voltage	$V_{(BR)EBO}$	5		V	$I_E=100\mu A$
Collector Cut-Off Current	$I_{CBO}$		0.1	$\mu A$	$V_{CB}=140V$
Emitter Cut-Off Current	$I_{EBO}$		0.1	$\mu A$	$V_{EB}=4V$
Collector-Emitter Saturation Voltage	$V_{CE(sat)}$		0.7	V	$I_C=150mA, I_B=15mA$
Static Forward Current Transfer Ratio	$h_{FE}$	100 10 Typ	300		$I_C=150mA, V_{CE}=10V^*$ $I_C=1A, V_{CE}=10V^*$
Transition Frequency	$f_T$	100		MHz	$I_C=50mA, V_{CE}=10V$ $f=100MHz$
Output Capacitance	$C_{obo}$		15	pF	$V_{CB}=10V, f=1MHz$

\* Measured under pulsed conditions. Pulse width=300 $\mu s$ . Duty cycle  $\leq 2\%$   
Spice parameter data is available upon request for this device

## TYPICAL CHARACTERISTICS

