




SPECIFICATIONS:

MATERIAL:-

INSULATOR: LCP, UL94V-0

CONTACT: PHOSPHOR BRONZE

FINISH:-

TIN PLATE

ELECTRICAL:-

CURRENT RATING: 0.5 AMP

DIELECTRIC VOLTAGE: 250V AC FOR ONE MINUTE

CONTACT RESISTANCE: 20 mΩ MAX.

INSULATION RESISTANCE: 50 MΩ MIN.

ENVIRONMENTAL:-

OPERATION TEMPERATURE: -40°C TO +85°C 

NOTES: ALL DIMENSIONS AND NOTES

MARKED * ARE CRITICAL AND

MUST BE CHECKED IN ACCORDANCE

WITH QUALITY DOC. QI-02A

 *STANDARD PACKAGING: TUBE
ADD 'R' TO END OF ORDER
CODE FOR TAPE AND REEL
PACKAGING (10500 MOQ APPLY)

*Mould not available. Contact
Sales for more details.

ORDER CODE 
F08-200 XX 46
NO. OF WAYS 

CONTACT	A	B	C	D
* 03	8.70	3.65	1.60	7.40
04	9.50	4.84	2.40	8.20
* 05	10.30	5.64	3.20	9.00
* 06	11.10	6.44	4.00	9.80
* 07	11.90	7.24	4.80	10.60
08	12.70	8.04	5.60	11.40
09	13.50	8.84	6.40	12.20
10	14.30	9.64	7.20	13.00
* 11	15.10	10.44	8.00	13.80
12	15.90	11.24	8.80	14.60
* 13	16.70	12.04	9.60	15.40
14	17.50	12.84	10.40	16.20
* 15	18.30	13.64	11.20	17.00
* 16	19.10	14.44	12.00	17.80
* 17	19.90	15.24	12.80	18.60
18	20.70	16.04	13.60	19.40
* 19	21.50	16.84	14.40	20.20
* 20	22.30	17.64	15.20	21.00
21	23.10	18.44	16.00	21.80
22	23.90	19.24	16.80	22.60
23	24.70	20.04	17.60	23.40
24	25.50	20.84	18.40	24.20
25	26.30	21.64	19.20	25.00
* 26	27.10	22.44	20.00	25.80
* 27	27.90	23.24	20.80	26.60
* 28	28.70	24.04	21.60	27.40
* 29	29.50	24.84	22.40	28.20
30	30.30	25.64	23.20	29.00

Leo	7	16.08.11	A360
Allan	6	09.07.10	A303
Allan	5	22.07.08	A147
Allan	4	21.12.07	A102
Allan	3	27.11.07	A092
Allan	2	20.09.07	A077
Allan	1	27.11.06	-

NAME	ISS.	DATE	C/NOTE
------	------	------	--------

APPROVED: T.L

CHECKED: Leo

DRAWN: Leo

CUSTOMER REF.:

ASSEMBLY DRG:

HARWIN

HARWIN USA
TEL: 603 893 5376
FAX: 603 893 5396
mis@harwin.com

HARWIN Europe (UK)
TEL: 023 9231 4545
FAX: 023 9231 4590
mis@harwin.co.uk

HARWIN Asia
TEL: +65 6 779 4909
FAX: +65 6 779 3868
mis@harwin.com.sg

THIS DRAWING AND ANY
INFORMATION OR DESCRIPTIVE
MATTER SET OUT HEREON ARE
CONFIDENTIAL AND COPYRIGHT
PROPERTY OF THE HARWIN
GROUP AND MUST NOT BE
DISCLOSED, LOANED, COPIED
OR USED FOR MANUFACTURING,
TENDERING OR FOR ANY
OTHER PURPOSE WITHOUT
THEIR WRITTEN PERMISSION.

TOLERANCES

X.X = $\pm 0.10\text{mm}$
X.XX = $\pm 0.05\text{mm}$

ANGLES = $\pm 3^\circ$
UNLESS STATED

MATERIAL:

SEE NOTES

FINISH:

SEE NOTES

S/AREA:

mm?


TITLE:

R/A TOP CONTACT ZIF SMT

DRAWING NUMBER:

F08-200 XX 46 

SHT
1
OF
2 



DIM	DESCRIPTION	TOLERANCE
S1	STRIP LENGTH	±1
S2	STRIP LENGTH	±1
D1	SUPPORT LENGTH	±1.5
D2	SUPPORT LENGTH	±1.5
P	CONDUCTOR PITCH	±0.08
PT	TOTAL CONDUCTOR PITCH	±0.1
W	TOTAL WIDTH	±0.1
L	OVERALL LENGTH	30~200=±3 201~400=±6 401~1000=±12
CW	CONDUCTOR WIDTH	±0.02
N	NO. OF CONDUCTOR	

Leo	7	16.08.11	A360
Allan	6	09.07.10	A303
Allan	5	22.07.08	A147
Allan	4	21.12.07	A102
Allan	3	27.11.07	A092
Allan	2	20.09.07	A077
Allan	1	27.11.06	-

	NAME	ISS.	DATE	C/NOTE
fact	APPROVED:		T.L	
	CHECKED:			
	DRAWN:		Leo	
	CUSTOMER REF.:			
	ASSEMBLY DRG:			

*STANDARD PACKAGING: TUBE
ADD 'R' TO END OF ORDER
CODE FOR TAPE AND REEL
PACKAGING (10500 MOQ APPLY)

*Mould not available. Contact
Sales for more details.

ORDER CODE

F08-200 XX 46

NO. OF WAYS