

## Audio Termination Panels



These panels are made from robust aluminium alloy extrusion and have 16 columns of unified XLR cutouts, fitted as standard with male or female 3 pin latching XLR's. Suitable for analogue or AES, these panels can also be supplied prewired to any of our other audio panels or just to a loom of a specified length.

Each unit has one clip on designation per row and two lacing bars. Standard finish is powder coat Storm Grey. Dawn grey or black available on request.

<b>AUDIO TERMINATION PANEL</b>	
<b>Product Code</b>	<b>Description</b>
ATP2216M	Audio Termination Panel 2U 2 x 16 XLR Male
ATP3316M	Audio Termination Panel 3U 3 x 16 XLR Male
ATP2216F	Audio Termination Panel 2U 2 x 16 XLR Female
ATP3416F	Audio Termination Panel 3U 3 x 16 XLR Female
ATP2216FM	Audio Termination Panel 2U 2 x 16 XLR Female & Male
ATP3316FM	Audio Termination Panel 3U 3 x 16 XLR Female & Male

As part of continual product improvement, the specifications, details and dimensions shown are subject to change without notice.

DEM Manufacturing  
 Hargreaves Way, Sawcliffe Industrial Park,  
 Scunthorpe, North Lincolnshire.  
 DN15 8RF  
 United Kingdom

Tel: +44 (0)1724 273200  
 Fax: +44 (0) 1724 280353  
 E-Mail: sales@dem-uk.com  
 Website: www.dem-uk.com