

Co-axial Termination Panels



Features:

Using suitably rated BNC connectors these panels can be used up to 3G. The BNC connectors are isolated from the front panel and can have a density of up to 24 channels on a single row. With a redesigned aluminium extrusion the designation strip is now clipped on to allow greater visibility and space for text.

Specifications of standard panels

- 75 ohm BNC bulkhead connectors
- 1 or 2 RU extruded aluminium front panel
- Clip on designation strip
- Lacing bar on the rear at a depth of 140mm

Product Code	Description
CTP112475R	Co-axial Termination Panel 1RU 1 X 24
CTP221675R	Co-axial Termination Panel 2RU 2 X 16
CTP222075R	Co-axial Termination Panel 2RU 2 X 20
CTP222475R	Co-axial Termination Panel 2RU 2 X 24

Custom panels

- 50 ohm BNC's
- Non standard layouts with up to 128 BNC's in a 4RU panel and silk-screening in place of designation strips

As part of continual product improvement, the specifications, details and dimensions shown are subject to change without notice.

DEM Manufacturing
 Hargreaves Way, Sawcliffe Industrial Park,
 Scunthorpe, North Lincolnshire. DN15 8RF
 United Kingdom.

Tel: +44 (0)1724 273200
 Fax: +44 (0) 1724 280353
 E-Mail: sales@dem-uk.com
 Website: www.dem-uk.com