

Description

Single or multipole hydraulic-magnetic circuit breakers with trip-free-mechanism and toggle actuation. A choice of switching characteristics ensures suitability for a wide range of applications. Industry standard dimensions and panel mounting. Auxiliary contacts optional. Low temperature sensitivity at rated load. Approved to CBE standard EN 60934 (IEC 60934) S-type HM CBE.

Typical applications

In the business fields Communication and Transport: power supplies, switchgear, instrumentation and process control engineering.

Standard current ratings and typical internal resistance values

| Current rating (A) | Trip curves and internal resistance (Ω) per pole | |
|--------------------|--|--------|
| | K1, M1, T1 | M2, T2 |
| 0.05 | 452 | 376 |
| 0.1 | 100 | 94 |
| 1 | 0.95 | 0.90 |
| 2 | 0.26 | 0.20 |
| 3 | 0.10 | 0.10 |
| 5 | 0.042 | 0.040 |
| 10 | < 0.02 | < 0.02 |
| 15 | < 0.02 | < 0.02 |
| 20 | < 0.02 | < 0.02 |
| 25 | < 0.02 | < 0.02 |
| 30 | < 0.02 | < 0.02 |
| 40 | < 0.01 | < 0.01 |
| 50 | < 0.01 | < 0.01 |
| 60 | < 0.01 | < 0.01 |
| 80 | < 0.01 | < 0.01 |
| 100 | < 0.01 | < 0.01 |
| 125 | < 0.01 | < 0.01 |

Interrupting capacity to EN 60934, UL 489 and UL 1077

| IEC 60934 – test series E: | | | |
|----------------------------|-----------------|-------------------------|---------------------|
| voltage | number of poles | I _N max. (A) | I _{cn} (A) |
| DC 80 V | 1 + 2 | 0.02...125 | 10 000 |
| AC 240/415 V | 1 - 6 | 0.02...80 | 6 x I _N |
| AC 240 V | 1 | 0.02...20 | 5 000 |
| UL 489 – test sequence Z: | | | |
| voltage | number of poles | I _N max. (A) | I _{cn} (A) |
| DC 80 V | 1 + 2 | 0.5...125 | 10 000 |
| AC 120 V | 1 | 0.5...80 | 5 000 |
| AC 120/240 V | 1 (2) | 0.5...80 | 5 000 |
| AC 240 V | 1 | 0.5...20 | 5 000 |
| UL 1077: | | | |
| voltage | number of poles | I _N max. (A) | I _{cn} (A) |
| DC 80 V | 1 + 2 | 0.02...125 | 10 000 |
| AC 277/480 V | 1 - 6 | 0.02...70 | 5 000 |



Technical data

| | |
|---|---|
| Voltage rating | 3 AC 415 V; AC 277/480 V; AC 120/240 V; AC 240 V; DC 80 V (higher DC voltages to special order) |
| Current rating range | 0.05...125 A single and multipole higher ratings upon request |
| Auxiliary circuit | AC 240 V 6 A DC 28 V 3 A DC 65 V 1 A DC 80 V 0.5 A |
| Typical life | 10,000 operations at 1 x I _N |
| Ambient temperature | -40...+85 °C (-40...+185 °F) |
| Insulation co-ordination (IEC 60664) | 2.5 kV/2 reinforced insulation in operating area |
| Dielectric strength | test voltage |
| operating area | AC 3,000 V |
| pole to pole | AC 1,500 V |
| main to auxiliary circuit | AC 3,000 V |
| switching to trip circuit | AC 1,500 V |
| Insulation resistance | > 100 MΩ (DC 500 V) |
| Degree of protection (IEC 60529) | operating area IP40 terminal area IP00 |
| Vibration | |
| upside down: | 10 g (57-2000 Hz) ± 0,76 mm (10-57 Hz) at 0.9 I _N |
| directions 1, 2, 3, 4, 5: | 10 g at 1 x I _N |
| with curves F1, F2: | 10 g at 0.8 x I _N in all planes. (57-2000 Hz) ± 0.76 mm (10-57 Hz) to IEC 60068-2-6, test Fc 10 frequency cycles/axis |
| Shock | |
| directions 1, 2, 3, 4, 5: | 100 g (11 ms) at 1 x I _N , |
| direction 6: | 100 g (11 ms) at 0.8 x I _N , |
| with curves F1, F2: | 100 g (11 ms) at 0.8 x I _N to IEC 60068-2-27, test Ea |
| Corrosion | 96 hours at 5% salt mist, to IEC 60068-2-11, test Ka |
| Humidity | 240 hours at 95 % RH, to IEC 60068-2-78, test Cab |
| Mass | approx. 90 - 120 g per pole depending on version |

Approvals

| | |
|----------------|--------------|
| VDE (EN 60934) | 1- to 6-pole |
| UL 489 | - |
| UL 1077 | 1- to 6-pole |
| CCC | 1- to 4-pole |

Ordering information for EN 60934 and UL 1077

Type No.

8345

Mounting

B flange mounting, with rectangular aperture with mounting nut 6-32UNC

C flange mounting, with rectangular aperture with mounting nut M3

F flange mounting, with round aperture with mounting nut M3

Configuration

0 without barrier

1 with small barrier

2 with large barrier (requested for multipole AC applications with approvals to UL 489, UL 1077, IEC)

Number of poles

1 single pole protected

2 two pole protected

3 three pole protected

4 four pole protected

Actuator configuration

A all poles with standard toggle

B reduced number of standard toggles

Z without actuator

Terminal design

P blade terminals ≤ 35 A

R round connectors 6 mm

U stud terminals M6 ≤ 125 A

V stud terminals 1/4-20UNC-3A ≤ 125 A

W laminated round terminals ≤ 125 A

Terminal hardware

0 without

3 with washer and nut

Characteristic curve

K1 short delay DC

M1 medium delay DC

M2 medium delay AC

T1 long delay DC

T2 long delay AC

Version

D standard

Colour configuration

B1 black actuator

Marking

front plate actuator base

B1 without ON-OFF

B2 I_N ON-OFF

Rated voltage

B AC or ≤ 80 V DC

C DC ≤ 80 V

AC ≤ 277 V

(only for configurations
0 and 1 for UL 1077)

Current ratings

0.05...125 A

higher current ratings

upon request

8345 - C 0 1 A - U 3 M1 - D B1 B1 B - 60 A ordering example

Ordering information for auxiliary contact module

Type number

X8345

Module

S auxiliary contact module

Auxiliary contacts

01 in all poles

02 in pole 1 only

Auxiliary contact version

K auxiliary contacts, tin-plated (symmetrical terminals)

Auxiliary contact function

W1 1 changeover

Terminal design

02 microswitch with blade terminals
DIN 46244-A2.8-0.5

M mounted to base unit

X8345 - S 01 K W1 02 M ordering example

Remote trip coil available to special order!

Ordering information for UL 489

Type No.
8345

Mounting

B flange mounting, with rectangular aperture with mounting nut 6-32UNC

C flange mounting, with rectangular aperture with mounting nut M3

F flange mounting, with round aperture with mounting nut M3

Configuration

0 without barrier for DC

1 with small barrier for DC (optional)

2 with large barrier for AC

Number of poles

1 single pole protected

2 two pole protected

Actuator configuration

A all poles with standard toggle

B reduced number of standard toggles

Z without actuator

Terminal design

P blade terminals ≤ 35 A

R round connectors 6 mm

U stud terminals M6 ≤ 125 A

V stud terminals 1/4-20UNC-3A ≤ 125 A

W laminated round terminals ≤ 125 A

Terminal hardware

0 without

3 with washer and nut

Characteristic curve

K1 short delay DC

M1 medium delay DC

M2 medium delay AC

T1 long delay DC

T2 long delay AC

Version

D standard

Colour configuration

B1 black actuator

Marking

front plate actuator base

B1 without ON-OFF

B2 I_N ON-OFF

Rated voltage

B AC or ≤ 80 V DC

Current ratings

0.05...125 A for DC

0.05...20 A for AC

higher current ratings

upon request

Approvals (optional)

V UL 489

8345 - C 0 1 A - U 3 M1 - D B1 B1 B - 60 A - . ordering example

Remote trip coil available to special order!

Ordering information for auxiliary contact module

Type number

X8345

Module

S auxiliary contact module

Auxiliary contacts

01 in all poles

02 in pole 1 only

Auxiliary contact version

K auxiliary contacts, tin-plated (symmetrical terminals)

Auxiliary contact function

W1 1 changeover

Terminal design

02 microswitch with blade terminals
DIN 46244-A2.8-0.5


M mounted to base unit

X8345 - S 01 K W1 02 M ordering example


Dimensions

Mounting version B/C

Flange mounting rectangular aperture




number of poles 1 to 4




mounting thread M3 or 6-32
all dimensions referred to the top edge
mounting depth 4.2 mm/.165 in.
max. insertion depth 5.5 mm
max. tightening torque 0.33 Nm

Cut-out dimensions:

1-pole




multipole




Mounting version F

Flange mounting round aperture




number of poles 1 to 4




mounting thread M3 or 6-32
all dimensions referred to the top edge
mounting depth 4.2 mm/.165 in.
max. insertion depth 5.5 mm
max. tightening torque 0.33 Nm

Cut-out dimensions:

1-pole




4-pole




max. panel thickness: 3 mm

Installation drawing




Terminal design / Dimensions

P - with blade terminals




R - round connectors


D = 6 mm (dia . 236) (version H) asymmetrical terminals (not for UL 489)




U/V - with auxiliary contacts (version H) asymmetrical terminals (not for UL 489)



auxiliary contacts version K symmetrical terminals




W - laminated round terminals




Internal connection diagrams


1-pole protected magnetically



1-pole protected hydraulic-magnetically




multipole




Typical time/current characteristics at +23 °C / +73.4 °F

(trip time at rated current and all poles symmetrically loaded)


Curve K1 (short delay) for DC




Curve M0 (medium delay) for AC/DC




Curve M1 (medium delay) for DC




Curve T1 (long delay) for DC



Curve M2 (medium delay) for AC 50/60 Hz



Curve T2 (long delay) for AC 50/60 Hz




All curves will only be maintained if the escutcheon is mounted on a vertical surface.


Other characteristic curves to special order (e. g. pulse delayed, for high inrush currents or capacitive loads).

Actuator configuration


A 1 toggle per pole, mounting version B/C




B reduced number of toggles per unit, mounting version B/C




Z without toggles



A 1 toggle per pole, mounting version F




B reduced number of toggles per unit, mounting version F




Interphase barriers / Dimensions

1 - Interphase barrier (small)



2 - Interphase barrier (large)



thickness 1mm / .039 in.



This is a metric design and millimeter dimensions take precedence (mm / inch)

All dimensions without tolerances are for reference only. In the interest of improved design, performance and cost effectiveness the right to make changes in these specifications without notice is reserved. Product markings may not be exactly as the ordering codes. Errors and omissions excepted.


Accessories

Splash cover (IP65) for 1-, 2-, 3-pole (only for mounting version B/C)


| | number of poles | mounting version | actuator configuration |
|--------------|-----------------|------------------|------------------------|
| X 222 444 01 | 1-pole | B | 1 |
| X 222 444 02 | 1-pole | C | 1 |
| X 222 444 11 | 2-pole | B | 2 |
| X 222 444 12 | 2-pole | C | 2 |
| X 222 444 21 | 3-pole | B | 3 |
| X 222 444 22 | 3-pole | C | 3 |



Toggle guard (only for mounting version B/C) Y 307 381 01



Shock directions



Description

A module which adds remote trip capability to all versions of type 8345. A voltage applied across the coil, by means of an external sensor for example, will cause disconnection of the main switch/circuit breaker mechanism.

Typical applications

Electrical monitoring of safety systems, remote trip.

Ordering information

| Type No. | |
|---|-----------------------------------|
| X8345 | Module for type 8345 |
| Module | |
| F | remote trip module |
| Assembly version | |
| 01 | only in pole 1 |
| 02 | only in pole 2 |
| Remote trip version | |
| X1 | DC |
| Voltage rating | |
| 24 | 24 V |
| 48 | 48 V |
| Terminal design | |
| 02 | blade terminals DIN 4644-A2.8-0.5 |
| M | module mounted to circuit breaker |
| X8345 - F 01 X1 24 02 M ordering example | |

Preferred types

NEW

Preferred types remote trip module:

X8345-F-01-X1-24-02-M
X8345-F-01-X1-48-02-M

Voltage ratings and typical internal resistance values


| Current rating (A) | Internal resistance (Ω) |
|--------------------|----------------------------------|
| DC 12 V | 3.4 |
| DC 24 V | 13.9 |
| DC 48 V | 64.3 |

This is a metric design and millimeter dimensions take precedence $\left(\frac{\text{mm}}{\text{inch}}\right)$

All dimensions without tolerances are for reference only. In the interest of improved design, performance and cost effectiveness the right to make changes in these specifications without notice is reserved. Product markings may not be exactly as the ordering codes. Errors and omissions excepted.


Dimensions

Additional remote trip module



Internal connection diagram

1-pole protected hydraulic-magnetically with additional remote trip coil



Technical data


| | |
|--|---|
| Voltage ratings | DC 12 V; DC 24 V; DC 48 V |
| Power consumption | approx. 40 W |
| Pulse operation | 20 ms < t _{ON} < 100 ms/t _{OFF} > 10 sec (Continuous duty possible for multipole devices upon request) |
| Typical life | 10,000 operations at U _N |
| Ambient temperature | -40...+85 °C (-40...+185 °F) |
| Insulation co-ordination (IEC 60664) | 2.5 kV/2 (EN 60934) |
| Dielectric strength between main circuit and trip coil circuit | test voltage AC 3,000 V (EN 60934) |
| Insulation resistance | > 100 M Ω (DC 500 V) |
| Vibration | 6 g (57-2000 Hz) \pm 0.46 mm (10-57 Hz) shock direction 1/2 4 g (57-2000 Hz) \pm 0.30 mm (10-57 Hz) shock direction 3/4 3 g (57-2000 Hz) \pm 0.23 mm (10-57 Hz) shock direction 5/6 to IEC 60068-2-6, test Fc 10 frequency cycles/axis |
| Shock | 100 g (11 ms) (not when mounted upside down) to IEC 60068-2-27, test Ea |
| Corrosion | 96 hours at 5 % salt mist, to IEC 60068-2-11, test Ka |
| Humidity | 240 hours at 95 % RH to IEC 60068-2-78, test Cab |
| Mass | approx. 8.5 g (without base unit) |

Description

The X8345-R is an additional module which provides remotely controlled ON and OFF functionality for the E-T-A series 8345 magnetic circuit breaker range. The module actuator, which is motor driven, is factory fitted adjacent to the circuit breaker(s) which it is controlling. The module can be operated by a suitable external changeover switch, momentary switches (one ON, one OFF) or logic system (not part of our product). The status of the actuator will follow the position of the external switch, i.e. if the circuit breaker trips electrically or is operated manually, the actuator will not change.

A single module will control a single pole breaker or multipole circuit breakers up to 2 poles. In the application it has to be ensured that the supply voltage is maintained at all times.

When switching the circuit breaker OFF manually the module has also to be switched off by means of the changeover switch before switching the breaker on again. The same is true for normal switch-on of the breaker.



X8345-R

Ordering information

Type number

X8345 Module for type 8345, 1 and 2 pole (3 pole upon request)

Module

R remote ON/OFF actuation

Operating voltage

12 DC 12 V

24 DC 24 V

Add-on version

01 mounted on right side

Mounting method

00 front panel mounting (standard)

02 2-bracket: module and circuit breaker fitted

Terminal design

01 spring loaded screwless terminal 5-pin

Supply status

M module mounted to the base unit

X8345 - R 24 01 00 01 M ordering example

Note: Bold-type, blue configurations are standard versions which are presently available.

Preferred types Remote-Control

NEW

X8345-R-24-01-00-01-M


X8345-R-24-01-02-01-M

Technical data


| | | |
|--------------------------------------|---|---------------------|
| Voltage rating | DC 12 V (9...16 V) | DC 24 V (16...32 V) |
| ON duty | 50 % / 60 sec | |
| Trip time | < 2 sec | |
| Blocking current | approx. 2 A | < 1.5 A |
| Control current | < 3 mA | |
| Typical life | 10,000 operations (ON/OFF) | |
| Ambient temperature | -25...70 °C (-13...158 °F) | |
| Insulation co-ordination (IEC 60664) | 2.5 kV/2 (EN 60934) | |
| Dielectric strength pole to module | test voltage AC 1,500 V (EN 60934) | |
| Insulation resistance | > 100 MΩ (DC 500 V) | |
| Vibration | 10 g (57-2000 Hz), ± 0,76 mm (10-57 Hz) to IEC 60068-2-6, test Fc, 10 frequency cycles/axis | |
| Shock | 100 g (11 ms) to IEC 60068-2-27, test Ea | |
| Corrosion | 96 hours at 5% salt mist, to IEC 60068-2-11, test Ka | |
| Humidity | 240 hours at 95 % RH, to IEC 60068-2-78, test Cab | |
| Mass | approx. 65 g (without base unit) | |

Internal connection diagrams

single pole, hydraulic-magnetic protection, with remote ON/OFF actuation (operated by changeover switch)





single pole, hydraulic-magnetic protection, with remote ON/OFF actuation (actuated by two momentary switches)



Typical applications


Remote circuit breaker control (ON/OFF) for communication systems, marine installations, automation equipment and similar requirements.

Dimensions




spring loaded
screwless terminal
5-pin

X8345-R-24-01-00-01-M



X8345-R-24-01-02-01-M



This is a metric design and millimeter dimensions take precedence (mm)
inch

All dimensions without tolerances are for reference only. In the interest of improved design, performance and cost effectiveness the right to make changes in these specifications without notice is reserved. Product markings may not be exactly as the ordering codes. Errors and omissions excepted.