

MMBD101/MMBD352/MMBD354/MMBD355

SURFACE MOUNT HIGH FREQUENCY SCHOTTKY DIODE

VOLTAGE 7.0 Volts **POWER** 250 mW

SOT-23

Unit : inch(mm)

FEATURES


- Low Capacitance, Minimizing Insertion Losses in VHF Applications
- Low V_F : 0.5V (Typ) at $I_F=10mA$
- Extremely Fast Switching Speed
- Lead free in comply with EU RoHS 2002/95/EC directives.
- Green molding compound as per IEC61249 Std. . (Halogen Free)

MECHANICAL DATA

Case : SOT-23, Plastic

Terminals : Solderable per MIL-STD-750, Method 2026

Approx weight : 0.0003 ounces, 0.0084 grams




MAXIMUM RATINGS

PARAMETER	SYMBOL	MMBD101	MMBD352	MMBD354	MMBD355	UNITS
Marking Code	-	101	352	354	355	-
Reverse Voltage	V_R	7				V
Forward Power Dissipation	P_F	250				mW
Junction Temperature Range	T_J	-55 to +125				°C
Storage Temperature Range	T_{STG}	-55 to +150				°C
Circuit Figure	-	SINGLE	SERIES	COMMON CATHODE	COMMON ANODE	-

THERMAL CHARACTERISTICS

PARAMETER	SYMBOL	VALUE	UNITS
Thermal Resistance , Junction to Ambient	R_{JA}	400	°C/W

Note 1. FR-5 Board = 1.0 x 0.75 x 0.062 in






MMBD101/MMBD352/MMBD354/MMBD355

ELECTRICAL CHARACTERISTICS ($T_A=25^{\circ}\text{C}$, unless otherwise noted)

PARAMETER	SYMBOL	TEST CONDITION	MIN.	TYP.	MAX.	UNITS
Reverse Breakdown Voltage	$V_{(BR)}$	$I_R=10\mu\text{A}$	7.0	10	-	V
Reverse Leakage Current	I_R	$V_R=3.0\text{V}$	-	-	0.25	μA
Forward Voltage	V_F	$I_F=10\text{mA}$	-	0.5	0.6	V
Total Capacitance	C_J	$f=1.0\text{MHz}$, $V_R=0\text{V}$	-	0.88	1.0	pF

ELECTRICAL CHARACTERISTICS CURVE




MMBD101/MMBD352/MMBD354/MMBD355

MOUNTING PAD LAYOUT

SOT-23

Unit : inch(mm)



ORDER INFORMATION

- Packing information

T/R - 12K per 13" plastic Reel

T/R - 3K per 7" plastic Reel

LEGAL STATEMENT

Copyright PanJit International, Inc 2012

The information presented in this document is believed to be accurate and reliable. The specifications and information herein are subject to change without notice. Pan Jit makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose. Pan Jit products are not authorized for use in life support devices or systems. Pan Jit does not convey any license under its patent rights or rights of others.



MMBD101/MMBD352/MMBD354/MMBD355

For example :

RB500V-40_R2_00001



Packing Code XX				Version Code XXXXXX		
Packing type	1 st Code	Packing size code	2 nd Code	HF or RoHS	1 st Code	2 nd ~5 th Code
T/B	A	N/A	0	HF	0	serial number
T/R	R	7"	1	RoHS	1	serial number
B/P	B	13"	2			
T/P	T	26mm	X			
TRR	S	52mm	Y			
TRL	L	PBCU	U			
FORMING	F	PBCD	D			

Part No_packing code_Version

MMBD101_R1_00001

MMBD101_R2_00001