

LSW SERIES

105°C 3000 hours, Screw Terminal Type

◆ **FEATURES**

- Load Life : 105°C 3000 hours.
- RoHS compliance.



◆ **SPECIFICATIONS**

Items	Characteristics																																																																																					
Category Temperature Range	-40~+105℃						-25~+105℃																																																																															
Rated Voltage Range	10~100V.DC						160~400V.DC																																																																															
Capacitance Tolerance	±20% (20℃,120Hz)																																																																																					
(tanδ) Dissipation Factor(MAX)	<table><tr><td>WV∖φD</td><td>36</td><td>51</td><td>64</td><td>77</td><td>90</td></tr><tr><td>10</td><td>0.75</td><td>1.0</td><td>1.3</td><td>1.5</td><td>1.5</td></tr><tr><td>16</td><td>0.6</td><td>0.7</td><td>0.8</td><td>1.0</td><td>1.0</td></tr><tr><td>25</td><td>0.4</td><td>0.5</td><td>0.7</td><td>0.8</td><td>0.8</td></tr><tr><td>35</td><td>0.3</td><td>0.5</td><td>0.6</td><td>0.7</td><td>0.7</td></tr><tr><td>50</td><td>0.25</td><td>0.3</td><td>0.5</td><td>0.6</td><td>0.6</td></tr></table>						WV∖φD	36	51	64	77	90	10	0.75	1.0	1.3	1.5	1.5	16	0.6	0.7	0.8	1.0	1.0	25	0.4	0.5	0.7	0.8	0.8	35	0.3	0.5	0.6	0.7	0.7	50	0.25	0.3	0.5	0.6	0.6	<table><tr><td>WV∖φD</td><td>36</td><td>51</td><td>64</td><td>77</td><td>90</td></tr><tr><td>63</td><td>0.2</td><td>0.25</td><td>0.3</td><td>0.4</td><td>0.4</td></tr><tr><td>80</td><td>0.2</td><td>0.2</td><td>0.25</td><td>0.3</td><td>0.3</td></tr><tr><td>100</td><td>0.15</td><td>0.2</td><td>0.25</td><td>0.25</td><td>0.25</td></tr><tr><td>160~250</td><td>0.15</td><td>0.15</td><td>0.2</td><td>0.2</td><td>0.2</td></tr><tr><td>315~400</td><td>0.2</td><td>0.2</td><td>0.25</td><td>0.25</td><td>0.25</td></tr></table>						WV∖φD	36	51	64	77	90	63	0.2	0.25	0.3	0.4	0.4	80	0.2	0.2	0.25	0.3	0.3	100	0.15	0.2	0.25	0.25	0.25	160~250	0.15	0.15	0.2	0.2	0.2	315~400	0.2	0.2	0.25	0.25	0.25	(20℃,) (120Hz)	
WV∖φD	36	51	64	77	90																																																																																	
10	0.75	1.0	1.3	1.5	1.5																																																																																	
16	0.6	0.7	0.8	1.0	1.0																																																																																	
25	0.4	0.5	0.7	0.8	0.8																																																																																	
35	0.3	0.5	0.6	0.7	0.7																																																																																	
50	0.25	0.3	0.5	0.6	0.6																																																																																	
WV∖φD	36	51	64	77	90																																																																																	
63	0.2	0.25	0.3	0.4	0.4																																																																																	
80	0.2	0.2	0.25	0.3	0.3																																																																																	
100	0.15	0.2	0.25	0.25	0.25																																																																																	
160~250	0.15	0.15	0.2	0.2	0.2																																																																																	
315~400	0.2	0.2	0.25	0.25	0.25																																																																																	
Leakage Current(MAX)	I=0.02CV or 5mA whichever is smaller. (After 5 minutes application of rated voltage) I=(μA)																																																																																					

◆ **MULTIPLIER FOR RIPPLE CURRENT**

Frequency Coefficient

(Hz) Frequency		60(50)	120	400	1k	10k≤
Coefficient	10~50WV	0.80	1.00	1.03	1.05	1.08
	63~100WV	0.80	1.00	1.05	1.07	1.10
	160~400WV	0.80	1.00	1.10	1.13	1.18

◆ **PART NUMBER**

LSW M D×L
 Rated Voltage Series Rated Capacitance Capacitance Tolerance Option Clamp Code Case Size

◆ **Dimensions in mm (not to scale)**

		(mm)						
		φD	W1	W2	W3	W4	W5	F
I type	36	24.0	30.0	3.5	7.0	10	12.7	
	51	34.0	40.0	3.5	6.0	12	21.8	
	64	40.0	45.0	4.5	7.0	12	28.2	
	77	47.0	53.0	4.5	6.0	12	31.4	
Y type	90	54.0	60.0	4.5	6.0	14	31.4	
	51	32.5	37.5	4.5	6.0	12	21.8	
	64	38.0	43.0	4.5	8.0	14	28.2	
	77	44.5	49.0	4.5	7.0	14	31.4	
	90	50.8	56.0	4.5	8.0	16	31.4	

※Please refer to page 145 about recommended tightening torque and permissible current of terminal.

◆STANDARD SIZE

WV Cap(μF)	10V		16V		25V		35V		50V		63V		80V	
3300													36×50	3.0
3900													36×63	3.3
4700											36×50	3.2	36×83	3.6
5600											36×63	3.5	36×83	3.9
6800							36×50	2.5	36×50	3.6	36×63	3.8	36×83	4.3
8200							36×50	2.8	36×63	3.9	36×83	4.3	36×98	5.1
10000							36×50	3.8	36×83	4.2	36×83	4.7	36×118	5.8
12000							36×63	4.3	36×83	5.0	36×98	5.6	51×83	7.0
15000					36×50	4.2	36×83	4.7	36×98	5.5	36×118	6.4	51×83	7.6
18000					36×63	4.6	36×83	5.1	36×98	5.7	51×83	7.5	51×98	7.7
22000			36×50	4.0	36×83	5.2	36×98	6.6	36×118	7.5	51×83	7.5	51×118	9.0
27000	36×50	4.4	36×63	5.0	36×83	5.4	36×118	6.7	51×83	7.5	51×98	8.7	64×99	10.1
33000	36×63	5.5	36×83	5.2	36×98	6.5	51×83	7.1	51×98	9.3	51×118	10.3	64×119	11.6
39000	36×63	6.0	36×83	5.8	36×98	7.5	51×83	8.4	51×98	9.4	64×99	11.2	64×139	13.5
47000	36×83	6.6	36×98	6.8	36×118	8.9	51×98	9.9	51×118	11.7	64×119	12.9	77×101	15.8
56000	36×83	7.5	36×98	6.9	51×83	10.0	51×98	10.3	64×99	12.4	64×139	15.2	77×121	17.0
68000	36×98	7.6	36×118	8.4	51×98	10.7	51×118	11.4	64×119	15.1	77×101	16.0	77×141	20.4
82000	36×118	9.0	51×83	8.4	51×98	12.0	64×99	12.5	77×101	15.5	77×121	17.7	77×151	21.5
100000	51×83	10.2	51×98	11.3	51×118	13.1	64×119	15.5	77×101	16.3	77×141	21.5	90×151	22.3
120000	51×83	11.0	51×98	11.4	64×99	13.7	77×101	15.5	77×121	19.1	90×141	22.4		
150000	51×98	13.4	51×118	12.5	64×119	16.4	77×121	17.9	77×141	23.4				
180000	51×118	14.0	64×99	14.2	77×101	16.7	77×141	20.0	90×141	23.7				
220000	64×99	14.5	64×119	16.6	77×121	20.5	77×151	24.1						
270000	64×119	16.0	77×101	17.5	77×141	21.3	90×141	26.5						
330000	77×101	18.0	77×121	24.3	77×151	26.0								
390000	77×101	19.5	77×141	25.2	90×141	27.2								
470000	77×121	20.0	77×151	26.7										
560000	77×141	24.1	90×141	29.1										
680000	90×141	26.5												

WV Cap(μF)	100V		160V		200V		250V		315V		350V		400V	
220											36×50	0.9	36×50	1.0
270									36×50	1.0	36×50	1.0	36×63	1.0
330									36×50	1.2	36×63	1.2	36×63	1.2
390									36×63	1.3	36×83	1.3	36×83	1.4
470							36×50	1.3	36×83	1.5	36×83	1.5	36×98	1.5
560					36×50	1.4	36×63	1.6	36×83	1.6	36×98	1.7	36×98	1.7
680					36×50	1.5	36×83	1.7	36×98	1.9	36×98	1.9	51×83	2.3
820			36×50	1.4	36×83	1.9	36×83	1.9	36×118	2.2	36×118	2.1	51×98	2.4
1000			36×63	1.9	36×83	2.2	36×98	2.3	51×83	2.3	51×98	2.5	51×118	2.7
1200			36×83	2.3	36×83	2.3	36×98	2.4	51×98	2.7	51×98	2.7	51×118	3.0
1500			36×83	2.6	36×98	2.9	36×118	2.9	51×98	3.1	51×118	3.3	64×99	3.5
1800			36×83	2.6	36×98	2.9	36×118	3.0	51×118	3.6	64×99	3.8	64×119	3.6
2200	36×50	2.9	36×98	3.2	36×118	3.3	51×98	3.8	64×99	4.2	64×119	4.6	77×101	4.1
2700	36×63	3.4	36×118	3.2	51×83	3.8	51×118	4.5	64×119	4.3	77×101	4.6	77×121	4.8
3300	36×83	3.9	36×118	3.7	51×98	4.7	64×99	5.2	77×101	4.9	77×121	5.3	77×141	5.7
3900	36×83	4.2	51×98	4.3	51×118	5.4	64×119	5.2	77×121	5.8	77×141	6.2	90×141	6.7
4700	36×83	4.6	51×98	4.8	64×99	6.2	64×119	5.7	77×121	6.3	90×141	7.4	90×141	7.4
5600	36×98	4.9	51×118	5.5	64×99	6.3	77×101	6.4	77×141	7.3	90×141	8.1		
6800	36×118	5.5	64×99	6.3	64×119	7.3	77×121	7.6	90×141	8.9				
8200	51×83	6.2	64×119	7.1	77×101	8.5	77×141	8.3						
10000	51×98	6.7	77×101	7.9	77×121	9.5	90×141	9.9						
12000	51×98	7.3	77×121	9.0	77×141	10.5	90×141	10.8						
15000	51×118	8.6	77×141	11.3	90×141	12.5								
18000	64×99	8.9	90×141	13.0	90×141	13.3								
22000	64×119	10.3	90×141	14.3										
27000	64×139	12.1												
33000	77×121	14.1												
39000	77×141	16.5												
47000	77×141	18.3												
56000	90×141	19.2												
68000	90×151	20.1												

↑ Ripple Current (A r.m.s./120Hz, 105°C)
↑ Case Size φD×L(mm)