

# 750-192 Flexible Metal-Core EMI/RFI Conduit with External Braid and Jacket




Series 75  
Metal-Core Conduit

**Flexible metal-core conduit plus a single shield of EMI/RFI braiding and jacket for environmental applications**



## How To Order



**Table I: Dash No./Dimensions**

| Dash No. | Glenair Brass |              | SST, Nickel/Iron |              |
|----------|---------------|--------------|------------------|--------------|
|          | A I.D.        | B O.D.       | A I.D.           | B O.D.       |
|          | Min           | Max          | Min              | Max          |
| 06       | .175 (4.45)   | .460 (11.7)  | .175 (4.45)      | .460 (11.7)  |
| 08       | .260 (6.60)   | .560 (14.2)  | .245 (6.22)      | .564 (14.3)  |
| 09       | .294 (7.47)   | .588 (14.9)  | .294 (7.47)      | .588 (14.9)  |
| 10       | .308 (7.82)   | .615 (15.6)  | .308 (7.82)      | .615 (15.6)  |
| 12       | .380 (9.65)   | .680 (17.3)  | .370 (9.40)      | .688 (17.5)  |
| 16       | .505 (12.8)   | .810 (20.6)  | .495 (12.6)      | .837 (21.3)  |
| 20       | .635 (16.1)   | .930 (23.6)  | .620 (15.7)      | .960 (24.4)  |
| 24       | .760 (19.3)   | 1.065 (27.0) | .745 (18.9)      | 1.080 (27.4) |
| 32       | 1.012 (25.7)  | 1.331 (33.8) | .995 (25.3)      | 1.400 (35.6) |
| 40       | 1.265 (32.1)  | 1.691 (43.0) | 1.245 (31.6)     | 1.662 (42.2) |
| 48       | 1.510 (38.4)  | 1.946 (49.4) | 1.495 (38.0)     | 1.912 (48.6) |
| 56       | 1.760 (44.7)  | 2.191 (55.7) | 1.760 (44.7)     | 2.183 (55.4) |
| 64       | 2.010 (51.1)  | 2.456 (62.4) | 1.995 (50.7)     | 2.422 (61.5) |
| 80       | 2.515 (63.9)  | 2.951 (75.0) | 2.495 (63.4)     | 2.922 (74.2) |
| 96       | 2.995 (76.1)  | 3.420 (86.9) | 2.995 (76.1)     | 3.412 (86.7) |

**Table II: Conduit Core**

| SYM | Core Material                        |
|-----|--------------------------------------|
| B   | Brass, Per A-A-52440 Type I, Grade B |
| C   | Stainless Steel                      |
| N   | 80% Nickel, 20% Iron                 |

**Table IV: Jacket**


| N  | Neoprene                        |
|----|---------------------------------|
| H  | Hypalon®                        |
| E  | EPDM                            |
| V  | Viton                           |
| B  | Duralectric, Black              |
| G  | Duralectric, Gray               |
| TN | Duralectric, Desert Tan         |
| O  | Duralectric, OSHA Safety Orange |

**Table III: Braided Shield**

| SYM | Shield/Braid                                            |
|-----|---------------------------------------------------------|
| B   | Bronze (Standard for Brass Core)                        |
| C   | Stainless Steel (Standard for SST and Nickel/Iron Core) |
| T   | Tin Copper                                              |
| N   | Nickel Copper                                           |
| S   | SnCuFe                                                  |
| A   | Silver Copper                                           |
| L   | Aarmorlite™                                             |
| D   | Dacron                                                  |
| M   | Nomex                                                   |
| E   | AmberStrand® 100%                                       |
| F   | AmberStrand® 75%/25%                                    |

**Std. Conduit Tolerances**

| Length (Inches) | Tolerance (Inches) |
|-----------------|--------------------|
| Up To 18        | ± .50              |
| 19 - 36         | ± 1.0              |
| 37 - 72         | ± 1.5              |
| 73 - 144        | ± 2.0              |
| 145 - 300       | ± 3.0              |
| 301 - 600       | ± 4.0              |
| 601 - 1200      | ± 5.0              |
| 1201 - Up       | ± 6.0              |



## Packaging

Long-length orders of 750-192 braided and jacketed conduit are subject to carrier weight and box size restrictions. For example, UPS air shipments are currently limited to 50 lbs. per box. Unless otherwise specified, Glenair standard practice is to ship optimal lengths of product based on weight, size, and individual carrier specifications. Consult factory for additional information or to specify packaging requirements.