

DATA SHEET
CL-L400-LC1N1-B



CITIZEN and **CITIZEN** are trademarks or registered trademarks of CITIZEN HOLDINGS CO., LTD. JAPAN.
CITILED is a trademark or a registered trademark of CITIZEN ELECTRONICS CO., LTD. JAPAN.

DATASHEET

1/12

1. Scope of Application

This data sheet is applied to the LED package, model CL-L400-LC1N1-B.

2. Part code

CL - L 4 0 0 - LC 1 N 1 - B
[1] [2] [3]

[1] Part Code

[2] CRI 70 min

[3] Correlated color temperature 5000K

< Features >


- External Dimensions 5.0 x 5.0 x 0.8
- Internal Structure Lead frame

- Luminous Flux: 129 lm @ 350 mA
- CCT: 5000K
- CRI: Ra 70 min
- Thermal Resistance: 9 C/W

- RoHS Compliant

Symbol	CITILED
Name	CL-L400-LC1N1-B
CITIZEN ELECTRONICS CO.,LTD. JAPAN	

3. Outline drawing



4. Performance

(1) Absolute Maximum Rating

Parameter	Symbol	Rating Value	Unit
Input Power	P _i	2.3	W
Forward Current	I _F	600	mA
Minimum current	I _F min	30	mA
Reverse Current	I _R	1	mA
Operating Temperature	T _{op}	-30 ~ +85	C
Storage Temperature	T _{st}	-40 ~ +100	C
oldering terminal Temperature	T _s	85	C
Junction Temperature	T _j	120	C

*1 Input power and forward current are the values when the LED is used within the range of the derating curve in this data sheet.

*2 Refer to 3. Outline drawing for T_s measurement point

*3 D.C. Current : T_j = T_s + R_{j-s} X P_i

Symbol	CITLED
Name	CL-L400-LC1N1-B
CITIZEN ELECTRONICS CO.,LTD. JAPAN	

DATASHEET

3/12


(2) Electro-optical Characteristics

T_c=25°C

Parameter	Symbol	Condition	Min.	Typ.	Max.	Unit
Forward Voltage	V _F	IF=350mA	2.75	3.01	3.35	V
Luminous Flux	Φ _v	IF=350mA	97	129	-	lm
CRI	R _a	IF=350mA	70	-	-	-
Thermal Resistance	R _{j-s}	Junction-Solder	-	9.0	-	C/W

Chromaticity coordinates (Condition : IF=350mA, T_s = 25°C)

	x	y
Center	0.3417	0.3475
a	0.3551	0.3760
b	0.3310	0.3562
c	0.3310	0.3220
d	0.3498	0.3357



Note: The tolerance of measurement at our tester is V_F±3% , Φ_v±10% , Chromaticity(x,y)±0.005 and R_a±1.


(3) Ranking information

Parameter	Symbol	Rank	Min	Max	Unit
Forward Voltage	VF	Q	2.75	2.95	V
		R	2.95	3.15	
		S	3.15	3.35	
Luminous Flux	φ _v	C	97	129	lm
		D	129	161	


Symbol	CITLED
Name	CL-L400-LC1N1-B
CITIZEN ELECTRONICS CO.,LTD. JAPAN	

5. Characteristics


Forward Current vs. Forward Voltage




Forward Current vs. Relative Luminous Flux



Forward Current vs. Chromaticity Coordinate



Solder Temperature vs. Chromaticity Coordinate




Symbol	CITLED
Name	CL-L400-LC1N1-B
CITIZEN ELECTRONICS CO.,LTD. JAPAN	


DATASHEET

5/12


Solder Temperature vs. Forward Voltage
IF=350mA




Solder Temperature vs. Relative Luminous Flux
IF=350mA





Solder Temperature vs. Allowable Forward Current Spectrum



T_s=25C, I_F =350 mA



Directive Characteristic



Symbol	CITLED
Name	CL-L400-LC1N1-B
CITIZEN ELECTRONICS CO.,LTD. JAPAN	

DATASHEET

6/12

6. Reliability

(1) Details of the tests

Test Item	Test Condition
Continuous Operation Test	IF=350mA Ta=25C × 1000 hours
Low Temperature Storage Test	-40 C × 1000 hours
High Temperature Storage Test	100 C × 1000 hours
Moisture-proof Test	85 C, 85 %RH for 500 hours
Thermal Shock Test	-40 C × 30 minutes – 100 C × 30 minutes, 100 cycle
Solder Heat Resistance Test	Recommended temperature profile (reflow soldering) x 2, (2nd test must be started after the samples are stabilized thermarly.)

(2) Judgement Criteria of Failure for Reliability Test

(Ta=25C)

Measuring Item	Symbol	Measuring Condition	Judgement Criteria for Failure
Forward Voltage	VF	IF=350mA	>U X 1.2
Total Luminous Flux	Φv	IF=350mA	<S X 0.7

U defines the upper limit of the specified characteristics. S defines the initial value.


Note : Measurement shall be taken between 2 hours and 24 hours, and the test pieces should be return to the normal ambient conditions after the completion of each test.

Symbol	CITILED
Name	CL-L400-LC1N1-B
CITIZEN ELECTRONICS CO.,LTD. JAPAN	

7. Taping Specifications


(1) Shape and dimensions of Reel

Unit:mm




(2) Dimensions of Career Tape

Unit:mm



(3) Configuration of Tape




(4) Quantity : 4000 pcs/reel

Symbol	CITLED
Name	CL-L400-LC1N1-B
CITIZEN ELECTRONICS CO.,LTD. JAPAN	

8. Packing Specifications

(1) Moisture proof packing

-To prevent moisture absorption during transportation and storage, reels are packed in aluminum envelopes which contain a desiccant with a humidity indicator.



(2) Storage

-To prevent moisture absorption, it is strongly recommended that reels (in bulk or taped) should be stored in the dry box (or the desiccator) with a desiccant as the appropriate storage place. If not, the following is recommended.

Temperature : 5-30 C
Humidity : 60%RH max

The devices should be mounted within 168H (7days) after unpacking.

If you store the unpacked reels, please store them in the dry box or seal them into the envelop again.

(3) Environmental conditions

-This device contain silver plated electrode. So, when being exposed to enviroment which contains corrosive gases, the silver plating becomes tarnished. Tarnished plating may lead to poor solderbility and degradation of optical characteristics.

-Please DO NOT expose this device to corrosive atomosphere anytime (during storage, after mounting). Please take care the above when designing your product.

-For outdoor use, necessary measures should be taken to prevent water, moisture and salt air damage.


-This product is NOT designed with following conditions in mind.
In water, oil, medicament, organic solvent and dust-laden environment.

Symbol	CITLED
Name	CL-L400-LC1N1-B
CITIZEN ELECTRONICS CO.,LTD. JAPAN	

9. Precautions


(1) Handling with care for this product

-The light emitting area is encapsulated with soft resin materials. Please avoid the resin area from being pressed, stressed, rubbed, come into contact with sharp metal nail because the function, performance and reliability of this product are negatively impacted.




-Please be aware that this product should not come into contact with any other parts while incorporating in your lighting apparatus or your other products.

-When pick and place this product, it is recommended that using the pick up nozzle with inner radius more than 4.4mm.



-Please avoid using narrow pick up nozzle, and pushing the resin area directly.

-Bending the circuit board with soldered LEDs may cause breakage of package. Please take care to bow, twist and warpage the PCB.



(2) Countermeasure against static electricity

-Handling of this product needs countermeasures against static electricity because this is a semiconductor product.

-Please take adequate measures to prevent any static electricity being produced such as the wearing of a wristband or anti-static gloves when handling this product.

-Every manufacturing facility in regard to the product (plant, equipment, machine, career machine and conveyance unit) should be connected to ground and please avoid the product to be electric-charged.

-ESD sensitivity of this product is over 1000V (HBM, based on JEITA ED-4701/304).

-After assembling the LEDs into your final products, it is recommended to check AB34 whether the assembled LEDs are damaged by static electricity (electrical leak phenomenon) or not.

-It is easy to find static damaged LED dies by a light-on test with the minimum current value.

Symbol	CITLED
Name	CL-L400-LC1N1-B
CITIZEN ELECTRONICS CO.,LTD. JAPAN	

9. Precautions (Continued)

(3) Thermal design

-The thermal design to draw heat away from the LED junction is most critical parameter for an LED illumination system. High operating temperatures at the LED junction adversely affect the performance of LED's light output and lifetime.
Therefore the LED junction temperature should not exceed the absolute maximum rating in LED illumination system.

-The LED junction temperature while operation of LED illumination system depends upon thermal resistance of internal LED package (R_j-s), outer thermal resistances of LED package, power loss and ambient temperature. Please take both of the thermal design specifications and ambient temperature conditions into consideration for the setting of driving conditions.

-For more information, please refer to application note "Thermal Management".

(4) Driving current

-A constant current is recommended as an applying driving current to this product.
In the case of constant voltage driving, please connect current-limiting resistor to each products in series and control the driving current to keep under the absolute maximum rating forward current value.

-Electrical transient might apply excess voltage, excess current and reverse voltage to the product(s).
They also affect negative impact on the product(s) therefore please make sure that no excess voltage, excess current and reverse voltage is applied to the product(s) when the LED driver is turn-on and/or turn-off.

-For more information, please refer to application note "Driving".

(5) Lighting at a minimum current value

-In a case where the minimum current (I_F min) is applied to the product, some of LED dice in the product might look different in their brightness due to the individual difference of the LED dice, and they are not failed.

Symbol	CITILED
Name	CL-L400-LC1N1-B
CITIZEN ELECTRONICS CO.,LTD. JAPAN	


9. Precautions (Continued)

(6) Soldering

-This product is adaptable to reflow process, and please use lead-free soldering.
Following soldering paste is recommended.


Melting temperature : 216 - 220 C.
Composition : Sn-3.5Ag-0.75Cu

-The temperature profile at the top surface of the parts is recommended as shown below.



-Next process of soldering should be carried out after the product has return to ambient temperature.

-Recommended soldering pattern is shown to the right, but mountability and solderability need to be optimized with actual conditions such as amount of solder, reflow temperature the process.



9) Eye Safety

-The International Electrical Commission (IEC) published in 2006 IEC 62471 "2006 Photobiological safety of lamps and lamp systems " which includes LEDs within its scope.

-When sorting single LEDs according to IEC 62471, almost all white LEDs can be classified as belonging to either Exempt Group (no hazard) or Risk Group 1 (low risk).

-However, Optical characteristics of LEDs such as radiant flux, spectrum and light distribution are factors that affect the risk group determination of the LED, and especially a high-power LED, that emits light containing blue wavelengths, might have properties equivalent to those of Risk Group 2 (moderate risk).

-Great care should be taken when directly viewing an LED that is driven at high current, has multiple uses as a module or when focusing the light with optical instruments, as these actions might greatly increase the hazard to your eyes.

-It is recommended to regard the evaluation of stand-alone LED packages as a reference and to evaluate your final product.

Symbol	CITLED
Name	CL-L400-LC1N1-B
CITIZEN ELECTRONICS CO.,LTD. JAPAN	

10. Precautions with regard to product use

- (1) This document is provided for reference purposes only so that CITIZEN ELECTRONICS' products are used as intended. CITIZEN ELECTRONICS neither makes warranties or representations with respect to the accuracy or completeness of the information contained in this document nor grants any license to any intellectual property rights or any other rights of CITIZEN ELECTRONICS or any third party with respect to the information in this document.
- (2) All information included in this document such as product data, diagrams, charts, is current as of the date this document is issued.
Such information, however, is subject to change without any prior notice.
Before purchasing or using any CITIZEN ELECTRONICS' products listed in this document, please confirm the latest product information with a CITIZEN ELECTRONICS' sales office, and formal specifications must be exchanged and signed by both parties prior to mass production.
- (3) CITIZEN ELECTRONICS has used reasonable care in compiling the information included in this document, but CITIZEN ELECTRONICS assumes no liability whatsoever for any damages incurred as a result of errors or omissions in the information included in this document.
- (4) Absent a written signed agreement, except as provided in the relevant terms and conditions of sale for product, and to the maximum extent allowable by law, CITIZEN ELECTRONICS assumes no liability whatsoever, including without limitation, indirect, consequential, special, or incidental damages or loss, including without limitation, loss of profits, loss of opportunities, business interruption and loss of data, and disclaims any and all express or implied warranties and conditions related to sale, use of product, or information, including warranties or conditions of merchantability, fitness for a particular purpose, accuracy of information, or no infringement.
- (5) Though CITIZEN ELECTRONICS works continually to improve products' quality and reliability, products can malfunction or fail. Customers are responsible for complying with safety standards and for providing adequate designs and safeguards to minimize risk and avoid situations in which a malfunction or failure of a product could cause loss of human life, bodily injury or damage to property, including data loss or corruption.
In addition, customers are also responsible for determining the appropriateness of use of any information contained in this document such as application cases not only with evaluating by their own but also by the entire system.
CITIZEN ELECTRONICS assumes no liability for customers' product design or applications.
- (6) Please contact CITIZEN ELECTRONICS' sales office if you have any questions regarding the information contained in this document, or if you have any other inquiries.

CITIZEN Micro HumanTech is a registered trademark of Citizen Holding Co., Japan.

CITILED is a registered trademark of CITIZEN ELECTRONICS CO., LTD. Japan

Symbol	CITILED
Name	CL-L400-LC1N1-B
CITIZEN ELECTRONICS CO.,LTD. JAPAN	