


## PNP SILICON POWER SWITCHING TRANSISTOR

2N3868


 TO-39  
 Metal Can Package

Designed for High Speed, Medium Current Switching and High Frequency Amplifier Applications

## ABSOLUTE MAXIMUM RATINGS

DESCRIPTION	SYMBOL	VALUE	UNITS
Collector Emitter Voltage	$V_{CEO}$	60	V
Collector Base Voltage	$V_{CBO}$	60	V
Emitter Base Voltage	$V_{EBO}$	4.0	V
Collector Current - Continuous Peak	$I_C$	3.0 10	A A
Base Current	$I_B$	0.5	A
Power Dissipation at $T_c=25^\circ\text{C}$	$P_D$	6.0	W
Derate Above $25^\circ\text{C}$		34.3	mW/ $^\circ\text{C}$
Power Dissipation at $T_a=25^\circ\text{C}$	$P_D$	1.0	W
Derate Above $25^\circ\text{C}$		5.71	mW/ $^\circ\text{C}$
Operating And Storage Junction Temperature Range	$T_j, T_{stg}$	- 65 to +200	$^\circ\text{C}$


## THERMAL CHARACTERISTICS

Junction to Case	$R_{th} (j-c)$	29	$^\circ\text{C/W}$
Junction to Ambient in free air	$R_{th} (j-a)$	175	$^\circ\text{C/W}$

 ELECTRICAL CHARACTERISTICS ( $T_c=25^\circ\text{C}$  unless specified otherwise)

DESCRIPTION	SYMBOL	TEST CONDITION	MIN	MAX	UNITS
Collector Emitter Voltage	$V_{CEO}$	$I_C=1\text{mA}, I_B=0$	60		V
Collector Base Voltage	$V_{CBO}$	$I_C=100\mu\text{A}, I_E=0$	60		V
Emitter Base Voltage	$V_{EBO}$	$I_E=100\mu\text{A}, I_C=0$	4.0		V
Collector Cut Off Current	$I_{CEX}$	$V_{CE}=60\text{V}, V_{BE(\text{off})}=2\text{V}$		1.0	$\mu\text{A}$
Collector Cut off Current	$I_{CBO}$	$V_{CB}=60\text{V}, I_E=0, T_c=150^\circ\text{C}$		150	$\mu\text{A}$
DC Current Gain	$h_{FE}$	$I_C=500\text{mA}, V_{CE}=1\text{V}$ $I_C=1.5\text{A}, V_{CE}=2\text{V}$ $I_C=2.5\text{A}, V_{CE}=3\text{V}$ $I_C=3\text{A}, V_{CE}=5\text{V}$	35 30 20 20	150	
Collector Emitter Saturation Voltage	$V_{CE(\text{sat})}$	$I_C=500\text{mA}, I_B=50\text{mA}$ $I_C=1.5\text{A}, I_B=150\text{mA}$ $I_C=2.5\text{A}, I_B=250\text{mA}$		0.50 0.75 1.30	V
Base Emitter Saturation Voltage	$V_{BE(\text{sat})}$	$I_C=500\text{mA}, I_B=50\text{mA}$ $I_C=1.5\text{A}, I_B=150\text{mA}$ $I_C=2.5\text{A}, I_B=250\text{mA}$	0.9	1.0 1.4 2.0	V

 \*Pulse Test: Pulse Width  $\leq 300\mu\text{s}$ , Duty Cycle  $\leq 2\%$

ELECTRICAL CHARACTERISTICS ( $T_c=25^\circ C$  unless specified otherwise)

## DYNAMIC CHARACTERISTICS

DESCRIPTION	SYMBOL	TEST CONDITION	MIN	MAX	UNITS
Current Gain Bandwidth Product	** $f_T$	$I_C=100mA, V_{CE}=5V, f=20MHz$	60		MHz
Output Capacitance	$C_{ob}$	$V_{CB}=10V, I_E=0, f=0.1MHz$		120	pF
Input Capacitance	$C_{ib}$	$V_{EB}=3V, I_C=0, f=0.1MHz$		1000	pF


## SWITCHING CHARACTERISTICS

Delay Time	$t_d$	$V_{CC}=30V, V_{BE(off)}=0, I_C=1.5A, I_{B1}=150mA$		35	ns
Rise Time	$t_r$			65	ns
Storage Time	$t_s$	$V_{CC}=30V, I_C=1.5A, I_{B1}=I_{B2}=150mA$		325	ns
Fall Time	$t_f$			75	ns

\*\*  $f_T = I_{hfe} \cdot f_{test}$ 


2N3868Rev031105E

## TO-39 Metal Can Package



DIM	MIN	MAX
A	8.50	9.39
B	7.74	8.50
C	6.09	6.60
D	0.40	0.53
E	—	0.88
F	2.41	2.66
G	4.82	5.33
H	0.71	0.86
J	0.73	1.02
K	12.70	—
L	42 DEG	48 DEG

All dimensions are in mm



PIN CONFIGURATION  
 1. Emitter  
 2. Base  
 3. Collector

## Packing Detail

PACKAGE	STANDARD PACK		INNER CARTON BOX		OUTER CARTON BOX		
	Details	Net Weight/Qty	Size	Qty	Size	Qty	Gr Wt
TO-39	500 pcs/polybag	540 gm/500 pcs	3" x 7.5" x 7.5"	20K	17" x 15" x 13.5"	32K	40 kgs

## Component Disposal Instructions

1. CDIL Semiconductor Devices are RoHS compliant, customers are requested to please dispose as per prevailing Environmental Legislation of their Country.
2. In Europe, please dispose as per EU Directive 2002/96/EC on Waste Electrical and Electronic Equipment (WEEE).

**Disclaimer**

The product information and the selection guides facilitate selection of the CDIL's Semiconductor Device(s) best suited for application in your product(s) as per your requirement. It is recommended that you completely review our Data Sheet(s) so as to confirm that the Device(s) meet functionality parameters for your application. The information furnished on the CDIL Web Site/CD are believed to be accurate and reliable. CDIL however, does not assume responsibility for inaccuracies or incomplete information. Furthermore, CDIL does not assume liability whatsoever, arising out of the application or use of any CDIL product; neither does it convey any license under its patent rights nor rights of others. These products are not designed for use in life saving/support appliances or systems. CDIL customers selling these products (either as individual Discrete Semiconductor Devices or incorporated in their end products), in any life saving/support appliances or systems or applications do so at their own risk and CDIL will not be responsible for any damages resulting from such sale(s).

CDIL strives for continuous improvement and reserves the right to change the specifications of its products without prior notice.



CDIL is a registered Trademark of  
Continental Device India Limited

C-120 Naraina Industrial Area, New Delhi 110 028, India.

Telephone + 91-11-2579 6150, 5141 1112 Fax + 91-11-2579 5290, 5141 1119  
email@cdil.com www.cdilsemi.com