


4.6 mm Round Type LED, Viewing Angle - 36°

42B Series



Electrical Characteristics							
Part No.	Chip Material	Emitted Colour	Lens Colour	Wave Length	Electro - Optical		
					Characterstics (I _f = 20mA)		
				λP (nm)	V _f (v)		I _v (mcd)
					Typ.	Max	
42B70D-4001	GaP/GaP	Hi-Red	Red Diffused	700	1.8	2.6	3
42B70T-4001	GaP/GaP	Hi-Red	Red Transparent	700	1.8	2.6	12
42B71D-4001	GaAsP/GaP	Hi-Eff Red	Red Diffused	640	1.8	2.6	500
42B71T-4001	GaAsP/GaP	Hi-Eff Red	Red Transparent	640	1.8	2.6	250
42B41D-4001	GaP/GaP	Yellow Green	Green Diffused	570	1.8	2.6	50
42B41T-4001	GaP/GaP	Yellow Green	Green Transparent	570	1.8	2.6	200
42B51D-4001	GaAsP/GaP	Yellow	Yellow Diffused	585	1.8	2.6	50
42B51T-4001	GaAsP/GaP	Yellow	Yellow Transparent	585	1.8	2.6	200
42B61D-4001	GaAsP/GaP	Orange	Orange Diffused	605	1.8	2.6	50
42B61T-4001	GaAsP/GaP	Orange	Orange Transparent	605	1.8	2.6	200
42B11D-4001	GaN	Blue	Blue Diffused	470	2.6	3.8	500
42B11C-4001	GaN	Blue	Water	470	2.6	3.8	2000
42B22C-4001	GaN	Blue Green	Water	505	2.6	3.8	10000
42B32C-4001	GaN	Green	Water	525	2.6	3.8	10000
42B82C-4001	GaN	White	Water		2.6	3.8	8000
42B82W-4001	GaN	White	Water Diffused		2.6	3.8	1000

42B_LEDRev100506D

Electrical Parameter (at T _a = 25°C)						
Colour	Reverse Voltage V _r (v)	Forward Current I _f (mA)	Forward Current Peak I _{fp} * (mA)	Power Pd (mW)	Operating Temp T _{opr} (°C)	Storage Temp T _{stg} (°C)
Green (GaP)	6	25	100	80	-25 ~ +80	-40 ~ +40
Red (GaP)	6	25	100	80	-25 ~ +80	-40 ~ +40
Orange (GaAsP/GaP)	6	25	100	80	-25 ~ +80	-40 ~ +40
Yellow (GaAsP/GaP)	6	25	100	80	-25 ~ +80	-40 ~ +40
Ultra Yellow (AlGaInP)	6	30	100	80	-25 ~ +80	-40 ~ +40
Ultra Orange (AlGaInP)	6	30	100	80	-25 ~ +80	-40 ~ +40
Ultra Red (AlGaInP)	6	30	100	80	-25 ~ +80	-40 ~ +40
Ultra Yellow Green	6	30	100	80	-25 ~ +80	-40 ~ +40
Blue (GaN/SiC)	6	30	100	170	-25 ~ +80	-40 ~ +40
* 1/10 Duty Cycle. 0.1 ms Pulse Width						

Soldering Instructions						
Types	DIP and Wave Soldering			Iron Soldering (1.5 mm Iron Tip)		
	Temp of Soldering Bath	Max Soldering Time	Distance from Solder Joint to Case	Temp of Soldering Iron	Max Soldering Time	Distance from Solder to case
LEDs	≤ 260 °C	3S	>2mm	≤ 300 °C	3S	>2mm
	≤ 260 °C	5S	>4mm	≤ 300 °C	5S	>4mm

Component Disposal Instructions

1. All Devices are RoHS compliant, customers are requested to please dispose as per prevailing Environmental Legislation of their Country.
2. In Europe, please dispose as per EU Directive 2002/96/EC on Waste Electrical and Electronic Equipment (WEEE).

Disclaimer

The product information and the selection guides facilitate selection of the next LEDs best suited for application in your product(s) as per your requirement. It is recommended that you completely review our Data Sheet(s) so as to confirm that the LED(s) meet functionality parameters for your application. The information furnished in the Data Sheet and on the CDIL Web Site/CD are believed to be accurate and reliable. CDIL however, does not assume responsibility for inaccuracies or incomplete information. Furthermore, CDIL does not assume liability whatsoever, arising out of the application or use of any CDIL product; neither does it convey any license under its patent rights nor rights of others. These products are not designed for use in life saving/support appliances or systems. CDIL customers selling these products (either as individual LEDs or incorporated in their end products), in any life saving/support appliances or systems or applications do so at their own risk and CDIL will not be responsible for any damages resulting from such sale(s). CDIL strives for continuous improvement and reserves the right to change the specifications of its products without prior notice.



CDIL is a registered Trademark of
Continental Device India Limited

C-120 Naraina Industrial Area, New Delhi 110 028, India.
Telephone + 91-11-2579 6150, 4141 1112 Fax + 91-11-2579 5290, 4141 1119
email@cdil.com www.cdilsemi.com